
Graviti

Graviti

Feb 28, 2023

GETTING STARTED

1	What can Graviti SDK do?	3
1.1	Installation	3
1.2	10 Minutes to Graviti	3
1.3	Upload Dataset	6
1.4	Dataset Management	8
1.5	Version Control	9
1.6	Sheet Management	17
1.7	Action Managemanet	33
1.8	Binary Files	36
1.9	Search	43
1.10	Pandas Integration	46
1.11	graviti	49
	Python Module Index	245
	Index	247

As a platform for unstructured data management, [Graviti](#) provides services in data hosting, version control, data visualization, and collaboration. Users can also integrate Graviti Data Platform into your own pipeline using developer tools.

WHAT CAN GRAVITI SDK DO?

Graviti Python SDK is a python library to access Graviti workspace and manage datasets. It provides a pythonic way to access datasets by Graviti OpenAPI.

1.1 Installation

Graviti SDK can be installed with pip or from source.

1.1.1 Pip

To install Graviti SDK with pip, run the following command:

```
$ pip3 install graviti
```

1.1.2 Source

To install Graviti SDK from source, clone the repository from [github](https://github.com/Graviti-AI/graviti-python-sdk):

```
$ git clone https://github.com/Graviti-AI/graviti-python-sdk.git
$ cd graviti-python-sdk
$ pip install -e .
```

1.2 10 Minutes to Graviti

This is a simple introductory tutorial for beginners.

1.2.1 Get an AccessKey

Before using Graviti SDK, please visit [Graviti Developer Tools](#) to get an AccessKey.

1.2.2 Dataset Preparation

This step is only for users who do not have datasets in their workspace. By running the code below, users can create a very simple dataset to experience Graviti SDK.

```
from graviti import DataFrame, Workspace
import graviti.portex as pt

ws = Workspace(f"{YOUR_ACCESSKEY}")
ds = ws.datasets.create("Graviti-dataset-demo")

std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main")
schema = pt.record(
    {
        "filename": pt.string(),
        "box2ds": pt.array(
            std.label.Box2D(
                categories=["boat", "car"],
                attributes={
                    "difficult": pt.boolean(),
                    "occluded": pt.boolean(),
                },
            ),
        ),
    }
)

filenames = ["a.jpg", "b.jpg", "c.jpg"]
data = []
for filename in filenames:
    row_data = {
        "filename": filename,
        "box2ds": [
            {
                "xmin": 1,
                "ymin": 1,
                "xmax": 4,
                "ymax": 5,
                "category": "boat",
                "attribute": {
                    "difficult": False,
                    "occluded": False,
                },
            },
        ],
    }
    data.append(row_data)

ds["train"] = DataFrame(data, schema)
ds.commit("Commit-1")
```

1.2.3 Get a Dataset

Workspace initialization:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")
```

List datasets on the workspace:

```
>>> ws.datasets.list()
LazyPagingList [
  Dataset("graviti-example/Graviti-dataset-demo")
]
```

Get one dataset:

```
>>> ds = ws.datasets.get("Graviti-dataset-demo")
>>> ds
Dataset("graviti-example/Graviti-dataset-demo")(
  (alias): '',
  (default_branch): 'main',
  (created_at): 2022-07-20 04:22:35+00:00,
  (updated_at): 2022-07-20 04:23:45+00:00,
  (is_public): False,
  (storage_config): 'AmazonS3-us-west-1'
)
```

1.2.4 Get a Sheet

```
>>> ds["train"]
  filename  box2ds
0  a.jpg    DataFrame(1, 6)
1  b.jpg    DataFrame(1, 6)
2  c.jpg    DataFrame(1, 6)
```

1.2.5 Get the Data

Get the DataFrame:

```
>>> df = ds["train"]
>>> df
  filename  box2ds
0  a.jpg    DataFrame(1, 6)
1  b.jpg    DataFrame(1, 6)
2  c.jpg    DataFrame(1, 6)
```

View the schema of the sheet:

```
>>> df.schema
record(
```

(continues on next page)

(continued from previous page)

```

fields={
  'filename': string(),
  'box2ds': array(
    items=label.Box2D(
      coords=float32(),
      categories=['boat', 'car'],
      attributes={
        'difficult': boolean(),
        'occluded': boolean(),
      },
    ),
  ),
},
)

```

Get the data by rows or columns:

```

>>> df.iloc[0]
filename    a.jpg
box2ds      DataFrame(1, 6)

```

```

>>> df["box2ds"]
0    DataFrame(1, 6)
1    DataFrame(1, 6)
2    DataFrame(1, 6)

```

```

>>> df.iloc[0]["box2ds"]
   xmin  ymin  xmax  ymax  category  attribute  difficult  occluded
0   1.0   1.0   4.0   5.0    boat      False      False      False

```

```

>>> df["box2ds"][0]
   xmin  ymin  xmax  ymax  category  attribute  difficult  occluded
0   1.0   1.0   4.0   5.0    boat      False      False      False

```

1.3 Upload Dataset

This is a simple guide to uploading a dataset.

1.3.1 Create or Get a Dataset

Create a new dataset:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")
dataset = ws.datasets.create("Graviti-dataset-demo")
```

Or get an existing dataset:

```
dataset = ws.datasets.get("Graviti-dataset-demo")
```

1.3.2 DataFrame Preparation

Users need to organize the data into *DataFrame* format with *Schema*. In addition, SDK also supports uploading different kinds of *Binary Files*, such as image, audio, etc.

```
from graviti import DataFrame
from graviti.file import Image
import graviti.portex as pt

std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main")
box2ds = std.label.Box2D(
    categories=["boat", "car"],
    attributes={
        "difficult": pt.boolean(),
        "occluded": pt.boolean(),
    },
)
schema = pt.record(
    {
        "filename": pt.string(),
        "image": std.file.Image(),
        "box2ds": pt.array(box2ds),
    }
)

filenames = ["a.jpg", "b.jpg", "c.jpg"]
data = []
for filename in filenames:
    row_data = {
        "filename": filename,
        "image": Image(f"PATH/TO/{filename}"),
        "box2ds": [
            {
                "xmin": 1,
                "ymin": 1,
                "xmax": 4,
                "ymax": 5,
                "category": "boat",
                "attribute": {
```

(continues on next page)

(continued from previous page)

```

        "difficult": False,
        "occluded": False,
    },
    },
],
}
data.append(row_data)
df = DataFrame(data=data, schema=schema)

```

1.3.3 Upload and Commit

Create or modify the sheet by uploading the dataframe, more details about sheet can be viewed in [Sheet Management](#).

```

dataset["train"] = df
dataset.commit("Commit-1")

```

The method `commit()` actually includes creating, uploading and committing the draft.

Interested users can learn more about dataset version management in [Version Control](#), which can also help troubleshooting when uploads fail.

1.4 Dataset Management

Dataset is the most basic concept in Graviti SDK. Almost all operations require a dataset first. Of course, it is necessary to initialize a Workspace before managing the dataset:

```

from graviti import Workspace
ws = Workspace(f"{YOUR_ACCESSKEY}")

```

1.4.1 Create a Dataset

SDK provides method `create()` to support creating a dataset based on the given name:

```
ws.datasets.create(f"{DATASET_NAME}")
```

In addition to name, alias and storage config can also be specified:

```
ws.datasets.create(f"{DATASET_NAME}", f"{DATASET_ALIAS}", f"{STORAGE_CONFIG}")
```

Note: Unlike the operation on the web page, here SDK will not create an empty draft after creating the dataset.

1.4.2 List Datasets

SDK provides method `list()` to support listing datasets on the workspace:

```
ws.datasets.list()
```

1.4.3 Get a Dataset

SDK provides method `get()` to support getting a dataset by name:

```
ws.datasets.get(f"{DATASET_NAME}")
```

1.4.4 Delete a Dataset

SDK provides method `delete()` to support deleting a dataset by name:

```
ws.datasets.delete(f"{DATASET_NAME}")
```

1.4.5 Edit the Dataset

SDK provides method `edit()` to support changing the name, alias and default branch of the dataset.

```
dataset = ws.datasets.get(f"{DATASET_NAME}")
dataset.edit(
    name=f"{NEW_DATASET_NAME}",
    alias=f"{NEW_ALIAS}",
    default_branch=f"{NEW_DEFAULT_BRANCH}"
)
```

1.5 Version Control

Version control is one of the important features of Graviti. It can help teams or individual users develop datasets in parallel and trace the history of the data.

1.5.1 HEAD

SDK supports viewing the version of the dataset through property `HEAD`:

```
>>> from graviti import Workspace
>>> ws = Workspace(f"{YOUR_ACCESSKEY}")
>>> dataset = ws.datasets.get("Graviti-dataset-demo")
>>> dataset.HEAD
Branch("main")(
  (commit_id): '47293b32f28c4008bc0f25b847b97d6f',
  (parent): None,
  (title): 'Commit-1',
  (committer): 'graviti-example',
```

(continues on next page)

(continued from previous page)

```

    (committed_at): 2022-07-20 04:23:45+00:00
)
>>> dataset.HEAD.name
"main"
>>> dataset.HEAD.commit_id
"47293b32f28c4008bc0f25b847b97d6f"

```

1.5.2 Checkout

SDK provides method `checkout()` to support switching the version of the dataset. This method will modify the HEAD of the dataset and discard the previous modification on the dataset.

Checkout the Branch("dev"):

```

>>> from graviti import Workspace
>>> ws = Workspace(f"{YOUR_ACCESSKEY}")
>>> dataset = ws.datasets.get("Graviti-dataset-demo")
>>> dataset.HEAD
Branch("main")(
  (commit_id): '47293b32f28c4008bc0f25b847b97d6f',
  (parent): None,
  (title): 'Commit-1',
  (committer): 'graviti-example',
  (committed_at): 2022-07-20 04:23:45+00:00
)
>>> dataset.checkout("dev")
Branch("dev")(
  (commit_id): '781007a41d1641859c87cb00f8e32bf3',
  (parent): Commit("3db73ac2876a42c0bf43a0489ce1756a"),
  (title): 'commit-5',
  (committer): 'graviti-example',
  (committed_at): 2022-07-19 04:23:45+00:00
)

```

Checkout the Tag("v1.0"):

```

>>> dataset.checkout("v1.0")
Tag("v1.0")(
  (commit_id): '2cd44960e0bf486c950536f7eeebc482',
  (parent): Commit("e8dc893eb2344b9a98bddce71a1c0eab"),
  (title): 'commit-7',
  (committer): 'graviti-example',
  (committed_at): 2022-07-19 04:25:45+00:00
)

```

Checkout the Commit("2cd4496"):

```

>>> dataset.checkout("2cd44960e0bf486c950536f7eeebc482")
Commit("2cd44960e0bf486c950536f7eeebc482")(
  (parent): Commit("e8dc893eb2344b9a98bddce71a1c0eab"),
  (title): 'commit-7',
  (committer): 'graviti-example',

```

(continues on next page)

(continued from previous page)

```
(committed_at): 2022-07-19 04:25:45+00:00
)
```

1.5.3 More Details

More details about the version control methods are as follows:

Commit

Commit is the basic element of Graviti version control system. Each commit of the dataset represents a **read-only** version.

The following sections will introduce the operations related to commits in the SDK. First of all, it is necessary to get a dataset:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")
dataset = ws.datasets.get(f"{DATASET_NAME}")
```

List Commits

SDK provides method *list()* to support listing commits preceding the given revision. The revision can be one commit ID:

```
dataset.commits.list(f"{COMMIT_ID}")
```

Or the branch name:

```
dataset.commits.list(f"{BRANCH_NAME}")
```

Or the tag name:

```
dataset.commits.list(f"{TAG_NAME}")
```

If no revision is specified, all commits preceding the current commit will be returned:

```
dataset.commits.list()
```

Get a Commit

SDK provides method *get()* to support getting a commit by revision. The revision can be one commit ID:

```
dataset.commits.get(f"{COMMIT_ID}")
```

Or the branch name:

```
dataset.commits.get(f"{BRANCH_NAME}")
```

Or the tag name:

```
dataset.commits.get(f"{TAG_NAME}")
```

If no revision is specified, the current commit of dataset will be returned:

```
dataset.commits.get()
```

Checkout Commit

SDK provides method `checkout()` to support switching the version of the dataset by commits:

```
dataset.checkout(f"{COMMIT_ID}")
```

Branch

Each dataset is created with a default branch `main`. When getting a dataset through the SDK, its version is the latest commit of the default branch.

The following sections will introduce the operations and precautions related to branches in the SDK. Of course, it is necessary to get a dataset first:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")
dataset = ws.datasets.get(f"{DATASET_NAME}")
```

Note: In most cases, a branch can be thought of as a named commit. But if there is a dataset that has just been created and has no commit history, the commit id of its default branch is `None`.

Create a Branch

SDK provides method `create()` to support creating a branch based on a revision. The revision can be one commit ID:

```
dataset.branches.create(f"{BRANCH_NAME}", f"{COMMIT_ID}")
```

The revision can also be the branch name. In this situation, the new branch will be created based on the latest commit of the source branch:

```
dataset.branches.create(f"{BRANCH_NAME}", f"{SOURCE_BRANCH_NAME}")
```

The revision can also be the tag name:

```
dataset.branches.create(f"{BRANCH_NAME}", f"{TAG_NAME}")
```

If no revision is specified, the created branch will be based on the current commit of the dataset:

```
dataset.branches.create(f"{BRANCH_NAME}")
```

List Branches

SDK provides method `list()` to support listing branches:

```
dataset.branches.list()
```

Get a Branch

SDK provides method `get()` to support getting a branch by name:

```
dataset.branches.get(f"{BRANCH_NAME}")
```

Delete a Branch

SDK provides method `delete()` to support deleting a branch by name:

```
dataset.branches.delete(f"{BRANCH_NAME}")
```

Checkout Branch

SDK provides method `checkout()` to support switching the version of the dataset by branches:

```
dataset.checkout(f"{BRANCH_NAME}")
dataset.HEAD # Check whether the dataset version is correct.
```

In addition, this checkout method is often used to update the version of the local dataset without getting the dataset again, for example:

```
# Other users committed a draft on the Branch("main").
dataset.checkout("main") # Update the version of the dataset.
```

Draft

All operations related to modifying data require a draft first. `Draft` can be viewed as a writable dataset in SDK.

The following sections will introduce the operations and precautions related to drafts in the SDK. Of course, it is necessary to get a dataset first:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")
dataset = ws.datasets.get(f"{DATASET_NAME}")
```

Create a Draft

SDK provides method `create()` to support creating a draft based on a branch:

```
dataset.drafts.create(f"{DRAFT_TITLE}", branch=f"{BRANCH_NAME}")
```

If no branch is specified, the created draft will be based on the current branch of the dataset:

```
dataset.drafts.create(f"{DRAFT_TITLE}")
```

In addition to title, it is also allowed to add description to the draft:

```
dataset.drafts.create(f"{DRAFT_TITLE}", f"{DRAFT_DESCRIPTION}")
```

Important: Graviti use number, not title, to uniquely identify drafts.

List Drafts

SDK provides method `list()` to support listing drafts. Drafts can be filtered by state including OPEN, COMMITTED, CLOSED and ALL:

```
dataset.drafts.list(f"{STATE}")
```

Drafts can also be filtered by the branch name:

```
dataset.drafts.list(branch=f"{BRANCH_NAME}")
```

If neither the state nor the branch name is specified, then all open drafts on all branches will be returned:

```
dataset.drafts.list()
```

Get a Draft

SDK provides method `get()` to support getting a draft by number:

```
dataset.drafts.get(DRAFT_NUMBER)
```

Edit the Draft

SDK provides method `edit()` to support changing the title and description of the draft:

```
draft = dataset.drafts.get(DRAFT_NUMBER)
draft.edit(title=f"{NEW_TITLE}", description=f"{NEW_DESCRIPTION}")
```

Upload the Draft

SDK provides method `upload()` to support uploading the local draft to Graviti. This step is essential if the user wants to save changes to the sheet of the dataset.

```
draft = dataset.drafts.get(DRAFT_NUMBER)
del draft["train"]
draft.upload()
```

Note: SDK supports specifying the max workers in multi-thread upload. The default is 8.

Commit the Draft

SDK provides method `commit()` to support committing a draft. This action means that a new commit will be created and all the changes from the draft will be saved into this commit. Furthermore, it is not allowed to read or upload data on a committed draft:

```
draft = dataset.drafts.get(DRAFT_NUMBER)
draft.commit(f"{COMMIT_TITLE}")
```

In addition to title, it is also allowed to add description to the commit:

```
draft.commit(f"{COMMIT_TITLE}", f"{COMMIT_DESCRIPTION}")
```

In this case, SDK will automatically update the version of the dataset after committing the draft. And all modifications on the dataset will be lost.

```
>>> dataset = ws.datasets.get("Graviti-dataset-demo")
>>> dataset.HEAD.name # The version of the dataset is Branch("main").
"main"
>>> dataset.HEAD.commit_id
"524d110ecae7474eaec9471f4a6c28b0"
>>> draft = dataset.drafts.create("draft-4", branch="dev")
>>> draft.commit("commit-4")
Branch("dev")(
  (commit_id): '3db73ac2876a42c0bf43a0489ce1756a',
  (parent): Commit("1b21a40f03ab4cec814ec47ee0d10b24"),
  (title): 'commit-4',
  (committer): 'graviti-example',
  (committed_at): 2022-07-21 04:23:45+00:00
)
>>> dataset.HEAD.name # The version of the dataset has been updated to Branch("dev").
"dev"
>>> dataset.HEAD.commit_id
"3db73ac2876a42c0bf43a0489ce1756a"
```

Users can avoid the automatic update by setting `update_dataset_head` to `False`:

```
>>> dataset = ws.datasets.get("Graviti-dataset-demo")
>>> dataset.HEAD.name # The version of the dataset is Branch("main").
"main"
```

(continues on next page)

(continued from previous page)

```

>>> dataset.HEAD.commit_id
"524d110ecae7474eac9471f4a6c28b0"
>>> draft = dataset.drafts.create("draft-5", branch="dev")
>>> draft.commit("commit-5", update_dataset_head=False)
Branch("dev")(
  (commit_id): '781007a41d1641859c87cb00f8e32bf3',
  (parent): Commit("3db73ac2876a42c0bf43a0489ce1756a"),
  (title): 'commit-5',
  (committer): 'graviti-example',
  (committed_at): 2022-07-21 04:24:45+00:00
)
>>> dataset.HEAD.name # The version of the dataset has not been updated.
"main"
>>> dataset.HEAD.commit_id
"524d110ecae7474eac9471f4a6c28b0"

```

Close the Draft

SDK provides method `close()` to support closing a draft: This action means that all changes made on this draft will be dropped. And the closed draft cannot be reopened. Furthermore, it is not allowed to read or upload data on a closed draft:

```

draft = dataset.drafts.get(DRAFT_NUMBER)
draft.close()

```

Tag

Graviti supports tagging specific commits in a dataset's history as being important, for example, to mark release revisions (v1.0, v2.0 and so on).

Before operating tags, a dataset with existing commits is needed:

```

from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")
dataset = ws.datasets.get(f"{DATASET_NAME}")

```

Create a Tag

SDK provides method `create()` to support creating a tag based on a revision. The revision can be one commit ID:

```
dataset.tags.create(f"{TAG_NAME}", f"{COMMIT_ID}")
```

The revision can also be the branch name. In this situation, the tag will be created based on the latest commit of the branch:

```
dataset.tags.create(f"{TAG_NAME}", f"{BRANCH_NAME}")
```

The revision can also be the tag name. SDK supports creating multiple tags based on the same commit:

```
dataset.tags.create(f"{TAG_NAME}", f"{SOURCE_TAG_NAME}")
```

If no tag is specified, the created tag will be based on the current commit of the dataset:

```
dataset.tags.create(f"{TAG_NAME}")
```

List Tags

SDK provides method `list()` to support listing tags:

```
dataset.tags.list()
```

Get a Tag

SDK provides method `get()` to support getting a tag by name:

```
dataset.tags.get(f"{TAG_NAME}")
```

Delete a Tag

SDK provides method `delete()` to support deleting a tag by name:

```
dataset.tags.delete(f"{TAG_NAME}")
```

Checkout Tag

SDK provides method `checkout()` to support switching the version of the dataset by tags:

```
dataset.checkout(f"{TAG_NAME}")
# Check whether the dataset version is correct.
dataset.HEAD
```

1.6 Sheet Management

In the Graviti SDK, Sheet and DataFrame are interpretations of the same thing at different levels.

Sheet refers to the form of data organization that is one level lower than the dataset. One dataset can have many different sheets, such as train, test, or frame-by-frame pictures from different videos. Each sheet has its own schema.

Graviti SDK organizes the data of a sheet into a DataFrame format, which makes it more convenient and intuitive to get and modify the data.

More details about the DataFrame and Schema are as follows:

1.6.1 DataFrame

DataFrame is an integrated data structure with an easy-to-use API for simplifying data processing in Dataset. A Graviti DataFrame contains 2-dimensional tabular data and a Protex schema describing the names and types of each column.

Initialize a DataFrame

Initialize a DataFrame from a list of dicts:

```
>>> from graviti import DataFrame
>>> data = [
...     {"filename": "a.jpg"},
...     {"filename": "b.jpg"},
...     {"filename": "c.jpg"},
... ]
>>> df = DataFrame(data)
>>> df
  filename
0  a.jpg
1  b.jpg
2  c.jpg
```

Initialize a DataFrame with multi-level column names:

```
>>> from graviti import DataFrame
>>> data = [
...     {"attribute": {"weather": "sunny", "color": "red"}},
...     {"attribute": {"weather": "rainy", "color": "black"}},
...     {"attribute": {"weather": "sunny", "color": "white"}},
... ]
>>> df = DataFrame(data)
>>> df
  attribute
  color    weather
0  red      sunny
1  black    rainy
2  white    sunny
```

Initialize a DataFrame with nested DataFrame construction:

```
>>> from graviti import DataFrame
>>> data = [
...     {"points": [{"xmin": 1, "ymin": 3}, {"xmin": 5, "ymin": 8}]},
...     {"points": [{"xmin": 6, "ymin": 10}]},
...     {"points": [{"xmin": 1, "ymin": 3}, {"xmin": 5, "ymin": 8}, {"xmin": 1, "ymin": 9}
...     ]},
... ]
>>> df = DataFrame(data)
>>> df
  points
0  DataFrame(2, 2)
1  DataFrame(1, 2)
2  DataFrame(3, 2)
```

(continues on next page)

(continued from previous page)

```
>>> df["points"][0]
      xmin  ymin
0      1     3
1      5     8
```

Read the DataFrame

Read data by row:

```
df.loc[0]
```

Read data by column:

```
df[f"{COLUMN_NAME}"]
```

Read a DataFrame cell:

```
df.loc[0][f"{COLUMN_NAME}"]
df[f"{COLUMN_NAME}"][0]
```

Edit the DataFrame

Edit Rows

Edit one row:

```
df.loc[0] = {"filename": "d.jpg"}
```

Edit multiple rows:

```
df.loc[0:2] = [{"filename": "d.jpg"}, {"filename": "e.jpg"}]
```

Edit the Items of Column

Edit one item:

```
df[f"{COLUMN_NAME}"][0] = "d.jpg"
```

Edit multiple items:

```
df[f"{COLUMN_NAME}"][0:2] = ["d.jpg", "e.jpg"]
```

Delete Rows

Delete one row:

```
del df.loc[0]
```

Delete multiple rows:

```
del df.loc[0:2]
```

Extend Rows

DataFrame supports method `extend()`.

Extend rows to the end of the DataFrame:

```
df.extend([{"filename": "a.jpg"}])
```

Extend another Dataframe to the end of the DataFrame:

```
df1 = DataFrame([{"filename": "a.jpg"}])  
df.extend(df1)
```

Add Columns

DataFrame supports adding columns by `setitem`:

```
>>> from graviti import DataFrame  
>>> data = [  
...     {"filename": "a.jpg"},  
...     {"filename": "b.jpg"},  
...     {"filename": "c.jpg"},  
... ]  
>>> df = DataFrame(data)  
>>> df  
  filename  
0  a.jpg  
1  b.jpg  
2  c.jpg  
>>> df["caption"] = ["a", "b", "c"]  
>>> df  
  filename  caption  
0  a.jpg      a  
1  b.jpg      b  
2  c.jpg      c  
>>> df.schema  
record(  
  fields={  
    'filename': string(),  
    'caption': string(),  
  },  
)
```

The above example shows adding a column of data with no specified type, and the schema of the column will be inferred. In this case, the column schema can only be Portex *Primitive Types*.

If specific Portex type is required, please add a Series as the column to the DataFrame.

```
>>> from graviti import DataFrame, Series
>>> data = [
...     {"filename": "a.jpg"},
...     {"filename": "b.jpg"},
...     {"filename": "c.jpg"},
... ]
>>> df = DataFrame(data)
>>> df
  filename
0  a.jpg
1  b.jpg
2  c.jpg
>>> df["category"] = Series(["cat", "dog", "cat"], pt.enum(["cat", "dog"]))
>>> df
  filename  category
0  a.jpg      cat
1  b.jpg      dog
2  c.jpg      cat
>>> df.schema
record(
  fields={
    'filename': string(),
    'category': enum(
      values=['cat', 'dog'],
    ),
  },
)
```

Note that not all DataFrame can be modified. Only if the fields of the schema are from given arguments, the DataFrame can be changed, like the above example. If the fields are defined in a template, the DataFrame cannot be changed, and `TypeError` will be raised:

```
>>> from graviti import DataFrame, Workspace
>>> import graviti.portex as pt

>>> std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main
↪")
>>> box2ds = std.label.Box2D(
...     categories=["boat", "car"],
...     attributes={
...         "difficult": pt.boolean(),
...         "occluded": pt.boolean(),
...     },
... )
>>> df = DataFrame(
...     [
...         {
...             "xmin": 1,
...             "ymin": 1,
```

(continues on next page)

(continued from previous page)

```

...         "xmax": 4,
...         "ymax": 5,
...         "category": "boat",
...         "attribute": {
...             "difficult": False,
...             "occluded": False,
...         },
...     }
... ],
...     schema=box2ds
... )
>>> df
   xmin  ymin  xmax  ymax  category  attribute
0  1.0  1.0  4.0  5.0    boat      False    False
>>> df["caption"] = ["a"]
TypeError: Cannot set item 'caption' in ImmutableFields

```

1.6.2 Schema

Each sheet has a record type schema to describe the name and the type of each column. Graviti use [Portex](#) schema language to define the schema, please refer to its documentation for the syntax.

Graviti SDK supports the python interaction with the Portex schema.

Primitive Types

Graviti SDK provides classes to initialize Portex primitive types:

boolean

```

>>> import graviti.portex as pt
>>> pt.boolean()
boolean()

```

binary

```

>>> import graviti.portex as pt
>>> pt.binary()
binary()

```

string

```

>>> import graviti.portex as pt
>>> pt.string()
string()

```

int32

```

>>> import graviti.portex as pt
>>> pt.int32()
int32()

```

int64

```
>>> import graviti.portex as pt
>>> pt.int64()
int64()
```

float32

```
>>> import graviti.portex as pt
>>> pt.float32()
float32()
```

float64

```
>>> import graviti.portex as pt
>>> pt.float64()
float64()
```

Complex Types

Graviti SDK provides classes to initialize Portex complex types.

enum

An enum type can be created by giving the values:

```
>>> import graviti.portex as pt
>>> enum = pt.enum(values=["a", "b", "c"])
>>> enum.values
['a', 'b', 'c']
```

array

The array type can be created by giving the item type. Param `length` can be specified to fix the length of array.

```
>>> import graviti.portex as pt
>>> array = pt.array(pt.int32())
>>> array
array(
  items=int32(),
)
>>> array = pt.array(pt.boolean(), length=2)
>>> array.items
boolean()
>>> array.length
2
```

record

The record type can be created by giving the fields, including names and types. The record type is used to describe the name and type of each column of the tabular data, and all the primitive and complex types mentioned above can be used here for each column type.

The names and types can be accessed by `fields`, which acts like a dict whose key is the column name and the value is column type.

Init record with list

```
>>> import graviti.portex as pt
>>> record = pt.record(
...     [
...         ("x", pt.int32()),
...         ("y", pt.int32()),
...         ("categories", pt.enum(values=["cat", "dog"]))
...     ]
... )
>>> record
record(
  fields={
    'x': int32(),
    'y': int32(),
    'categories': enum(
      values=['cat', 'dog'],
    ),
  },
)
>>> record.fields
{
  'x': int32(),
  'y': int32(),
  'categories': enum(
    values=['cat', 'dog'],
  ),
}
```

Init record with dict

```
>>> import graviti.portex as pt
>>> record = pt.record(
...     {
...         "x": pt.int32(),
...         "y": pt.int32(),
...         "categories": pt.enum(values=["cat", "dog"]),
...     }
... )
>>> record
record(
  fields={
    'x': int32(),
    'y': int32(),
    'categories': enum(
```

(continues on next page)

(continued from previous page)

```

        values=['cat', 'dog'],
    ),
},
)
>>> record.fields
{
  'x': int32(),
  'y': int32(),
  'categories': enum(
    values=['cat', 'dog'],
  ),
}

```

Template Type

The template type can be created by giving the parameters and the declaration. And the type can be instantiated by giving the arguments.

```

>>> import graviti.portex as pt
>>> vector_template = {
...     "type": "template",
...     "parameters": [
...         {
...             "name": "coords",
...             "default": {"type": "int32"},
...         },
...         {
...             "name": "labels",
...             "default": None,
...         },
...     ],
...     "declaration": {
...         "type": "record",
...         "fields": [
...             {
...                 "name": "x",
...                 "+": "$coords",
...             },
...             {
...                 "name": "y",
...                 "+": "$coords",
...             },
...             {
...                 "name": "label",
...                 "exist_if": "$labels",
...                 "type": "enum",
...                 "values": "$labels",
...             },
...         ],
...     },
... }

```

(continues on next page)

(continued from previous page)

```
>>> Vector = pt.template.template("Vector", vector_template)
>>> Vector
<class 'graviti.portex.template.Vector'>
>>> vector = Vector(coords=pt.float32(), labels=["cat", "dog"])
>>> vector
Vector(
  coords=float32(),
  labels=['cat', 'dog'],
)
```

Schema Files

Graviti SDK provides `read_yaml()` and `read_json()` to read the Portex type from a yaml or a json file.

YAML File

Take the following `schema.yaml` file as an example:

```
---
type: record
fields:
  - name: filename
    type: string

  - name: category
    type: int32

  - name: attribute
    type: record
    fields:
      - name: weather
        type: enum
        values: ["sunny", "rainy", "windy"]

      - name: distorted
        type: boolean
```

```
>>> import graviti.portex as pt
>>> schema = pt.read_yaml("schema.yaml")
>>> schema
record(
  fields={
    'filename': string(),
    'category': int32(),
    'attribute': record(
      fields={
        'weather': enum(
          values=['sunny', 'rainy', 'windy'],
        ),
        'distorted': boolean(),
      },
    ),
  ),
)
```

(continues on next page)

(continued from previous page)

```
    },
)
```

JSON File

Take the following `schema.json` file as an example:

```
{
  "type": "record",
  "fields": [
    {
      "name": "filename",
      "type": "string"
    },
    {
      "name": "category",
      "type": "int32"
    },
    {
      "name": "attribute",
      "type": "record",
      "fields": [
        {
          "name": "weather",
          "type": "enum",
          "values": [
            "sunny",
            "rainy",
            "windy"
          ]
        },
        {
          "name": "distorted",
          "type": "boolean"
        }
      ]
    }
  ]
}
```

```
>>> import graviti.portex as pt
>>> schema = pt.read_json("schema.json")
>>> schema
record(
  fields={
    'filename': string(),
    'category': int32(),
    'attribute': record(
      fields={
        'weather': enum(
          values=['sunny', 'rainy', 'windy'],
        ),
```

(continues on next page)

(continued from previous page)

```

        'distorted': boolean(),
    },
),
},
)

```

Schema Package

Graviti SDK supports to use external packages defined under a repo. By giving the repo and revision, the package can be initialized and used locally.

SDK provides `build_package()` to build an external Portex type package from the repo. Take `standard` as an example, which is used as the standard external package by Graviti.

```

>>> import graviti.portex as pt
>>> std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main
↳ ")
Cloning repo 'https://github.com/Project-OpenBytes/portex-standard@main'
Cloned to '/tmp/portex/2a656e669aea0b88dca87784a3963215'
>>> std
ExternalPackage {
  'calibration.Intrinsic': <class 'graviti.portex.builder.calibration.Intrinsic'>,
  'calibration.Extrinsic': <class 'graviti.portex.builder.calibration.Extrinsic'>,
  'geometry.Vector3D': <class 'graviti.portex.builder.geometry.Vector3D'>,
  'geometry.Quaternion': <class 'graviti.portex.builder.geometry.Quaternion'>,
  'geometry.Keypoint2D': <class 'graviti.portex.builder.geometry.Keypoint2D'>,
  'geometry.Vector2D': <class 'graviti.portex.builder.geometry.Vector2D'>,
  'geometry.PointList2D': <class 'graviti.portex.builder.geometry.PointList2D'>,
  'label.file.SemanticMask': <class 'graviti.portex.builder.label.file.SemanticMask'>,
  'label.file.InstanceMask': <class 'graviti.portex.builder.label.file.InstanceMask'>,
  'label.file.RemoteInstanceMask': <class 'graviti.portex.builder.label.file.
↳ RemoteInstanceMask'>,
  'label.file.PanopticMask': <class 'graviti.portex.builder.label.file.PanopticMask'>,
  'label.file.RemoteSemanticMask': <class 'graviti.portex.builder.label.file.
↳ RemoteSemanticMask'>,
  'label.tensor.SemanticMask': <class 'graviti.portex.builder.label.tensor.SemanticMask'>
↳ ,
  'label.tensor.InstanceMask': <class 'graviti.portex.builder.label.tensor.InstanceMask'>
↳ ,
  ... (25 items are folded),
  'tensor.Image': <class 'graviti.portex.builder.tensor.Image'>
}
>>> box2d = std.label.Box2D(categories=["cat", "dog"])
>>> box2d
label.Box2D(
  coords=float32(),
  categories=['cat', 'dog'],
)

```

Note: Using branch as the revision to build the external package is unstable, since the latest commit may change.

Tag name or commit ID as revision is recommended.

Binary Files

SDK supports adding and uploading binary files, whose schema must be of type `file.File`, `file.Image`, `file.Audio` or `file.PointCloud` in `standard` package.

```
>>> import graviti.portex as pt
>>> std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main
↪")
Cloning repo 'https://github.com/Project-OpenBytes/portex-standard@main'
Cloned to '/tmp/portex/2a656e669aea0b88dca87784a3963215'
>>> record = pt.record(
...     {
...         "filename": pt.string(),
...         "image": std.file.Image,
...     }
... )
```

When using the record in the above example as the schema of a DataFrame, the column of “image” stores image files. Please see [Binary Files](#) for more details about data.

Schema Methods

Convert

PortexType provides methods to convert to or init from python object, json string and yaml string. Take the following schema as an example:

```
>>> import graviti.portex as pt
>>> schema = pt.record(
...     {
...         "x": pt.int32(),
...         "y": pt.int32(),
...         "categories": pt.enum(values=["cat", "dog"]),
...     }
... )
>>> schema
record(
  fields={
    'x': int32(),
    'y': int32(),
    'categories': enum(
      values=['cat', 'dog'],
    ),
  },
)
```

Python Object

```

>>> pyobj = schema.to_pyobj()
>>> pyobj
{'type': 'record',
 'fields': [{'name': 'x', 'type': 'int32'},
            {'name': 'y', 'type': 'int32'},
            {'name': 'categories', 'type': 'enum', 'values': ['cat', 'dog']}]}

>>> pt.PortexType.from_pyobj(pyobj)
record(
  fields={
    'x': int32(),
    'y': int32(),
    'categories': enum(
      values=['cat', 'dog'],
    ),
  },
)

```

JSON String

```

>>> json_string = schema.to_json()
>>> json_string
'{"type": "record", "fields": [{"name": "x", "type": "int32"}, {"name": "y", "type":
↪ "int32"}, {"name": "categories", "type": "enum", "values": ["cat", "dog"]}]}

>>> pt.PortexType.from_json(json_string)
record(
  fields={
    'x': int32(),
    'y': int32(),
    'categories': enum(
      values=['cat', 'dog'],
    ),
  },
)

```

YAML String

```

>>> yaml_string = schema.to_yaml()
>>> yaml_string
'type: record\nfields:\n- name: x\n  type: int32\n- name: y\n  type: int32\n- name:
↪ categories\n  type: enum\n  values:\n    - cat\n    - dog\n'

>>> pt.PortexType.from_yaml(yaml_string)
record(
  fields={
    'x': int32(),
    'y': int32(),
    'categories': enum(
      values=['cat', 'dog'],
    ),
  },
)

```

Expand

For better comprehension and operations, SDK provides methods to expand external Portex type to builtin types:

```
>>> import graviti.portex as pt
>>> std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main
↪")
>>> box2d = std.label.Box2D(categories=["cat", "dog"])
# Expand the first layer of the external type
>>> box2d.internal_type
label._Label(
  geometry={
    'xmin': float32(),
    'ymin': float32(),
    'xmax': float32(),
    'ymax': float32(),
  },
  categories=['cat', 'dog'],
)
# Expand the top level of the external type to internal type
>>> box2d.to_builtin()
record(
  fields={
    'xmin': float32(),
    'ymin': float32(),
    'xmax': float32(),
    'ymax': float32(),
    'category': label.Category(
      categories=['cat', 'dog'],
    ),
  },
)
```

In the Graviti SDK, the relationship between sheet name, DataFrame and dataset is like the relationship between key, value and dict. Thus, SDK supports managing sheets like manipulating the dict in python.

The following will introduce more details about the sheet management methods in the SDK. First of all, it is necessary to get a dataset:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")
dataset = ws.datasets.get(f"{DATASET_NAME}")
```

1.6.3 Create a Sheet

First *Initialize a DataFrame*:

```
>>> from graviti import DataFrame
>>> data = [
...     {"filename": "a.jpg"},
...     {"filename": "b.jpg"},
...     {"filename": "c.jpg"},
... ]
>>> df = DataFrame(data)
>>> df
  filename
0  a.jpg
1  b.jpg
2  c.jpg
```

Set the DataFrame into dataset, then commit it:

```
dataset[f"{SHEET_NAME}"] = df
dataset.commit(f"{COMMIT_MESSAGE}")
```

1.6.4 List Sheets

List sheet names :

```
list(dataset.keys())
```

1.6.5 Get a Sheet

Get a sheet by name:

```
dataset[f"{SHEET_NAME}"]
```

1.6.6 Delete a Sheet

Delete a sheet by name:

```
del dataset[f"{SHEET_NAME}"]
dataset.commit(f"{COMMIT_MESSAGE}")
```

1.7 Action Managemanet

Graviti Action is designed to automate the data usage workflow in an efficient and simple way.

The data usage workflow is defined in “action”. Check [Action](#) for more details.

Everytime an action is executed, an action “Run” will be generated to manage the runtime info. Check [Run](#) for more details.

1.7.1 Action

Graviti SDK use class [Action](#) to represent an action. The action name is used as the unique identifier of an action. And the data usage workflow is defined in the action payload which follows the yaml syntax.

Action is a dataset level resource, it is necessary to get a dataset first:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")

dataset = ws.datasets.get(f"{DATASET_NAME}")
```

Create an Action

SDK provides method [create\(\)](#) to create an action:

```
with open(f"{PAYLOAD_YAML_FILE_PATH}") as fp:
    payload = fp.read()

dataset.actions.create(f"{ACTION_NAME}", payload)
```

List Actions

SDK provides method [list\(\)](#) to list actions:

```
dataset.actions.list()
```

Get an Action

SDK provides method [get\(\)](#) to get an action:

```
dataset.actions.get(f"{ACTION_NAME}")
```

Update an Action

SDK provides method `Action.edit()` to update an action:

Rename the action:

```
action = dataset.actions.get(f"{ACTION_NAME}")
action.edit(name=f"{NEW_ACTION_NAME}")
```

Update the action payload:

```
with open(f"{PAYLOAD_YAML_FILE_PATH}") as fp:
    new_payload = fp.read()

action.edit(payload=f"{NEW_ACTION_NAME}")
```

Note: Everytime the payload is updated, the `Action.edition` will be incremented by one.

Disable or Enable an Action

SDK provides methods `Action.disable()` and `Action.enable()` to disable and enable an action:

Once an action is disabled, it cannot be triggered automatically and manually.

```
>>> action = dataset.actions.get(f"{ACTION_NAME}")
>>> action.state
'ENABLED'

>>> action.disable()
>>> action.state
'DISABLED'

>>> action.enable()
>>> action.state
'ENABLED'
```

Delete an Action

SDK provides method `delete()` to delete an action:

```
dataset.actions.delete(f"{ACTION_NAME}")
```

Run an Action

“Run an Action” is equivalent to “Create an Action Run”, check [Create an Action Run](#) to run an action.

1.7.2 Run

Graviti SDK use class [Run](#) to represent an action run. The run number is used as the unique identifier of an action.

Action run is a action level resource, it is necessary to get an action first:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")

dataset = ws.datasets.get(f"{DATASET_NAME}")
action = dataset.actions.get(f"{ACTION_NAME}")
```

Create an Action Run

“Create an Action Run” is equivalent to “Run an Action”.

SDK provides method [create\(\)](#) to create an action run:

```
# Run an action with the default arguments:
action.runs.create()

# Run an action with given arguments:
action.runs.create({f"{ARGUMENT_NAME}": f"{ARGUMENT_VALUE}"})
```

List Action Runs

SDK provides method [list\(\)](#) to list action runs:

```
action.runs.list()
```

Get an Action Run

SDK provides method [get\(\)](#) to get an action run:

```
action.runs.get(f"{RUN_NUMBER}")
```

Cancel an Action Run

SDK provides method `Run.cancel()` to cancel an action run:

```
run = action.runs.get(f"{RUN_NUMBER}")
run.cancel()
```

Get the Run Log

Get the log of an action run is not supported directly in SDK so far. The log can be get from the Graviti webpage which url can be found in the property `Run.url`.

```
run = action.runs.get(f"{RUN_NUMBER}")
print(run.url)
```

1.8 Binary Files

Graviti SDK use the `File` and `RemoteFile` to represent a specific file.

In addition, SDK also provides several commonly used file formats, including `Image`, `Audio` and `PointCloud`.

More details about the Copy Files and Storage Config are as follows:

1.8.1 Copy Files

Graviti Data Platform supports copy binary files across different datasets.

Graviti stores binary files in the Object Storage Services, not in the Graviti database. The database only stores the access info of the binary files. The binary file copy operation only copies the access info, the real binary files will not be copied. Which means copy will not create additional storage space of Object Storage Services.

Important: The binary files can only be copied across the datasets in the same workspace with the same storage config

Note: The copy can be understood as the linux `ln` operation.

Example Code

This example downsample the source dataset with binary files, and copy the downsampled DataFrame to a new dataset. Get the DataFrame from the source dataset:

```
from graviti import Workspace

# initialize the Workspace
ws = Workspace(f"{ACCESS_KEY}")

# get the source dataset
```

(continues on next page)

(continued from previous page)

```
src_ds = ws.datasets.get("source_dataset")

# get the "data" sheet from the source dataset
src_df = src_ds["data"]
```

The “data” sheet in the source dataset contains binary files:

```
>>> src_df.schema
record(
  fields={
    'filename': string(),
    'file': file.File(),
  },
)

>>> src_df
  filename  file
0  0000.txt  RemoteFile("9cf96ce")
1  0001.txt  RemoteFile("d31c5f0")
2  0002.txt  RemoteFile("5f83d98")
3  0003.txt  RemoteFile("272c9a9")
4  0004.txt  RemoteFile("d25c42d")
5  0005.txt  RemoteFile("b6e904a")
6  0006.txt  RemoteFile("019fad7")
7  0007.txt  RemoteFile("7100110")
8  0008.txt  RemoteFile("945b3a8")
9  0009.txt  RemoteFile("59a0f9a")
```

Downsample the source dataframe and add it into the target dataset:

```
>>> # create the target dataset
>>> dst_ds = ws.datasets.create("target_dataset")

>>> # use the dataframe slice feature to downsample the source dataframe
>>> dst_df = src_df.iloc[::2]
>>> dst_df
  filename  file
0  0000.txt  RemoteFile("9cf96ce")
1  0002.txt  RemoteFile("5f83d98")
2  0004.txt  RemoteFile("d25c42d")
3  0006.txt  RemoteFile("019fad7")
4  0008.txt  RemoteFile("945b3a8")

>>> # add the downsampled dataframe to the target dataset
>>> dst_ds["downsampled"] = dst_df
```

Commit:

```
>>> dst_ds.commit("copy files from source_dataset")
Draft("#1: copy files from source_dataset") created successfully
uploading structured data: 100%| 5/5 [00:03<00:00, 1.38it/s]
uploading binary files: 100%| 5/5 [00:03<00:00, 1.38it/s]
Draft("#1: copy files from source_dataset") uploaded successfully
```

(continues on next page)

(continued from previous page)

```
Draft("#1: copy files from source_dataset") committed successfully
The HEAD of the dataset after commit:
Branch("main")(
  (commit_id): '913b44d7aebe43a18265c27a20d2decf',
  (parent): None,
  (title): 'copy files from source_dataset',
  (committer): 'linjiX',
  (committed_at): 2022-11-11 18:52:19+08:00
)
```

After commit, the downsampled dataframe with binary files is copied to the target dataset:

```
>>> # read the data from the target dataset
>>> dst_ds["downsampled"]
  filename  file
0  0000.txt  RemoteFile("9cf96ce")
1  0002.txt  RemoteFile("5f83d98")
2  0004.txt  RemoteFile("d25c42d")
3  0006.txt  RemoteFile("019fad7")
4  0008.txt  RemoteFile("945b3a8")
```

1.8.2 Storage Config

The binary files in Graviti Data Platform are stored in Object Storage Services, such as S3(AWS), OSS(Aliyun) and AZURE(Mircosoft).

Graviti uses “Storage Config” to store the information of the Object Storage Services. Graviti not only provides default storage configs ("GRAVITI" config), but also supports adding storage configs which belong to the customers ("AUTHORIZED" config). And the different storage configs can be used to create different datasets.

Storage Config is a workspace level resource, it is necessary to get a workspace first:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")
```

List Storage Configs

SDK provides method `list()` to list storage configs:

```
ws.storage_configs.list()
```

Get a Storage Config

SDK provides method `get()` to get a storage config:

```
ws.storage_configs.get(f"{STORAGE_CONFIG_NAME}")
```

Default Storage Config

A workspace has a default storage config, the default storage config will be used to create datasets which the storage config is not provided by the creator.

SDK provides property `default_storage_config` to get the default storage config.

```
ws.storage_configs.default_storage_config
```

SDK provides method `edit()` to set the default storage config.

```
ws.storage_configs.edit(default_storage_config=f"{STORAGE_CONFIG_NAME}")
```

Create Dataset with Specific StorageConfig

Method `DatasetManager.create()` provides `storage_config` parameter to create dataset with specific storage config.

```
# Create a dataset with specific storage config
dataset = ws.datasets.create(f"{DATASET_NAME}", storage_config=f"{STORAGE_CONFIG_NAME}")

# The default storage config will be used if the "storage_config" is not provided
dataset = ws.datasets.create(f"{DATASET_NAME}")
```

And the attr `Dataset.storage_config` is provided to get the `storage_config` of the dataset.

```
storage_config = dataset.storage_config
```

Create and Delete StorageConfig

Create and delete storage config is not provided in Graviti SDK so far. Please visit the Website [Graviti Storage Config](#) for creation and deletion.

1.8.3 File

SDK supports all various binary files including video files and text files by *File*.

Load the local text files to DataFrame:

```
import graviti.portex as pt
from graviti import DataFrame, File

std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main")
schema = pt.record(
    {
        "filename": pt.string(),
        "file": std.file.File(),
    }
)

data = [
    {
        "filename": "EXAMPLE1.txt",
        "file": File("PATH/TO/YOUR/EXAMPLE1.txt")
    },
    {
        "filename": "EXAMPLE2.txt",
        "file": File("PATH/TO/YOUR/EXAMPLE2.txt")
    },
]

df = DataFrame(data, schema)
```

Read the text in DataFrame:

```
text = df["text"][0]
with text.open() as fp:
    fp.read().decode("utf-8")
```

For all binary files, SDK supports viewing their basic information, including extension, size and checksum:

```
text.extension
text.size
text.get_checksum()
```

1.8.4 Image

Load the local image into DataFrame:

```
import graviti.portex as pt
from graviti import DataFrame, Image

std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main")
schema = pt.record(
    {
        "filename": pt.string(),
```

(continues on next page)

(continued from previous page)

```

        "image": std.file.Image(),
    }
)

data = [
    {
        "filename": "EXAMPLE1.png",
        "image": Image("PATH/TO/YOUR/EXAMPLE1.png")
    },
    {
        "filename": "EXAMPLE2.png",
        "image": Image("PATH/TO/YOUR/EXAMPLE2.png")
    },
]

df = DataFrame(data, schema)

```

Read the image in DataFrame:

```

import PIL

image = df["image"][0]
with image.open() as fp:
    PIL.Image.open(fp)

```

For image files, SDK supports viewing their height and width:

```

image.height
image.width

```

1.8.5 Audio

Load the local audio into DataFrame:

```

import graviti.portex as pt
from graviti import DataFrame, Audio

std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main")
schema = pt.record(
    {
        "filename": pt.string(),
        "audio": std.file.Audio(),
    }
)

data = [
    {
        "filename": "EXAMPLE1.wav",
        "audio": Audio("PATH/TO/YOUR/EXAMPLE1.wav")
    },
    {

```

(continues on next page)

(continued from previous page)

```
        "filename": "EXAMPLE2.wav",
        "audio": Audio("PATH/TO/YOUR/EXAMPLE2.wav")
    },
]

df = DataFrame(data, schema)
```

Read the audio in DataFrame:

```
audio = df["audio"][0]
with audio.open() as fp:
    fp.read()
```

1.8.6 Point Cloud

Load the local point_cloud into DataFrame:

```
import graviti.portex as pt
from graviti import DataFrame, PointCloud

std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main")
schema = pt.record(
    {
        "filename": pt.string(),
        "point_cloud": std.file.PointCloud(),
    }
)

data = [
    {
        "filename": "EXAMPLE1.pcd",
        "point_cloud": PointCloud("PATH/TO/YOUR/EXAMPLE1.pcd")
    },
    {
        "filename": "EXAMPLE2.pcd",
        "point_cloud": PointCloud("PATH/TO/YOUR/EXAMPLE2.pcd")
    },
]

df = DataFrame(data, schema)
```

Read the point_cloud in DataFrame:

```
point_cloud = df["point_cloud"][0]
with point_cloud.open() as fp:
    fp.read()
```

1.9 Search

Graviti Data Platform supports searching columns in sheet.

Check [Search History](#) for managing search histories and get the search result.

Check [Search in DataFrame](#) for triggering a search from SDK.

1.9.1 Search History

Graviti Data Platform stores the search histories.

Graviti SDK use class [SearchHistory](#) to represent a search history. The search ID is used as the unique identifier of a search history. It can be accessed through SDK attr [SearchHistory.search_id](#) or copied from Graviti website.

Search History is a dataset level resource, it is necessary to get a dataset first:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")

dataset = ws.datasets.get(f"{DATASET_NAME}")
```

List Search Histories

SDK provides method [list\(\)](#) to list search histories:

```
dataset.searches.list()
```

Get a Search History

SDK provides method [get\(\)](#) to get a search history:

```
dataset.searches.get(f"{SEARCH_ID}")
```

Delete a Search History

SDK provides method [delete\(\)](#) to delete a search history:

```
dataset.searches.delete(f"{SEARCH_ID}")
```

Run a Search

SDK provides method [SearchHistory.run\(\)](#) to run and get the search result.

```
search_history = dataset.searches.get(f"{SEARCH_ID}")

search_result_df = search_history.run()
```

1.9.2 Search in DataFrame

Graviti SDK supports to triggered Graviti search from DataFrame through the following two methods:

- `DataFrame.query()`
- `DataFrame.apply()`

Dataset Preparation

Take the following DataFrame as an example:

```
from graviti import DataFrame
import graviti.portex as pt

std = pt.build_package("https://github.com/Project-OpenBytes/portex-standard", "main")
schema = pt.record(
    {
        "filename": pt.string(),
        "box2ds": pt.array(
            std.label.Box2D(
                categories=["boat", "car"],
            )
        )
    }
)

data = []
for filename in ("a.jpg", "b.jpg", "c.jpg"):
    data.append(
        {
            "filename": filename,
            "box2ds": [
                {
                    "xmin": 10,
                    "ymin": 10,
                    "xmax": 100,
                    "ymax": 100,
                    "category": "boat",
                },
                {
                    "xmin": 20,
                    "ymin": 20,
                    "xmax": 200,
                    "ymax": 200,
                    "category": "car" if filename == "a.jpg" else "boat",
                },
            ],
        }
    )

df = DataFrame(data, schema)
```

```
>>> df
   filename  box2ds
0  a.jpg      DataFrame(2, 5)
1  b.jpg      DataFrame(2, 5)
2  c.jpg      DataFrame(2, 5)
```

Upload the DataFrame:

```
from graviti import Workspace

ws = Workspace(f"{YOUR_ACCESSKEY}")

dataset = ws.datasets.create("search_demo")
dataset["train"] = df
dataset.commit("initial commit")
```

Get the uploaded DataFrame:

```
df = dataset["train"]
```

Query

The query operation will use the lambda function to evaluate each rows, and return the True rows. The lambda function must return a boolean value.

SDK uses the `engine.online()` to start online searching. For example, search for all rows with filename as "a.jpg":

```
>>> from graviti import engine
>>> with engine.online():
...     result = df.query(lambda x: x["filename"] == "a.jpg")
>>> result
   filename  box2ds
0  a.jpg      DataFrame(2, 5)
```

SDK use `any()` to match box2ds in rows where at least one category is boat:

```
>>> from graviti import engine
>>> with engine.online():
...     result = df.query(lambda x: (x["box2ds"]["category"]=="boat").any())
>>> result
   filename  box2ds
0  a.jpg      DataFrame(2, 5)
1  b.jpg      DataFrame(2, 5)
2  c.jpg      DataFrame(2, 5)
```

SDK use `all()` to match box2ds in rows whose category are all boat:

```
>>> from graviti import engine
>>> with engine.online():
...     result = df.query(lambda x: (x["box2ds"]["category"]=="boat").all())
>>> result
   filename  box2ds
```

(continues on next page)

(continued from previous page)

```
0 b.jpg      DataFrame(2, 5)
1 c.jpg      DataFrame(2, 5)
```

Apply

The apply operation will apply the lambda function to DataFrame row by row.

Search all box2ds with the categories of “car”:

```
>>> from graviti import engine
>>> with engine.online():
...     result = df.apply(lambda x: x["box2ds"].query(lambda y: y["category"]=="car"))
>>> result
0 DataFrame(1, 5)
1 DataFrame(0, 5)
2 DataFrame(0, 5)
```

Query & Apply

SDK also supports calling `apply()` after the `query()`.

Search all rows with the box2ds category has “car” and remove null rows:

```
>>> from graviti import engine
>>> with engine.online():
...     result = df.query(lambda x: (x["box2ds"]["category"] == "car").any()).apply(
...         lambda x: x["box2ds"].query(lambda y: y["category"] == "car")
...     )
>>> result
0 DataFrame(1, 5)
```

1.10 Pandas Integration

Graviti SDK provides converting methods to pandas DataFrame and Series.

1.10.1 Graviti to Pandas

Graviti SDK provides `DataFrame.to_pandas()` and `Series.to_pandas()` methods to convert graviti `DataFrame` and `Series` to pandas.

```
>>> from graviti import DataFrame

>>> df = DataFrame(
...     [
...         {
...             "A": i,
...             "B": f"data{i}",
...             "C": bool(i % 2),
```

(continues on next page)

(continued from previous page)

```

...     }
...     for i in range(10)
... ]
... )
>>> pandas_df = df.to_pandas()
>>> pandas_df
   A      B      C
0  0  data0  False
1  1  data1   True
2  2  data2  False
3  3  data3   True
4  4  data4  False
5  5  data5   True
6  6  data6  False
7  7  data7   True
8  8  data8  False
9  9  data9   True

>>> type(pandas_df)
pandas.core.frame.DataFrame

```

```

>>> from graviti import Series

>>> series = Series(range(10))
>>> pandas_series = series.to_pandas()
>>> pandas_series
0    0
1    1
2    2
3    3
4    4
5    5
6    6
7    7
8    8
9    9
dtype: int64
>>> type(pandas_series)
pandas.core.series.Series

```

1.10.2 Pandas to Graviti

Graviti SDK provides `DataFrame.from_pandas()` and `Series.from_pandas()` methods to convert pandas DataFrame and Series to graviti.

```

>>> import pandas as pd
>>> from graviti import DataFrame

>>> pandas_df = pd.DataFrame(
...     [

```

(continues on next page)

(continued from previous page)

```
...     {
...         "A": i,
...         "B": f"data{i}",
...         "C": bool(i % 2),
...     }
...     for i in range(10)
... ]
... )
>>> df = DataFrame.from_pandas(pandas_df)
>>> df
   A    B    C
0  0  data0 False
1  1  data1  True
2  2  data2 False
3  3  data3  True
4  4  data4 False
5  5  data5  True
6  6  data6 False
7  7  data7  True
8  8  data8 False
9  9  data9  True

>>> type(df)
graviti.dataframe.frame.DataFrame
```

```
>>> import pandas as pd
>>> from graviti import Series

>>> pandas_series = pd.Series(range(10))
>>> series = Series.from_pandas(pandas_series)
>>> series
0  0
1  1
2  2
3  3
4  4
5  5
6  6
7  7
8  8
9  9

>>> type(series)
graviti.dataframe.column.series.NumberSeries
```

1.11 graviti

Graviti Python SDK.

1.11.1 Subpackages

`graviti.dataframe`

Dataframe module.

Subpackages

`graviti.dataframe.column`

Column Series module.

Submodules

`graviti.dataframe.column.indexing`

The implementation of the Graviti indexing related class.

Module Contents

Classes

<code><i>ColumnSeriesILocIndexer</i></code>	Index class for ColumnSeries.iloc.
<code><i>ColumnSeriesLocIndexer</i></code>	Index class for ColumnSeries.loc.

class `graviti.dataframe.column.indexing.ColumnSeriesILocIndexer(obj)`
Index class for ColumnSeries.iloc.

Parameters `obj` (`graviti.dataframe.column.series.Series`) –

class `graviti.dataframe.column.indexing.ColumnSeriesLocIndexer(obj)`
Index class for ColumnSeries.loc.

Parameters `obj` (`graviti.dataframe.column.series.Series`) –

graviti.dataframe.column.series

The implementation of the Graviti Series.

Module Contents

Classes

<i>Series</i>	One-dimensional array.
<i>PyarrowSeries</i>	Pyarrow based one-dimensional array.
<i>NumberSeries</i>	One-dimensional array for portex builtin number type.
<i>StringSeries</i>	One-dimensional array for portex builtin string type.
<i>BinarySeries</i>	One-dimensional array for portex builtin binary type.
<i>ArraySeries</i>	One-dimensional array for portex builtin type array.
<i>FileSeries</i>	One-dimensional array for file.
<i>EnumSeries</i>	One-dimensional array for portex builtin type enum.
<i>TimeSeries</i>	One-dimensional array for portex builtin temporal type.

Attributes

pd

graviti.dataframe.column.series.pd

class graviti.dataframe.column.series.Series

Bases: [*graviti.dataframe.container.Container*](#)

One-dimensional array.

Parameters

- **data** – The data that needs to be stored in Series. Could be ndarray or Iterable.
- **schema** – Data type to force. If None, will be inferred from data.

Examples

Constructing Series from a list.

```
>>> d = [1,2,3,4]
>>> series = Series(data=d)
>>> series
0 1
1 2
2 3
3 4
```

classmethod from_pyarrow(*cls, array*)

Instantiate a Series backed by an pyarrow array.

Parameters **array** (*pyarrow.Array*) – The input pyarrow array.

Raises **TypeError** – When the input pyarrow type is not supported.

Returns The loaded Series instance.

Return type *Series*

classmethod **from_pandas**(*cls, series*)

Convert a pandas Series to a graviti Series.

Parameters **series** (*pandas.Series*) – The input pandas Series.

Returns The converted graviti Series.

Return type *Series*

property **iloc**(*self*)

Purely integer-location based indexing for selection by position.

Allowed inputs are:

- An integer, e.g. 5.
- A list or array of integers, e.g. [4, 3, 0].
- A slice object with ints, e.g. 1:7.
- A boolean array of the same length as the axis being sliced.

Returns The instance of the ILocIndexer.

Return type *graviti.dataframe.column.indexing.ColumnSeriesILocIndexer*

Examples

```
>>> series = Series([1, 2, 3])
>>> series.loc[0]
1
>>> df.loc[[0]]
0    1
dtype: int64
```

property **loc**(*self*)

Access a group of rows and columns by indexes or a boolean array.

Allowed inputs are:

- A single index, e.g. 5.
- A list or array of indexes, e.g. [4, 3, 0].
- A slice object with indexes, e.g. 1:7.
- A boolean array of the same length as the axis being sliced.

Returns The instance of the LocIndexer.

Return type *graviti.dataframe.column.indexing.ColumnSeriesLocIndexer*

Examples

```
>>> series = Series([1, 2, 3])
>>> series.loc[0]
1
>>> df.loc[[0]]
0    1
dtype: int64
```

abstract to_pylist(*self*, *, *_to_backend=False*)

Convert the container to a python list.

Raises **NotImplementedError** – The method of the base class should not be called.

Parameters **_to_backend** (*bool*) –

Return type List[*Any*]

abstract to_pandas(*self*)

Convert the graviti Container to a pandas Series or DataFrame.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type pandas.Series

class graviti.dataframe.column.series.**PyarrowSeries**

Bases: *Series*

Pyarrow based one-dimensional array.

to_pylist(*self*, *, *_to_backend=False*)

Convert the Series to a python list.

Returns The python list representing the Series.

Parameters **_to_backend** (*bool*) –

Return type List[*Any*]

to_pandas(*self*)

Convert the graviti Series to a pandas Series.

Returns The converted pandas Series.

Return type pandas.Series

class graviti.dataframe.column.series.**NumberSeries**

Bases: *PyarrowSeries*

One-dimensional array for portex builtin number type.

class graviti.dataframe.column.series.**StringSeries**

Bases: *PyarrowSeries*

One-dimensional array for portex builtin string type.

class graviti.dataframe.column.series.**BinarySeries**

Bases: *PyarrowSeries*

One-dimensional array for portex builtin binary type.

class graviti.dataframe.column.series.**ArraySeries**

Bases: *Series*

One-dimensional array for portex builtin type array.

to_pylist(*self*, *, *_to_backend=False*)
Convert the Series to a python list.

Returns The python list representing the Series.

Parameters *_to_backend* (*bool*) –

Return type List[*Any*]

to_pandas(*self*)
Convert the graviti Series to a pandas Series.

Returns The converted pandas Series.

Return type pandas.Series

class graviti.dataframe.column.series.**FileSeries**

Bases: *Series*

One-dimensional array for file.

to_pylist(*self*, *, *_to_backend=False*)
Convert the BinaryFileSeries to python list.

Returns The python list.

Parameters *_to_backend* (*bool*) –

Return type List[*Any*]

to_pandas(*self*)
Convert the graviti Series to a pandas Series.

Returns The converted pandas Series.

Return type pandas.Series

class graviti.dataframe.column.series.**EnumSeries**

Bases: *PyarrowSeries*

One-dimensional array for portex builtin type enum.

to_pylist(*self*, *, *_to_backend=False*)
Convert the Series to a python list.

Returns The python list representing the Series.

Parameters *_to_backend* (*bool*) –

Return type List[*Any*]

to_pandas(*self*)
Convert the graviti EnumSeries to a pandas Categorical Series.

Returns The converted pandas Categorical Series.

Return type pandas.Series

class graviti.dataframe.column.series.**TimeSeries**

Bases: *PyarrowSeries*

One-dimensional array for portex builtin temporal type.

to_pylist(*self*, *, *_to_backend=False*)
Convert the Series to a python list.

Returns The python list representing the Series.

Parameters `_to_backend` (*bool*) –

Return type `List[Any]`

`graviti.dataframe.row`

Row Series module.

Submodules

`graviti.dataframe.row.indexing`

The implementation of the Graviti indexing related class.

Module Contents

Classes

<code><i>RowSeriesILocIndexer</i></code>	Index class for RowSeries.iloc.
<code><i>RowSeriesLocIndexer</i></code>	Index class for RowSeries.loc.

class `graviti.dataframe.row.indexing.RowSeriesILocIndexer`(*obj*)
Index class for RowSeries.iloc.

Parameters `obj` (`graviti.dataframe.row.series.Series`) –

class `graviti.dataframe.row.indexing.RowSeriesLocIndexer`(*obj*)
Index class for RowSeries.loc.

Parameters `obj` (`graviti.dataframe.row.series.Series`) –

`graviti.dataframe.row.series`

The implementation of the Graviti Series.

Module Contents

Classes

<code><i>Series</i></code>	One-dimensional array.
----------------------------	------------------------

class `graviti.dataframe.row.series.Series`(*data=None, schema=None, index=None*)
One-dimensional array.

Parameters

- **data** (`Optional[Dict[str, Any]]`) – The data that needs to be stored in Series. Could be ndarray or Iterable.

- **schema** (*Any*) – Data type to force. If None, will be inferred from data.
- **index** (*Optional[List[str]]*) – Index of the data.

Examples

Constructing Series from a list.

```
>>> d = {"filename": "a.jpg", "attributes": {"color": "red", "pose": "frontal"}}
>>> series = Series(data=d)
>>> series
filename          a.jpg
attributes color      red
              pose frontal
```

property `iloc(self)`

Purely integer-location based indexing for selection by position.

Allowed inputs are:

- An integer, e.g. 5.
- A list or array of integers, e.g. [4, 3, 0].
- A slice object with ints, e.g. 1:7.
- A boolean array of the same length as the axis being sliced.

Returns The instance of the `ILocIndexer`.

Return type *graviti.dataframe.row.indexing.RowSeriesILocIndexer*

Examples

```
>>> series = Series([1, 2, 3])
>>> series.loc[0]
1
>>> df.loc[[0]]
0    1
dtype: int64
```

property `loc(self)`

Access a group of rows and columns by indexes or a boolean array.

Allowed inputs are:

- A single index, e.g. 5.
- A list or array of indexes, e.g. [4, 3, 0].
- A slice object with indexes, e.g. 1:7.
- A boolean array of the same length as the axis being sliced.

Returns The instance of the `LocIndexer`.

Return type *graviti.dataframe.row.indexing.RowSeriesLocIndexer*

Examples

```
>>> series = Series([1, 2, 3])
>>> series.loc[0]
1
>>> df.loc[[0]]
0    1
dtype: int64
```

graviti.dataframe.sql

search module.

Submodules

graviti.dataframe.sql.array

The implementation of the search related array.

Module Contents

Classes

<i>LogicalOperatorsMixin</i>	A mixin for dynamically implementing logical operators.
<i>EqualOperatorsMixin</i>	A mixin for dynamically implementing euqal operators.
<i>ComparisonOperatorsMixin</i>	A mixin for dynamically implementing comparison operators.
<i>ArithmeticOperatorsMixin</i>	A mixin for dynamically implementing arithmetic operators.
<i>Array</i>	One-dimensional array for portex builtin type array.
<i>BooleanArray</i>	One-dimensional array for portex builtin type array with the boolean items.
<i>StringArray</i>	One-dimensional array for portex builtin type array with the string and enum items.
<i>EnumArray</i>	One-dimensional array for portex builtin type array with the string and enum items.
<i>TemporalArrayBase</i>	One-dimensional array for portex builtin temporal types.
<i>DateArray</i>	One-dimensional array for portex builtin date type.
<i>TimeArray</i>	One-dimensional array for portex builtin time type.
<i>TimestampArray</i>	One-dimensional array for portex builtin timestamp type.
<i>TimedeltaArray</i>	One-dimensional array for portex builtin timedelta type.
<i>NumberArray</i>	One-dimensional array for portex builtin type array with the numerical items.
<i>DataFrame</i>	The Two-dimensional array for the search.

continues on next page

Table 1.6 – continued from previous page

<i>ArrayDistributor</i>	A distributor to instance DataFrame, ArrayScalar by different array items.
<i>ArraySeries</i>	The One-dimensional array for the search.

class `graviti.dataframe.sql.array.LogicalOperatorsMixin(expr, schema, upper_expr)`

Bases: [`graviti.dataframe.sql.container.ArrayContainer`](#)

A mixin for dynamically implementing logical operators.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.EqualOperatorsMixin(expr, schema, upper_expr)`

Bases: [`graviti.dataframe.sql.container.ArrayContainer`](#)

A mixin for dynamically implementing euqal operators.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.ComparisonOperatorsMixin(expr, schema, upper_expr)`

Bases: [`graviti.dataframe.sql.container.ArrayContainer`](#)

A mixin for dynamically implementing comparison operators.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.ArithmeticOperatorsMixin(expr, schema, upper_expr)`

Bases: [`graviti.dataframe.sql.container.ArrayContainer`](#)

A mixin for dynamically implementing arithmetic operators.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.Array(expr, schema, upper_expr)`

Bases: [`graviti.dataframe.sql.container.ArrayContainer`](#)

One-dimensional array for portex builtin type array.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

- **upper_expr** (*_E*) –

query(*self*, *func*)

Query the data of an ArraySeries with a lambda function.

Parameters **func** (*Callable*[[*Any*], *Any*]) – The query function.

Returns The ArraySeries with the query expression.

Return type *Array*

any(*self*)

Whether any element is True.

Returns The BooleanSeries with the any expression.

Return type *graviti.dataframe.sql.scalar.BooleanScalar*

all(*self*)

Whether all elements are True.

Returns The BooleanSeries with the all expression.

Return type *graviti.dataframe.sql.scalar.BooleanScalar*

class *graviti.dataframe.sql.array.BooleanArray*(*expr*, *schema*, *upper_expr*)

Bases: *Array*, *LogicalOperatorsMixin*, *EqualOperatorsMixin*

One-dimensional array for portex builtin type array with the boolean items.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class *graviti.dataframe.sql.array.StringArray*(*expr*, *schema*, *upper_expr*)

Bases: *Array*, *LogicalOperatorsMixin*, *EqualOperatorsMixin*

One-dimensional array for portex builtin type array with the string and enum items.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class *graviti.dataframe.sql.array.EnumArray*(*expr*, *schema*, *upper_expr*)

Bases: *Array*, *EqualOperatorsMixin*

One-dimensional array for portex builtin type array with the string and enum items.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class *graviti.dataframe.sql.array.TemporalArrayBase*(*expr*, *schema*, *upper_expr*)

Bases: *Array*, *EqualOperatorsMixin*, *ComparisonOperatorsMixin*

One-dimensional array for portex builtin temporal types.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.DateArray(expr, schema, upper_expr)`

Bases: [*TemporalArrayBase*](#)

One-dimensional array for portex builtin date type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.TimeArray(expr, schema, upper_expr)`

Bases: [*TemporalArrayBase*](#)

One-dimensional array for portex builtin time type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.TimestampArray(expr, schema, upper_expr)`

Bases: [*TemporalArrayBase*](#)

One-dimensional array for portex builtin timestamp type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.TimedeltaArray(expr, schema, upper_expr)`

Bases: [*TemporalArrayBase*](#)

One-dimensional array for portex builtin timedelta type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

class `graviti.dataframe.sql.array.NumberArray(expr, schema, upper_expr)`

Bases: [*Array*](#), [*ComparisonOperatorsMixin*](#), [*ArithmeticOperatorsMixin*](#)

One-dimensional array for portex builtin type array with the numerical items.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

- **upper_expr** (*_E*) –

size(*self*)

Get the length of array series.

Returns The NumberScalar with the size expression.

Return type *graviti.dataframe.sql.scalar.NumberScalar*

max(*self*)

Get the max value of array series.

Returns The NumberScalar with the max expression.

Return type *graviti.dataframe.sql.scalar.NumberScalar*

min(*self*)

Get the min value of array series.

Returns The NumberScalar with the min expression.

Return type *graviti.dataframe.sql.scalar.NumberScalar*

sum(*self*)

Get the sum of array series.

Returns The NumberScalar with the sum expression.

Return type *graviti.dataframe.sql.scalar.NumberScalar*

class *graviti.dataframe.sql.array.DataFrame*(*expr*, *schema*, *upper_expr*)

Bases: *graviti.dataframe.sql.container.ArrayContainer*

The Two-dimensional array for the search.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

query(*self*, *func*)

Query the data of an ArraySeries with a lambda function.

Parameters **func** (*Callable[[Any], Any]*) – The query function.

Returns The DataFrame with the query expression.

Return type *DataFrame*

class *graviti.dataframe.sql.array.ArrayDistributor*(*expr*, *schema*, *upper_expr*)

Bases: *graviti.dataframe.sql.container.ArrayContainer*

A distributor to instance DataFrame, ArrayScalar by different array items.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

classmethod **from_upper**(*cls*, *expr*, *schema*)

Instantiate a Search object from the upper level.

Parameters

- **expr** (*graviti.dataframe.sql.container._E*) – The expression of the search.
- **schema** (*graviti.portex.PortexType*) – The schema of the series.

Returns The loaded object.

Return type *graviti.dataframe.sql.container.ArrayContainer*

class *graviti.dataframe.sql.array.ArraySeries*(*expr, schema, upper_expr*)

Bases: *graviti.dataframe.sql.container.ArrayContainer*

The One-dimensional array for the search.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –
- **upper_expr** (*_E*) –

graviti.dataframe.sql.container

The search container and register.

Module Contents

Classes

<i>ScalarContainer</i>	The base class for the search scalar container.
<i>ArrayContainer</i>	The base class for the search array container.
<i>SearchContainerRegister</i>	The class decorator to connect portex type and the search array container.

class *graviti.dataframe.sql.container.ScalarContainer*(*expr, schema*)

The base class for the search scalar container.

Parameters

- **expr** (*_E*) – The expression of the search.
- **schema** (*graviti.portex.PortexType*) – The schema of the series.

classmethod **from_upper**(*cls, expr, schema*)

Instantiate a Search object from the upper level.

Parameters

- **expr** (*_E*) – The expression of the search.
- **schema** (*graviti.portex.PortexType*) – The schema of the series.
- **cls** (*Type[_S]*) –

Returns The loaded object.

Return type *_S*

class *graviti.dataframe.sql.container.ArrayContainer*(*expr, schema, upper_expr*)

The base class for the search array container.

Parameters

- **expr** (*_E*) – The expression of the search.
- **schema** (*graviti.portex.PortexType*) – The schema of the series.
- **upper_expr** (*_E*) – The expression of the search.

classmethod **from_upper**(*cls, expr, schema*)

Instantiate a Search object from the upper level.

Parameters

- **expr** (*_E*) – The upper expression of the search.
- **schema** (*graviti.portex.PortexType*) – The schema of the series.

Returns The loaded object.

Return type *ArrayContainer*

class *graviti.dataframe.sql.container*.**SearchContainerRegister**(**portex_types*)

The class decorator to connect portex type and the search array container.

Parameters **portex_types** (*Type[graviti.portex.PortexType]*) – The portex types needs to be connected.

graviti.dataframe.sql.operator

The search operators for type inference.

Module Contents**Classes**

<i>OperatorRegister</i>	The class decorator to connect operator name and operator function.
-------------------------	---

Functions

<i>infer_type</i> (schema, expr)	Infer portex type from the Graviti criteria expr.
<i>get_type</i> (schema, expr)	Get portex type from the Graviti criteria expr.

Attributes

<i>PYTHON_TYPE_TO_PORTEX_TYPE</i>
<i>OPERATORS</i>

graviti.dataframe.sql.operator.**PYTHON_TYPE_TO_PORTEX_TYPE**

`graviti.dataframe.sql.operator.OPERATORS :Dict[str, _Operator]`

class `graviti.dataframe.sql.operator.OperatorRegister(*names)`

The class decorator to connect operator name and operator function.

Parameters

- **name** – The name of the operator.
- **names** (*str*) –

`graviti.dataframe.sql.operator.infer_type(schema, expr)`

Infer portex type from the Graviti criteria expr.

Parameters

- **schema** (*graviti.portex.PortexRecordBase*) – The schema of the sheet.
- **expr** (*_Expr*) – The Graviti criteria expr.

Returns The result portex type inferred from the expr.

Raises *CriteriaError* – When the operator is not supported.

Return type `graviti.portex.PortexType`

`graviti.dataframe.sql.operator.get_type(schema, expr)`

Get portex type from the Graviti criteria expr.

Parameters

- **schema** (*graviti.portex.PortexRecordBase*) – The schema of the sheet.
- **expr** (*str*) – The Graviti criteria expr.

Returns The result portex type inferred from the expr.

Raises *CriteriaError* – When the portex type cannot be get from the expr.

Return type `graviti.portex.PortexType`

`graviti.dataframe.sql.scalar`

The implementation of the search related Scalar.

Module Contents

Classes

<i>LogicalOperatorsMixin</i>	A mixin for dynamically implementing logical operators.
<i>EqualOperatorsMixin</i>	A mixin for dynamically implementing equal operators.
<i>ComparisonOperatorsMixin</i>	A mixin for dynamically implementing comparison operators.
<i>ArithmeticOperatorsMixin</i>	A mixin for dynamically implementing arithmetic operators.
<i>NumberScalar</i>	One-dimensional array for numerical portex builtin type.
<i>BooleanScalar</i>	One-dimensional array for portex builtin type boolean.
<i>StringScalar</i>	One-dimensional array for portex builtin type string.

continues on next page

Table 1.11 – continued from previous page

<i>EnumScalar</i>	One-dimensional array for portex builtin type enum.
<i>TemporalScalarBase</i>	One-dimensional array for portex builtin temporal type.
<i>DateScalar</i>	One-dimensional array for portex builtin date type.
<i>TimeScalar</i>	One-dimensional array for portex builtin time type.
<i>TimestampScalar</i>	One-dimensional array for portex builtin timestamp type.
<i>TimedeltaScalar</i>	One-dimensional array for portex builtin timedelta type.
<i>RowSeries</i>	The One-dimensional array for the search.

Attributes

NUMERICAL_PRIORITIES

`graviti.dataframe.sql.scalar.NUMERICAL_PRIORITIES :Dict[Type[graviti.portex.PortexType], int]`

class `graviti.dataframe.sql.scalar.LogicalOperatorsMixin(expr, schema)`

Bases: `graviti.dataframe.sql.container.ScalarContainer`

A mixin for dynamically implementing logical operators.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

class `graviti.dataframe.sql.scalar.EqualOperatorsMixin(expr, schema)`

Bases: `graviti.dataframe.sql.container.ScalarContainer`

A mixin for dynamically implementing equal operators.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

class `graviti.dataframe.sql.scalar.ComparisonOperatorsMixin(expr, schema)`

Bases: `graviti.dataframe.sql.container.ScalarContainer`

A mixin for dynamically implementing comparison operators.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

class `graviti.dataframe.sql.scalar.ArithmeticOperatorsMixin(expr, schema)`

Bases: `graviti.dataframe.sql.container.ScalarContainer`

A mixin for dynamically implementing arithmetic operators.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

```
class graviti.dataframe.sql.scalar.NumberScalar(expr, schema)
    Bases: LogicalOperatorsMixin, EqualOperatorsMixin, ComparisonOperatorsMixin,
    ArithmeticOperatorsMixin
```

One-dimensional array for numerical portex builtin type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

```
class graviti.dataframe.sql.scalar.BooleanScalar(expr)
    Bases: LogicalOperatorsMixin, EqualOperatorsMixin
```

One-dimensional array for portex builtin type boolean.

Parameters **expr** (*graviti.dataframe.sql.container._E*) –

```
class graviti.dataframe.sql.scalar.StringScalar(expr, schema)
    Bases: LogicalOperatorsMixin, EqualOperatorsMixin
```

One-dimensional array for portex builtin type string.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

```
class graviti.dataframe.sql.scalar.EnumScalar(expr, schema)
    Bases: EqualOperatorsMixin
```

One-dimensional array for portex builtin type enum.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

```
class graviti.dataframe.sql.scalar.TemporalScalarBase(expr, schema)
    Bases: EqualOperatorsMixin, ComparisonOperatorsMixin
```

One-dimensional array for portex builtin temporal type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

```
class graviti.dataframe.sql.scalar.DateScalar(expr, schema)
    Bases: TemporalScalarBase
```

One-dimensional array for portex builtin date type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

```
class graviti.dataframe.sql.scalar.TimeScalar(expr, schema)
    Bases: TemporalScalarBase
```

One-dimensional array for portex builtin time type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

class *graviti.dataframe.sql.scalar.TimestampScalar*(*expr, schema*)

Bases: *TemporalScalarBase*

One-dimensional array for portex builtin timestamp type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

class *graviti.dataframe.sql.scalar.TimedeltaScalar*(*expr, schema*)

Bases: *TemporalScalarBase*

One-dimensional array for portex builtin timedelta type.

Parameters

- **expr** (*_E*) –
- **schema** (*graviti.portex.PortexType*) –

class *graviti.dataframe.sql.scalar.RowSeries*(*schema*)

Bases: *graviti.dataframe.sql.container.ScalarContainer*

The One-dimensional array for the search.

Parameters **schema** (*graviti.portex.PortexRecordBase*) –

Submodules

graviti.dataframe.container

The table-structured data container related classes.

Module Contents

Classes

Container

The base class for the table-structured data container.

class *graviti.dataframe.container.Container*

The base class for the table-structured data container.

property *iloc*(*self*)

Purely integer-location based indexing for selection by position.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type *Any*

property *loc*(*self*)

Access the row by index.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type *Any*

abstract to_pylist(*self*, *, *_to_backend=False*)

Convert the container to a python list.

Raises **NotImplementedError** – The method of the base class should not be called.

Parameters *_to_backend* (*bool*) –

Return type List[*Any*]

abstract to_pandas(*self*)

Convert the graviti Container to a pandas Series or DataFrame.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type Union[pandas.Series, pandas.DataFrame]

copy(*self*)

Get a copy of the container.

Returns A copy of the container.

Parameters *self* (*_T*) –

Return type *_T*

graviti.dataframe.frame

The implementation of the Graviti DataFrame.

Module Contents

Classes

<i>DataFrame</i>	Two-dimensional, size-mutable, potentially heterogeneous tabular data.
------------------	--

Attributes

<i>pd</i>
<i>APPLY_KEY</i>

graviti.dataframe.frame.pd

graviti.dataframe.frame.APPLY_KEY = apply_result

class graviti.dataframe.frame.DataFrame

Bases: *graviti.dataframe.container.Container*

Two-dimensional, size-mutable, potentially heterogeneous tabular data.

Parameters

- **data** – The data that needs to be stored in DataFrame.

- **schema** – The schema of the DataFrame. If None, will be inferred from *data*.
- **columns** – Column labels to use for resulting frame when data does not have them, defaulting to RangeIndex(0, 1, 2, ..., n). If data contains column labels, will perform column selection instead.

Examples

Constructing DataFrame from list.

```
>>> df = DataFrame(
...     [
...         {"filename": "a.jpg", "box2ds": {"x": 1, "y": 1}},
...         {"filename": "b.jpg", "box2ds": {"x": 2, "y": 2}},
...         {"filename": "c.jpg", "box2ds": {"x": 3, "y": 3}},
...     ]
... )
>>> df
  filename box2ds
         x     y
0   a.jpg    1    1
1   b.jpg    2    2
2   c.jpg    3    3
```

classmethod `from_pyarrow(cls, array)`

Create DataFrame with pyarrow struct array.

Parameters

- **array** (*pyarrow.StructArray*) – The input pyarrow struct array.
- **cls** (*Type[_T]*) –

Returns The loaded DataFrame instance.

Return type *_T*

classmethod `from_pandas(cls, df)`

Create DataFrame with pandas DataFrame.

Parameters

- **df** (*pandas.DataFrame*) – The input pandas DataFrame.
- **cls** (*Type[_T]*) –

Raises **NotImplementedError** – When the column index of input DataFrame is MultiIndex.

Returns The loaded DataFrame instance.

Return type *_T*

property `iloc(self)`

Purely integer-location based indexing for selection by position.

Allowed inputs are:

- An integer, e.g. 5.
- A tuple, e.g. (5, "COLUMN_NAME")

Returns The instance of the ILocIndexer.

Return type *graviti.dataframe.indexing.DataFrameILocIndexer*

Examples

```
>>> df = DataFrame({"col1": [1, 2], "col2": [3, 4]})
>>> df.iloc[0]
col1    1
col2    3
Name: 0, dtype: int64
>>> df.iloc[0, "col1"]
1
```

property `loc(self)`

Access the row by indexes.

Allowed inputs are:

- A single index, e.g. 5.
- A tuple, e.g. (5, "COLUMN_NAME")

Returns The instance of the LocIndexer.

Return type *graviti.dataframe.indexing.DataFrameLocIndexer*

Examples

```
>>> df = DataFrame({"col1": [1, 2], "col2": [3, 4]})
>>> df.loc[0]
col1    1
col2    3
Name: 0, dtype: int64
>>> df.loc[0, "col1"]
1
```

property `shape(self)`

Return a tuple representing the dimensionality of the DataFrame.

Returns Shape of the DataFrame.

Return type Tuple[int, int]

Examples

```
>>> df = DataFrame(
...     [
...         {"filename": "a.jpg", "box2ds": {"x": 1, "y": 1}},
...         {"filename": "b.jpg", "box2ds": {"x": 2, "y": 2}},
...         {"filename": "c.jpg", "box2ds": {"x": 3, "y": 3}},
...     ]
... )
>>> df
  filename box2ds
```

(continues on next page)

(continued from previous page)

```

      x      y
0  a.jpg    1    1
1  b.jpg    2    2
2  c.jpg    3    3
>>> df.shape
(3, 2)

```

property `size(self)`

Return an int representing the number of elements in this object.

Returns Size of the DataFrame.**Return type** int**Examples**

```

>>> df = DataFrame({"col1": [1, 2], "col2": [3, 4]})
>>> df.size
4

```

keys(`self`)

Return a iterator of the column names in DataFrame.

Returns The column name iterator.**Return type** Iterator[str]**items**(`self`)

Return a iterator of the column names and the columns in DataFrame.

Yields The column name and the column.**Return type** Iterator[Tuple[str, *graviti.dataframe.container.Container*]]**head**(`self, n=5`)Return the first *n* rows.**Parameters**

- **n** (*int*) – Number of rows to select.
- **self** (*_T*) –

Returns The first *n* rows.**Return type** *_T***Examples**

```

>>> df = DataFrame(
...     [
...         {"animal": "alligator"},
...         {"animal": "bee"},
...         {"animal": "falcon"},
...         {"animal": "lion"},
...         {"animal": "monkey"},
...     ]

```

(continues on next page)

(continued from previous page)

```

...     {"animal": "parrot"},
...     {"animal": "shark"},
...     {"animal": "whale"},
...     {"animal": "zebra"},
... ]
... )
>>> df
   animal
0 alligator
1      bee
2    falcon
3      lion
4    monkey
5    parrot
6     shark
7     whale
8     zebra

```

Viewing the first n lines (three in this case)

```

>>> df.head(3)
   animal
0 alligator
1      bee
2    falcon

```

For negative values of n

```

>>> df.head(-3)
   animal
0 alligator
1      bee
2    falcon
3      lion
4    monkey
5    parrot

```

tail(*self*, $n=5$)

Return the last n rows.

Parameters

- **n** (*int*) – Number of rows to select.
- **self** (*_T*) –

Returns The last n rows.

Return type *_T*

Examples

```
>>> df = DataFrame(
...     [
...         {"animal": "alligator"},
...         {"animal": "bee"},
...         {"animal": "falcon"},
...         {"animal": "lion"},
...         {"animal": "monkey"},
...         {"animal": "parrot"},
...         {"animal": "shark"},
...         {"animal": "whale"},
...         {"animal": "zebra"},
...     ]
... )
>>> df
   animal
0 alligator
1      bee
2   falcon
3     lion
4   monkey
5   parrot
6    shark
7    whale
8    zebra
```

Viewing the last 5 lines

```
>>> df.tail()
   animal
0  monkey
1  parrot
2   shark
3   whale
4   zebra
```

Viewing the last n lines (three in this case)

```
>>> df.tail(3)
   animal
0   shark
1   whale
2   zebra
```

extend(*self*, *values*)

Extend Sequence object or DataFrame to itself row by row.

Parameters **values** (*Union[Iterable[Dict[str, Any]], DataFrame]*) – A sequence object or DataFrame.

Raises

- **TypeError** – When the self is the member of another Dataframe.
- **TypeError** – When the given Dataframe mismatched with the self schema.

Return type None

Examples

```
>>> df = DataFrame([
...     {"filename": "a.jpg", "box2ds": {"x": 1, "y": 1}},
...     {"filename": "b.jpg", "box2ds": {"x": 2, "y": 2}},
... ])
```

Extended by another list.

```
>>> df.extend([{"filename": "c.jpg", "box2ds": {"x": 3, "y": 3}}])
>>> df
  filename box2ds
0    a.jpg    1    1
1    b.jpg    2    2
2    c.jpg    3    3
```

Extended by another DataFrame.

```
>>> df2 = DataFrame([{"filename": "d.jpg", "box2ds": {"x": 4, "y": 4}}])
>>> df.extend(df2)
>>> df
  filename box2ds
0    a.jpg    1    1
1    b.jpg    2    2
2    d.jpg    4    4
```

to_pylist(*self*, *, *_to_backend*=False)

Convert the DataFrame to a python list.

Returns The python list representing the DataFrame.

Parameters *_to_backend* (bool) –

Return type List[Dict[str, Any]]

to_pandas(*self*)

Convert the graviti DataFrame to a pandas DataFrame.

Returns The converted pandas DataFrame.

Return type pandas.DataFrame

query(*self*, *func*)

Query the columns of a DataFrame with a lambda function.

Parameters *func* (Callable[[Any], Any]) – The query function.

Returns The query result DataFrame.

Raises **TypeError** – When the DataFrame is not in a Commit.

Return type DataFrame

Examples

```
>>> df = DataFrame([
...     {"filename": "a.jpg", "box2ds": {"x": 1, "y": 1}},
...     {"filename": "b.jpg", "box2ds": {"x": 2, "y": 2}},
... ])
>>> df.query(lambda x: x["filename"] == "a.jpg")
   filename box2ds
0    a.jpg      1    1
```

`apply(self, func)`

Apply a function to the DataFrame row by row.

Parameters `func` (*Callable[[Any], Any]*) – Function to apply to each row.

Returns The apply result DataFrame or Series.

Raises **TypeError** – When the DataFrame is not in a Commit.

Return type *graviti.dataframe.container.Container*

Examples

```
>>> df = DataFrame([
...     {"filename": "a.jpg", "box2ds": {"x": 1, "y": 1}},
...     {"filename": "b.jpg", "box2ds": {"x": 2, "y": 2}},
... ])
>>> df.apply(lambda x: x["box2ds"]["x"] + 1)
   filename box2ds
0    a.jpg      2    1
1    b.jpg      3    2
```

`graviti.dataframe.indexing`

The implementation of the Graviti indexing related class.

Module Contents

Classes

<i>DataFrameIlocIndexer</i>	Index class for DataFrame.iloc.
<i>DataFrameLocIndexer</i>	Index class for DataFrame.loc.

class `graviti.dataframe.indexing.DataFrameIlocIndexer(obj)`

Index class for DataFrame.iloc.

Parameters `obj` (*graviti.dataframe.DataFrame*) –

class `graviti.dataframe.indexing.DataFrameLocIndexer(obj)`

Index class for DataFrame.loc.

Parameters `obj (graviti.dataframe.DataFrame)` –

`graviti.file`

File module.

Submodules

`graviti.file.audio`

Graviti audio file class.

Module Contents

Classes

<code>Audio</code>	This class represents local audio files.
<code>RemoteAudio</code>	This class represents remote audio files.

class `graviti.file.audio.Audio(path)`

Bases: `graviti.file.base.File`

This class represents local audio files.

Parameters `path (graviti.utility.PathLike)` –

class `graviti.file.audio.RemoteAudio(key, extension, size, object_permission_manager)`

Bases: `graviti.file.base.RemoteFile`

This class represents remote audio files.

Parameters

- **key** (`str`) –
- **extension** (`str`) –
- **size** (`int`) –
- **object_permission_manager** (`graviti.manager.ObjectPermissionManager`) –

`graviti.file.base`

Graviti basic file class.

Module Contents

Classes

<i>FileBase</i>	This class represents the file in a DataFrame.
<i>File</i>	This class represents local files.
<i>RemoteFile</i>	This class represents the file on Graviti platform.

class `graviti.file.base.FileBase`

Bases: `graviti.utility.ReprMixin`

This class represents the file in a DataFrame.

property `key(self)`

Get the key of the file.

Returns The key of the file.

Return type `str`

property `extension(self)`

Get the extension of the file.

Returns The extension of the file.

Return type `str`

property `size(self)`

Get the size of the file.

Returns The size of the file.

Return type `int`

abstract `open(self)`

Return the binary file pointer of this file.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type `Union[graviti.utility.UserResponse, _io.BufferedReader]`

class `graviti.file.base.File(path)`

Bases: *FileBase*

This class represents local files.

Parameters `path (graviti.utility.PathLike)` – The local path of the file.

property `path(self)`

Get the path of the file.

Returns The path of the file.

Return type `pathlib.Path`

property `key(self)`

Get the key of the file.

Returns The key of the file.

Return type `str`

property `extension(self)`

Get the extension of the file.

Returns The extension of the file.

Return type str

property size(*self*)

Get the size of the file.

Returns The size of the file.

Return type int

get_checksum(*self*)

Get the sha1 checksum of the local file.

Returns The sha1 checksum of the local file.

Return type str

open(*self*)

Return the binary file pointer of this file.

Returns The local file pointer.

Return type `_io.BufferedReader`

class `graviti.file.base.RemoteFile`(*key*, *extension*, *size*, *object_permission_manager*)

Bases: [FileBase](#)

This class represents the file on Graviti platform.

Parameters

- **key** (*str*) – The key of the file.
- **extension** (*str*) – The extension of the file.
- **size** (*int*) – The size of the file.
- **object_permission_manager** (*graviti.manager.ObjectPermissionManager*) – The permission to access the file.

open(*self*)

Return the binary file pointer of this file.

Returns The remote file pointer.

Return type `graviti.utility.UserResponse`

`graviti.file.image`

Graviti image file class.

Module Contents

Classes

<i>Image</i>	This class represents local image files.
<i>RemoteImage</i>	This class represents remote image files.

class graviti.file.image.**Image**(*path*)

Bases: [graviti.file.base.File](#)

This class represents local image files.

Parameters *path* ([graviti.utility.PathLike](#)) – The local path of the image.

property *height*(*self*)

Get the height of the image.

Returns The height of the image.

Return type int

property *width*(*self*)

Get the width of the image.

Returns The width of the image.

Return type int

class graviti.file.image.**RemoteImage**(*key*, *extension*, *size*, *height*, *width*, *object_permission_manager*)

Bases: [graviti.file.base.RemoteFile](#)

This class represents remote image files.

Parameters

- **key** (*str*) – The key of the image file.
- **extension** (*str*) – The extension of the image file.
- **size** (*int*) – The size of the image file.
- **height** (*int*) – The height of the image.
- **width** (*int*) – The width of the image.
- **object_permission_manager** ([graviti.manager.ObjectPermissionManager](#)) – The permission to access the file.

property *height*(*self*)

Get the height of the image.

Returns The height of the image.

Return type int

property *width*(*self*)

Get the width of the image.

Returns The width of the image.

Return type int

graviti.file.image_size

Functions to get image size.

Module Contents**Classes**

<i>ImageFormatBase</i>	The base class for different image formats.
<i>JPEG</i>	The class for JPEG image format.
<i>PNG</i>	The class for PNG image format.
<i>OldPNG</i>	The class for an older version of PNG image format.
<i>GIF</i>	The class for GIF image format.
<i>JPEG2000</i>	The class for JPEG 2000 image format.
<i>BMP</i>	The class for BMP image format.
<i>TIFF</i>	The class for TIFF image format.
<i>ICO</i>	The class for ICO image format.
<i>WebP</i>	The class for WebP image format.
<i>FLIF</i>	The class for Flif image format.

Functions

<i>get_image_size</i> (path)	Get the height and width of the input image file.
------------------------------	---

Attributes

<i>Image</i>

graviti.file.image_size.Image

graviti.file.image_size.get_image_size(path)

Get the height and width of the input image file.

Parameters *path* (*pathlib.Path*) – The path of the image.

Returns The height and width of the input image.

Return type Tuple[int, int]

class graviti.file.image_size.**ImageFormatBase**

The base class for different image formats.

classmethod **check**(cls, header, size)

Check if the input header fits the current image format.

Parameters

- **header** (*bytes*) – The header of the image.
- **size** (*int*) – The size of the image.

Returns Whether if the input header fits the current image format.

Return type bool

classmethod `get_image_size(cls, header, fp)`

Get the height and width through the input data.

Parameters

- **header** (*bytes*) – The header of the image or the entire image.
- **fp** (*_io.BufferedReader*) – The image file pointer.

Returns The height and width of the image.

Raises *ImageDecodeError* – When the input image file is invalid.

Return type Tuple[int, int]

class `graviti.file.image_size.JPEG`

Bases: *ImageFormatBase*

The class for JPEG image format.

class `graviti.file.image_size.PNG`

Bases: *ImageFormatBase*

The class for PNG image format.

class `graviti.file.image_size.OldPNG`

Bases: *ImageFormatBase*

The class for an older version of PNG image format.

class `graviti.file.image_size.GIF`

Bases: *ImageFormatBase*

The class for GIF image format.

class `graviti.file.image_size.JPEG2000`

Bases: *ImageFormatBase*

The class for JPEG 2000 image format.

class `graviti.file.image_size.BMP`

Bases: *ImageFormatBase*

The class for BMP image format.

class `graviti.file.image_size.TIFF`

Bases: *ImageFormatBase*

The class for TIFF image format.

class `graviti.file.image_size.ICO`

Bases: *ImageFormatBase*

The class for ICO image format.

class `graviti.file.image_size.WebP`

Bases: *ImageFormatBase*

The class for WebP image format.

class `graviti.file.image_size.FLIF`

Bases: *ImageFormatBase*

The class for Flif image format.

graviti.file.point_cloud

Graviti point cloud file class.

Module Contents

Classes

<i>PointCloud</i>	This class represents local point cloud files.
<i>RemotePointCloud</i>	This class represents remote point cloud files.

class graviti.file.point_cloud.PointCloud(*path*)

Bases: *graviti.file.base.File*

This class represents local point cloud files.

Parameters *path* (*graviti.utility.PathLike*) –

class graviti.file.point_cloud.RemotePointCloud(*key*, *extension*, *size*, *object_permission_manager*)

Bases: *graviti.file.base.RemoteFile*

This class represents remote point cloud files.

Parameters

- **key** (*str*) –
- **extension** (*str*) –
- **size** (*int*) –
- **object_permission_manager** (*graviti.manager.ObjectPermissionManager*) –

graviti.manager

Manager module.

Submodules

graviti.manager.action

The implementation of the Action and ActionManager.

Module Contents

Classes

<i>Action</i>	This class defines the structure of an action.
<i>ActionManager</i>	This class defines the operations on the action in Graviti.
<i>Run</i>	This class defines the structure of an action run.

continues on next page

Table 1.24 – continued from previous page

<i>RunManager</i>	This class defines the operations on the action run in Graviti.
<i>Node</i>	This class defines the structure of a node of action run.

class `graviti.manager.action.Action(dataset, response)`

Bases: `graviti.utility.ReprMixin`

This class defines the structure of an action.

Parameters

- **dataset** (`graviti.manager.dataset.Dataset`) – Class `Dataset` instance.
- **response** (`Dict[str, Any]`) – The response of the OpenAPI associated with the action:

```
{
    "id": <str>,
    "name": <str>,
    "edition": <int>,
    "state": <str>,
    "payload": <str>,
},
```

name

The name of this action.

edition

The edition of this action.

state

The state of this action.

payload

The payload of this action.

property runs(self)

Get class `RunManager` instance.

Returns Required `RunManager` instance.

Return type `RunManager`

edit(self, *, name=None, payload=None)

Update the action.

Parameters

- **name** (`Optional[str]`) – The new name of the action.
- **payload** (`Optional[str]`) – The new payload of the action.

Return type `None`

enable(self)

Enable the action.

Return type `None`

disable(self)

Disable the action.

Return type `None`

```
class graviti.manager.action.ActionManager(dataset)
```

This class defines the operations on the action in Graviti.

Parameters *dataset* (`graviti.manager.dataset.Dataset`) – *Dataset* instance.

```
create(self, name, payload)
```

Create an action.

Parameters

- **name** (*str*) – The name of the action.
- **payload** (*str*) – The payload of the action.

Returns The *Action* instance with the given name.

Return type *Action*

```
get(self, name)
```

Get the action with the given name.

Parameters *name* (*str*) – The required action name.

Raises *ResourceNameError* – When the given name is an empty string.

Returns The *Action* instance with the given name.

Return type *Action*

```
list(self, *, sort=None)
```

List the information of actions.

Parameters *sort* (`graviti.utility.SortParam`) – The column and the direction the list result sorted by.

Returns The LazyPagingList of *actions* instances.

Return type `graviti.manager.lazy.LazyPagingList[Action]`

```
delete(self, name)
```

Delete an action.

Parameters *name* (*str*) – The name of the action to be deleted.

Raises *ResourceNameError* – When the given name is an empty string.

Return type *None*

```
class graviti.manager.action.Run(action, response)
```

Bases: `graviti.utility.ReprMixin`

This class defines the structure of an action run.

Parameters

- **action** (*Action*) – Class *Action* instance.
- **response** (`Dict[str, Any]`) – The response of the OpenAPI associated with the action run:

```
{
    "id": <str>,
    "number": <int>,
    "name": <str>,
    "workflow_id": <str>,
    "status": <int>,
```

(continues on next page)

(continued from previous page)

```

    "arguments": <dict>,
    "started_at": <str>,
    "ended_at": <str>,
},

```

number

The number of this action run.

name

The name of this action run.

status

The status of this action run.

arguments

The arguments of this action run.

started_at

The start time of this action run.

ended_at

The end time of this action run.

duration

The duration of this action run.

nodes(*self*)

Get the nodes of the action run.

Returns The nodes of the action run.

Return type List[*Node*]

property url(*self*)

Get the url of the action run.

Returns The url of the action run.

Raises ValueError – When the access key format is wrong.

Return type str

cancel(*self*)

Cancel the action run.

Return type None

class graviti.manager.action.**RunManager**(*action*)

This class defines the operations on the action run in Graviti.

Parameters *action* (*Action*) – *Action* instance.

create(*self*, *arguments=None*)

Run an action manually.

Parameters *arguments* (*Optional[Dict[str, Any]]*) – The arguments of the action run.

Returns The *Run* instance with the given arguments.

Return type *Run*

get(*self*, *run_number*)

Get the action with the given name.

Parameters `run_number` (*int*) – The number of the action run.

Returns The [Action](#) instance with the given name.

Return type [Run](#)

`list(self, *, sort=None)`

List the information of action runs.

Parameters `sort` (*graviti.utility.SortParam*) – The column and the direction the list result sorted by.

Returns The LazyPagingList of [runs](#) instances.

Return type *graviti.manager.lazy.LazyPagingList*[[Run](#)]

`class graviti.manager.action.Node(run, response)`

Bases: *graviti.utility.ReprMixin*

This class defines the structure of a node of action run.

Parameters

- **run** ([Run](#)) – Class [Run](#) instance.
- **response** (*Dict[str, Any]*) – The response of the OpenAPI associated with the action run node:

```
{
    "id": <str>,
    "name": <str>,
    "display_name": <str>,
    "phase": <str>,
    "started_at": <str>,
    "ended_at": <str>,
    "children": <list[str]>,
},
```

node_id

The id of this action run node.

name

The name of this action run node.

display_name

The display name of this action run node.

phase

The phase of this action run node.

started_at

The start time of this action run node.

ended_at

The end time of this action run node.

duration

The duration of this action run node.

children

The children of this action run node.

graviti.manager.branch

The implementation of the Branch and BranchManager.

Module Contents**Classes**

<i>Branch</i>	This class defines the structure of a branch.
<i>BranchManager</i>	This class defines the operations on the branch in Graviti.

class graviti.manager.branch.**Branch**(dataset, name, commit_id)

Bases: [*graviti.manager.commit.NamedCommit*](#)

This class defines the structure of a branch.

Parameters

- **dataset** ([*graviti.manager.dataset.Dataset*](#)) – Class *Dataset* instance.
- **name** (*str*) – The name of the branch.
- **commit_id** (*Optional[str]*) – The commit id.

class graviti.manager.branch.**BranchManager**(dataset)

This class defines the operations on the branch in Graviti.

Parameters **dataset** ([*graviti.manager.dataset.Dataset*](#)) – *Dataset* instance.

create(self, name, revision=*CURRENT_COMMIT*)

Create a branch.

Parameters

- **name** (*str*) – The branch name.
- **revision** (*str*) – The information to locate the specific commit, which can be the commit id, the branch name, or the tag name. The default value is the current commit of the dataset.

Raises [*NoCommitsError*](#) – When create branches on default branch without commit history.

Returns The [*Branch*](#) instance with the given name.

Return type [*Branch*](#)

get(self, name)

Get the branch with the given name.

Parameters **name** (*str*) – The required branch name.

Raises [*ResourceNameError*](#) – When the given name is an empty string.

Returns The [*Branch*](#) instance with the given name.

Return type [*Branch*](#)

list(self)

List the information of branches.

Returns The LazyPagingList of [*branches*](#) instances.

Return type [*graviti.manager.lazy.LazyPagingList\[Branch\]*](#)

delete(*self*, *name*)

Delete a branch.

Parameters **name** (*str*) – The name of the branch to be deleted.

Raises *ResourceNameError* – When the given name is an empty string.

Return type None

`graviti.manager.commit`

The implementation of the Commit and CommitManager.

Module Contents

Classes

<i>Commit</i>	This class defines the structure of a commit.
<i>NamedCommit</i>	This class defines the structure of a named commit.
<i>CommitManager</i>	This class defines the operations on the commit in Graviti.

class `graviti.manager.commit.Commit`(*dataset*, *commit_id*)

Bases: `graviti.manager.sheets.Sheets`

This class defines the structure of a commit.

Parameters

- **dataset** (`graviti.manager.dataset.Dataset`) – Class `Dataset` instance.
- **commit_id** (*Optional[str]*) – The commit id.

commit_id

The commit id of the commit.

parent

The parent commit of the commit.

title

The title of the commit.

description

The description of the commit.

committer

The committer of the commit.

committed_at

The commit time of the commit.

classmethod `from_response`(*cls*, *dataset*, *response*)

Create a *Commit* instance from python dict.

Parameters

- **dataset** (`graviti.manager.dataset.Dataset`) – The dataset of the commit.

- **response** (*Dict[str, Any]*) – A python dict containing all the information of the commit:

```
{
    "commit_id": <str>
    "parent_commit_id": <Optional[str]>
    "title": <str>
    "description": <str>
    "committer": <str>
    "committed_at": <str>
}
```

- **cls** (*Type[_C]*) –

Returns A *Commit* instance created from the input python dict.

Return type *_C*

class graviti.manager.commit.**NamedCommit**(dataset, name, commit_id)

Bases: *Commit*

This class defines the structure of a named commit.

NamedCommit is the base class of *Branch* and *Tag*.

Parameters

- **dataset** (*graviti.manager.dataset.Dataset*) – Class *Dataset* instance.
- **name** (*str*) – The name of the named commit.
- **commit_id** (*Optional[str]*) – The commit id.

classmethod **from_response**(cls, dataset, response)

Create a *NamedCommit* instance from python dict.

Parameters

- **dataset** (*graviti.manager.dataset.Dataset*) – The dataset of the *NamedCommit*.
- **response** (*Dict[str, Any]*) – A python dict containing all the information of the *NamedCommit*:

```
{
    "name": <str>
    "commit_id": <Optional[str]>
    "parent_commit_id": <Optional[str]>
    "title": <str>
    "description": <str>
    "committer": <str>
    "committed_at": <str>
}
```

- **cls** (*Type[_NC]*) –

Returns A *NamedCommit* instance created from the input python dict.

Return type *_NC*

class graviti.manager.commit.**CommitManager**(dataset)

This class defines the operations on the commit in Graviti.

Parameters **dataset** (*graviti.manager.dataset.Dataset*) – *Dataset* instance.

get(*self*, *revision*=*CURRENT_COMMIT*)

Get the certain commit with the given revision.

Parameters **revision** (*str*) – The information to locate the specific commit, which can be the commit id, the branch name, or the tag name. The default value is the current commit of the dataset.

Raises *NoCommitsError* – When revision is not given and the commit id of current dataset is None, or when the given branch has no commit history yet.

Returns The *Commit* instance with the given revision.

Return type *Commit*

list(*self*, *revision*=*CURRENT_COMMIT*)

List the commits.

Parameters **revision** (*str*) – The information to locate the specific commit, which can be the commit id, the branch name, or the tag name. If it is given, list the commits before the given commit. If it is not given, list the commits before the current commit.

Returns The LazyPagingList of *commits* instances.

Return type Union[*graviti.manager.lazy.LazyPagingList[Commit]*, List[Optional[*Commit*]]]

graviti.manager.common

Common tools.

Module Contents

Classes

<i>DefaultValue</i>	This class defines the default value of parameters from methods in manager.
---------------------	---

Functions

<i>check_head_status</i> (head, remote_revision, remote_commit_id)	Check if the commit for the HEAD of the current dataset is up-to-date.
--	--

Attributes

<i>LIMIT</i>
<i>CURRENT_COMMIT</i>
<i>CURRENT_BRANCH</i>

continues on next page

Table 1.29 – continued from previous page

ALL_BRANCHES

```
graviti.manager.common.LIMIT = 128
```

```
class graviti.manager.common.DefaultValue(name)
```

This class defines the default value of parameters from methods in manager.

Parameters *name* (*str*) – The name of the default value.

```
graviti.manager.common.CURRENT_COMMIT :Any
```

```
graviti.manager.common.CURRENT_BRANCH :Any
```

```
graviti.manager.common.ALL_BRANCHES :Any
```

```
exception graviti.manager.common.StatusWarning(revision_type, name)
```

Bases: Warning

This class defines the warning that the commit of dataset branch or tag is not up-to-date.

Parameters

- **revision_type** (*str*) – The type of current dataset revision.
- **name** (*str*) – The name of current dataset revision.

```
graviti.manager.common.check_head_status(head, remote_revision, remote_commit_id)
```

Check if the commit for the HEAD of the current dataset is up-to-date.

Parameters

- **head** (*graviti.manager.commit.Commit*) – The current revision of the local dataset.
- **remote_revision** (*str*) – The revision of the remote dataset in server.
- **remote_commit_id** (*Optional[str]*) – The commit id of the remote dataset in server.

Return type None

```
graviti.manager.dataset
```

The implementation of the Dataset and DatasetManager.

Module Contents

Classes

<i>RevisionType</i>	RevisionType is an enumeration type including "BRANCH", "COMMIT" and "TAG".
<i>ObjectPermissionManagerType</i>	ObjectPermissionManagerType is an enumeration type including "OSS", "S3" and "AZURE".
<i>Dataset</i>	This class defines the basic concept of the dataset on Graviti.
<i>DatasetManager</i>	This class defines the operations on the dataset on Graviti.

Attributes

logger

handler

`graviti.manager.dataset.logger`

`graviti.manager.dataset.handler`

class `graviti.manager.dataset.RevisionType`

Bases: `enum.Enum`

RevisionType is an enumeration type including “BRANCH”, “COMMIT” and “TAG”.

class `graviti.manager.dataset.ObjectPermissionManagerType`

Bases: `enum.Enum`

ObjectPermissionManagerType is an enumeration type including “OSS”, “S3” and “AZURE”.

class `graviti.manager.dataset.Dataset(workspace, response)`

Bases: `graviti.utility.UserMutableMapping[str, graviti.dataframe.DataFrame]`, `graviti.utility.ReprMixin`

This class defines the basic concept of the dataset on Graviti.

Parameters

- **workspace** (`graviti.Workspace`) – Class `Workspace` instance.
- **response** (`Dict[str, Any]`) – The response of the OpenAPI associated with the dataset:

```
{
    "id": <str>
    "name": <str>
    "alias": <str>
    "workspace": <str>
    "default_branch": <str>
    "commit_id": <Optional[str]>
    "cover_url": <str>
    "creator": <str>
    "created_at": <str>
    "updated_at": <str>
    "is_public": <bool>
    "storage_config": <str>
    "backend_type": <str>
}
```

name

The name of the dataset, unique for a user.

alias

Dataset alias.

workspace

The workspace of the dataset.

default_branch

The default branch of dataset.

commit_id

The commit ID of the dataset.

creator

The creator of the dataset.

created_at

The time when the dataset was created.

updated_at

The time when the dataset was last modified.

is_public

Whether the dataset is public.

storage_config

The storage config of dataset.

property HEAD(*self*)

Return the current branch or commit.

Returns The current branch or commit.

Return type *graviti.manager.commit.Commit*

property branches(*self*)

Get class *BranchManager* instance.

Returns Required *BranchManager* instance.

Return type *graviti.manager.branch.BranchManager*

property drafts(*self*)

Get class *DraftManager* instance.

Returns Required *DraftManager* instance.

Return type *graviti.manager.draft.DraftManager*

property commits(*self*)

Get class *CommitManager* instance.

Returns Required *CommitManager* instance.

Return type *graviti.manager.commit.CommitManager*

property tags(*self*)

Get class *TagManager* instance.

Returns Required *TagManager* instance.

Return type *graviti.manager.tag.TagManager*

property searches(*self*)

Get class *SearchManager* instance.

Returns Required *SearchManager* instance.

Return type *graviti.manager.search.SearchManager*

property actions(*self*)

Get class *ActionManager* instance.

Returns Required *ActionManager* instance.

Return type *graviti.manager.action.ActionManager*

checkout(*self*, *revision*)

Checkout to a commit.

Parameters **revision** (*str*) – The information to locate the specific commit, which can be the commit id, the branch, or the tag.

Return type *None*

edit(*self*, *, *name=None*, *alias=None*, *default_branch=None*)

Update the meta data of the dataset.

Parameters

- **name** (*Optional[str]*) – The new name of the dataset.
- **alias** (*Optional[str]*) – The new alias of the dataset.
- **default_branch** (*Optional[str]*) – The new default branch of the dataset.

Return type *None*

commit(*self*, *title*, *description=None*, *jobs=8*, *quiet=False*)

Create, upload and commit the draft to push the local dataset to Graviti.

Parameters

- **title** (*str*) – The commit title.
- **description** (*Optional[str]*) – The commit description.
- **jobs** (*int*) – The number of the max workers in multi-thread upload, the default is 8.
- **quiet** (*bool*) – Set to True to stop showing the upload process bar.

Raises

- **StatusError** – When the HEAD of the dataset is not a branch.
- **StatusError** – When the dataset has no modifications.

Return type *None*

class *graviti.manager.dataset.DatasetManager*(*workspace*)

This class defines the operations on the dataset on Graviti.

Parameters **workspace** (*graviti.Workspace*) – Class *Workspace* instance.

create(*self*, *name*, *alias=""*, *storage_config=None*)

Create a Graviti dataset with given name.

Parameters

- **name** (*str*) – The name of the dataset, unique for a user.
- **alias** (*str*) – Alias of the dataset, default is "".
- **storage_config** (*Optional[str]*) – The auth storage config name.

Returns The created *Dataset* instance.

Return type *Dataset*

get(*self*, *name*)

Get a Graviti dataset with given name.

Parameters **name** (*str*) – The name of the dataset, unique for a user.

Returns The requested *Dataset* instance.

Raises *ResourceNameError* – When the required dataset does not exist.

Return type *Dataset*

list(*self*)

List Graviti datasets.

Returns The LazyPagingList of *Dataset* instances.

Return type *graviti.manager.lazy.LazyPagingList[Dataset]*

delete(*self, name*)

Delete a Graviti dataset with given name.

Parameters **name** (*str*) – The name of the dataset, unique for a user.

Return type *None*

graviti.manager.draft

The implementation of the Draft and DraftManager.

Module Contents

Classes

<i>Draft</i>	The basic structure of the Graviti draft.
<i>DraftManager</i>	This class defines the operations on the draft in Graviti.

class *graviti.manager.draft.Draft*(*dataset, response*)

Bases: *graviti.manager.sheets.Sheets*

The basic structure of the Graviti draft.

Parameters

- **dataset** (*graviti.manager.dataset.Dataset*) – Class *Dataset* instance.
- **response** (*Dict[str, Any]*) – The response of the OpenAPI associated with the draft:

```
{
    "id": <str>
    "number": <int>
    "state": <str>
    "title": <str>
    "description": <str>
    "branch": <str>
    "parent_commit_id": <Optional[str]>
    "creator": <str>
    "created_at": <str>
    "updated_at": <str>
}
```

number

The number of the draft.

state

The draft state which includes “OPEN”, “CLOSED”, “COMMITTED”.

title

The title of the draft.

description

The draft description.

branch

The based branch of the draft.

parent

The parent of the draft.

creator

The creator of the draft.

created_at

The time when the draft is created.

updated_at

The time of last update.

edit(*self*, *, *title=None*, *description=None*)

Update title and description of the draft.

Parameters

- **title** (*Optional[str]*) – The title of the draft.
- **description** (*Optional[str]*) – The description of the draft.

Return type None

close(*self*)

Close the draft.

Return type None

commit(*self*, *title*, *description=None*, *update_dataset_head=True*)

Commit the current draft.

Parameters

- **title** (*str*) – The commit title.
- **description** (*Optional[str]*) – The commit description.
- **update_dataset_head** (*bool*) – Whether to update the dataset HEAD.
 - True (the default value): The dataset will be updated to the committed version. At this time, previous modifications to the dataset will be lost.
 - False: The HEAD of the dataset will not be updated. This can be set if the user needs to continue with some operations on the dataset.

Returns The [Branch](#) instance.

Return type [graviti.manager.branch.Branch](#)

Examples

The default scenario: `update_dataset_head` is `True`.

```
>>> dataset = ws.datasets.get("Graviti-dataset-demo")
>>> dataset.HEAD.name # The version of the dataset is Branch("main").
"main"
>>> dataset.HEAD.commit_id
"524d110ecae7474eaec9471f4a6c28b0"
>>> draft = dataset.drafts.create("draft-4", branch="dev")
>>> draft.commit("commit-4")
Branch("dev")(
  (commit_id): '3db73ac2876a42c0bf43a0489ce1756a',
  (parent): Commit("1b21a40f03ab4cec814ec47ee0d10b24"),
  (title): 'commit-4',
  (committer): 'graviti-example',
  (committed_at): 2022-07-19 04:23:45+00:00
)
>>> dataset.HEAD.name # The version of the dataset has been updated to Branch(
↪ "dev").
"dev"
>>> dataset.HEAD.commit_id
"3db73ac2876a42c0bf43a0489ce1756a"
```

Set `update_dataset_head` to `False`.

```
>>> dataset = ws.datasets.get("Graviti-dataset-demo")
>>> dataset.HEAD.name # The version of the dataset is Branch("main").
"main"
>>> dataset.HEAD.commit_id
"524d110ecae7474eaec9471f4a6c28b0"
>>> draft = dataset.drafts.create("draft-5", branch="dev")
>>> draft.commit("commit-5", update_dataset_head=False)
Branch("dev")(
  (commit_id): '781007a41d1641859c87cb00f8e32bf3',
  (parent): Commit("3db73ac2876a42c0bf43a0489ce1756a"),
  (title): 'commit-5',
  (committer): 'graviti-example',
  (committed_at): 2022-07-19 04:25:45+00:00
)
>>> dataset.HEAD.name # The version of the dataset has not been updated.
"main"
>>> dataset.HEAD.commit_id
"524d110ecae7474eaec9471f4a6c28b0"
```

upload(*self*, *jobs*=8, *quiet*=False)

Upload the local dataset to Graviti.

Parameters

- **jobs** (*int*) – The number of the max workers in multi-thread upload, the default is 8.
- **quiet** (*bool*) – Set to `True` to stop showing the upload process bar.

Return type `None`

class `graviti.manager.draft.DraftManager(dataset)`

This class defines the operations on the draft in Graviti.

Parameters `dataset` (`graviti.manager.dataset.Dataset`) – `Dataset` instance.

create(*self*, *title*, *description=None*, *branch=CURRENT_BRANCH*)

Create a draft.

Parameters

- **title** (*str*) – The draft title.
- **description** (*Optional[str]*) – The draft description.
- **branch** (*str*) – The branch name. The default value is the current branch of the dataset.

Returns The `Draft` instance with the given title and description.

Raises `StatusError` – When creating the draft without basing on a branch.

Return type `Draft`

get(*self*, *draft_number*)

Get the certain draft with the given draft number.

Parameters `draft_number` (*int*) – The required draft number.

Returns The `Draft` instance with the given number.

Return type `Draft`

list(*self*, *state='OPEN'*, *branch=ALL_BRANCHES*)

List all the drafts.

Parameters

- **state** (*str*) – The draft state which includes “OPEN”, “CLOSED”, “COMMITTED”, “ALL”. The default value is “OPEN”.
- **branch** (*str*) – The branch name. The default value is all branches.

Returns The LazyPagingList of `drafts` instances.

Return type `graviti.manager.lazy.LazyPagingList[Draft]`

`graviti.manager.lazy`

Related classes for the lazy evaluation.

Module Contents

Classes

<code>LazyItem</code>	In paging lazy evaluation system, a <code>LazyItem</code> instance represents an element in a pagination.
<code>ReturnGenerator</code>	<code>ReturnGenerator</code> is a generator wrap to get the return value easily.

continues on next page

Table 1.33 – continued from previous page

<i>LazyPage</i>	In paging lazy evaluation system, a LazyPage instance represents a page with elements.
<i>InitPage</i>	In paging lazy evaluation system, InitPage is the page to initialize <i>LazyPagingList</i> .
<i>LazyPagingList</i>	LazyPagingList is a wrap of web paging request.

Attributes

PagingGenerator

graviti.manager.lazy.**PagingGenerator**

class graviti.manager.lazy.**LazyItem**(*page, data*)

Bases: Generic[_T]

In paging lazy evaluation system, a LazyItem instance represents an element in a pagination.

If user wants to access the element, LazyItem will trigger the paging request to pull a page of elements and return the required element. All the pulled elements will be stored in different LazyItem instances and will not be requested again.

Parameters

- **page** (*LazyPage[_T]*) – The page the item belongs to.
- **data** (*_T*) –

page

The parent *LazyPage* of this item.

data

The actual element stored in this item.

classmethod **from_page**(*cls, page*)

Create a LazyItem instance from page.

Parameters **page** (*LazyPage[_T]*) – The page of the element.

Returns The LazyItem instance which stores the input page.

Return type *LazyItem[_T]*

classmethod **from_data**(*cls, data*)

Create a LazyItem instance from data.

Parameters **data** (*_T*) – The actual data needs to be stored in LazyItem.

Returns The LazyItem instance which stores the input data.

Return type *LazyItem[_T]*

get(*self*)

Access the actual element represented by LazyItem.

If the element is already pulled from web, it will be return directly, otherwise this function will request for a page of elements to get the required element.

Returns The actual element this LazyItem instance represents.

Return type `_T`

class `graviti.manager.lazy.ReturnGenerator(generator)`

Bases: `Generic[_T, _R]`

`ReturnGenerator` is a generator wrap to get the return value easily.

Parameters `generator` (`Generator[_T, Any, _R]`) – The generator needs to be wrapped.

value

The return value of the input generator.

class `graviti.manager.lazy.LazyPage(offset, limit, func)`

Bases: `Generic[_T]`

In paging lazy evaluation system, a `LazyPage` instance represents a page with elements.

`LazyPage` is used for sending paging request to pull a page of elements and storing them in different `LazyItem` instances.

Parameters

- **offset** (`int`) – The offset of the page.
- **limit** (`int`) – The limit of the page.
- **func** (`PagingGenerator[_T]`) – A paging generator function, which takes `offset<int>` and `limit<int>` as inputs and returns a generator. The returned generator should yield the element user needs, and return the total count of the elements in the paging request.

items

The `LazyItem` list which represents a page of elements.

classmethod `from_items(cls, offset, limit, func, item_contents)`

Create a `LazyPage` instance with the given items and generator function.

Parameters

- **offset** (`int`) – The offset of the page.
- **limit** (`int`) – The limit of the page.
- **func** (`PagingGenerator[_T]`) – A paging generator function, which takes `offset<int>` and `limit<int>` as inputs and returns a generator. The returned generator should yield the element user needs, and return the total count of the elements in the paging request.
- **item_contents** (`Iterable[_T]`) – The lazy item contents that need to be stored on this page.

Returns The `LazyPage` instance which stores the input items and function.

Return type `LazyPage[_T]`

pull(`self`)

Send paging request to pull a page of elements and store them in `LazyItem`.

Return type `None`

class `graviti.manager.lazy.InitPage(offset, limit, func)`

Bases: `LazyPage[_T]`

In paging lazy evaluation system, `InitPage` is the page to initialize `LazyPagingList`.

`InitPage` will send a paging request to pull a page of elements and storing them in different `LazyItem` instances when construction. And the `totalCount` of the page will also be stored in the instance.

Parameters

- **offset** (*int*) – The offset of the page.
- **limit** (*int*) – The limit of the page.
- **func** (*PagingGenerator[_T]*) – A paging generator function, which takes offset<int> and limit<int> as inputs and returns a generator. The returned generator should yield the element user needs, and return the total count of the elements in the paging request.

items

The *LazyItem* list which represents a page of elements.

total_count

The totalCount of the paging request.

class graviti.manager.lazy.**LazyPagingList**(*func, limit*)
Bases: MutableSequence[_T], graviti.utility.ReprMixin

LazyPagingList is a wrap of web paging request.

It follows the python MutableSequence protocol, which means it can be used like a python builtin list. And it provides features like lazy evaluation and cache.

Parameters

- **func** (*PagingGenerator[_T]*) – A paging generator function, which takes offset<int> and limit<int> as inputs and returns a generator. The returned generator should yield the element user needs, and return the total count of the elements in the paging request.
- **limit** (*int*) – The page size of each paging request.

insert(*self, index, value*)

Insert object before index.

Parameters

- **index** (*int*) – Position of the LazyPagingList.
- **value** (*_T*) – Element to be inserted into the LazyPagingList.

Return type None

append(*self, value*)

Append object to the end of the LazyPagingList.

Parameters **value** (*_T*) – Element to be appended to the LazyPagingList.

Return type None

reverse(*self*)

Reverse the items of the LazyPagingList in place.

Return type None

pop(*self, index=-1*)

Return the item at index (default last) and remove it from the LazyPagingList.

Parameters **index** (*int*) – Position of the LazyPagingList.

Returns Element to be removed from the LazyPagingList.

Return type *_T*

index(*self, value, start=0, stop=None*)

Return the first index of the value.

Parameters

- **value** (*Any*) – The value to be found.
- **start** (*int*) – The start index of the subsequence.
- **stop** (*Optional[int]*) – The end index of the subsequence.

Raises **ValueError** – When the value is not in the LazyPagingList

Returns The first index of the value.

Return type *int*

count(*self, value*)

Return the number of occurrences of value.

Parameters **value** (*Any*) – The value needs to be counted.

Returns The number of occurrences of value.

Return type *int*

extend(*self, values*)

Extend LazyPagingList by appending elements from the iterable.

Parameters **values** (*Iterable[_T]*) – Elements to be extended into the LazyPagingList.

Return type *None*

graviti.manager.permission

The implementation of the dataset object permission.

Module Contents

Classes

<i>ObjectPermissionManager</i>	The basic structure of the object permission of the dataset.
<i>OSSObjectPermissionManager</i>	The basic structure of the object permission of the dataset stored in OSS.
<i>AZUREObjectPermissionManager</i>	The basic structure of the object permission of the dataset stored in AZURE.
<i>S3ObjectPermissionManager</i>	The basic structure of the object permission of the dataset stored in S3.

class `graviti.manager.permission.ObjectPermissionManager(dataset)`

The basic structure of the object permission of the dataset.

Parameters **dataset** (*graviti.manager.Dataset*) – Class Dataset instance.

property **prefix**(*self*)

Return the prefix of the put permission.

Returns The prefix of the put permission.

Return type *str*

abstract `get_object(self, key, _allow_retry=True)`

Get the object from graviti.

Parameters

- **key** (*str*) – The key of the file.
- **_allow_retry** (*bool*) – Whether requesting the get permission again is allowed.

Raises `NotImplementedError` – The method of the base class should not be called.

Return type `graviti.utility.UserResponse`

abstract `put_object(self, key, path, _allow_retry=True)`

Put the object to OSS.

Parameters

- **key** (*str*) – The key of the file.
- **path** (*pathlib.Path*) – The path of the file.
- **_allow_retry** (*bool*) – Whether requesting the put permission again is allowed.

Raises `NotImplementedError` – The method of the base class should not be called.

Return type `None`

class `graviti.manager.permission.OSSObjectPermissionManager(dataset)`

Bases: `ObjectPermissionManager`

The basic structure of the object permission of the dataset stored in OSS.

Parameters `dataset` (*graviti.manager.Dataset*) –

get_object (*self*, *key*, *_allow_retry=True*)

Get the object from OSS.

Parameters

- **key** (*str*) – The key of the file.
- **_allow_retry** (*bool*) – Whether requesting the get permission again is allowed.

Raises `ResponseError` – If post response error.

Returns The response of OSS get object API.

Return type `graviti.utility.UserResponse`

put_object (*self*, *key*, *path*, *_allow_retry=True*)

Put the object to OSS.

Parameters

- **key** (*str*) – The key of the file.
- **path** (*pathlib.Path*) – The path of the file.
- **_allow_retry** (*bool*) – Whether requesting the put permission again is allowed.

Raises `ResponseError` – If post response error.

Return type `None`

class `graviti.manager.permission.AZUREObjectPermissionManager(dataset)`

Bases: `ObjectPermissionManager`

The basic structure of the object permission of the dataset stored in AZURE.

Parameters **dataset** (*graviti.manager.Dataset*) –

get_object(*self, key, _allow_retry=True*)

Get the object from AZURE.

Parameters

- **key** (*str*) – The key of the file.
- **_allow_retry** (*bool*) – Whether requesting the get permission again is allowed.

Raises *ResponseError* – If post response error.

Returns The response of AZURE get object API.

Return type *graviti.utility.UserResponse*

put_object(*self, key, path, _allow_retry=True*)

Put the object to AZURE.

Parameters

- **key** (*str*) – The key of the file.
- **path** (*pathlib.Path*) – The path of the file.
- **_allow_retry** (*bool*) – Whether requesting the put permission again is allowed.

Raises *ResponseError* – If post response error.

Return type *None*

class *graviti.manager.permission.S3ObjectPermissionManager*(*dataset*)

Bases: *ObjectPermissionManager*

The basic structure of the object permission of the dataset stored in S3.

Parameters **dataset** (*graviti.manager.Dataset*) –

get_object(*self, key, _allow_retry=True*)

Get the object from S3.

Parameters

- **key** (*str*) – The key of the file.
- **_allow_retry** (*bool*) – Whether requesting the get permission again is allowed.

Raises *ResponseError* – If post response error.

Returns The response of S3 get object API.

Return type *graviti.utility.UserResponse*

put_object(*self, key, path, _allow_retry=True*)

Put the object to OSS.

Parameters

- **key** (*str*) – The key of the file.
- **path** (*pathlib.Path*) – The path of the file.
- **_allow_retry** (*bool*) – Whether requesting the put permission again is allowed.

Raises *ResponseError* – If post response error.

Return type *None*

`graviti.manager.search`

The implementation of the SearchHistory and SearchManager.

Module Contents

Classes

<code>SearchHistory</code>	This class defines the structure of the search history of Graviti Data Platform.
<code>SearchManager</code>	This class defines the operations on the searches on Graviti.

class `graviti.manager.search.SearchHistory`(*dataset, response*)

Bases: `graviti.utility.ReprMixin`

This class defines the structure of the search history of Graviti Data Platform.

Parameters

- **dataset** (`graviti.manager.dataset.Dataset`) – Class `Dataset` instance.
- **response** (`Dict[str, Any]`) – The response of the OpenAPI associated with the search history:

```
{
  "id": <str>
  "commit_id": <str>,
  "draft_number": <int>,
  "sheet": <str>,
  "criteria": <dict>,
  "record_count": <int>,
  "creator": <str>,
  "created_at": <str>,
},
```

search_id

The id of this search history.

commit

The commit of this search history.

draft_number

The draft number of this search history.

sheet

The sheet name of this search history.

criteria

The criteria of this search history.

creator

The creator of this search history.

created_at

The create time of this search history.

record_count(*self*)

Get the record count of the search.

Returns The record count of the search.

Return type int

schema(*self*)

Get the schema of the search result.

Returns The schema of the search result.

Return type graviti.portex.record

run(*self*)

Run the search and get the result DataFrame.

Returns The search result DataFrame.

Return type graviti.dataframe.DataFrame

class graviti.manager.search.**SearchManager**(*dataset*)

This class defines the operations on the searches on Graviti.

Parameters

- **access_key** – User’s access key.
- **url** – The URL of the graviti website.
- **dataset** ([graviti.manager.dataset.Dataset](#)) –

get(*self*, *search_id*)

Get a Graviti search history with given search id.

Parameters **search_id** (*str*) – The id of the search history.

Returns The requested [SearchManager](#) instance.

Return type [SearchHistory](#)

list(*self*, *, *commit_id=None*, *draft_number=None*, *sheet=None*, *sort=None*)

List Graviti search histories.

Parameters

- **commit_id** (*Optional[str]*) – The commit id.
- **draft_number** (*Optional[int]*) – The draft number.
- **sheet** (*Optional[str]*) – The name of the sheet.
- **sort** ([graviti.utility.SortParam](#)) – The column and the direction the list result sorted by.

Returns The LazyPagingList of [SearchHistory](#) instances.

Return type [graviti.manager.lazy.LazyPagingList\[SearchHistory\]](#)

delete(*self*, *search_id*)

Delete a Graviti search history with given search id.

Parameters **search_id** (*str*) – The id of the search history.

Return type None

`graviti.manager.sheets`

The implementation of the Sheets.

Module Contents

Classes

<i>Sheets</i>	The basic structure of the Graviti sheets.
---------------	--

class `graviti.manager.sheets.Sheets`

Bases: `MutableMapping[str, graviti.dataframe.DataFrame]`, `graviti.utility.ReprMixin`

The basic structure of the Graviti sheets.

keys(*self*)

Return a new view of the keys in sheets.

Returns The keys in dict.

Return type `KeysView[str]`

values(*self*)

Return a new view of the values in sheets.

Returns The values in dict.

Return type `ValuesView[graviti.dataframe.DataFrame]`

items(*self*)

Return a new view of the (key, value) pairs in sheets.

Returns The (key, value) pairs in dict.

Return type `ItemsView[str, graviti.dataframe.DataFrame]`

`graviti.manager.storage_config`

The implementation of the StorageConfig and StorageConfigManager.

Module Contents

Classes

<i>StorageConfig</i>	This class defines the structure of the storage config of Graviti Data Platform.
<i>StorageConfigManager</i>	This class defines the operations on the storage config in Graviti.

class `graviti.manager.storage_config.StorageConfig(workspace, name)`

Bases: `graviti.utility.ReprMixin`

This class defines the structure of the storage config of Graviti Data Platform.

Parameters

- **workspace** (*graviti.Workspace*) – The workspace of the storage config.
- **response** – The response of the OpenAPI associated with the storage config:

```
{
  "id": <str>
  "name": <str>
  "config_type": <str>
  "backend_type": <str>
}
```

- **name** (*str*) –

name

The name of the storage config.

config_type

The type of the storage config.

backend_type

The backend type of the storage config.

classmethod from_response(*cls, workspace, response*)

Create a *StorageConfig* instance from the response.

Parameters

- **workspace** (*graviti.Workspace*) – The workspace of the storage config.
- **response** (*Dict[str, Any]*) – The response of the storage config:

```
{
  "id": <str>
  "name": <str>
  "config_type": <str>
  "backend_type": <str>
}
```

- **cls** (*Type[_T]*) –

Returns A *StorageConfig* instance created from the response.

Return type *_T*

class *graviti.manager.storage_config.StorageConfigManager*(*workspace*)

This class defines the operations on the storage config in Graviti.

Parameters **workspace** (*graviti.Workspace*) – Class *Workspace* instance.

property default_storage_config(*self*)

The default storage config of this workspace.

Returns The default storage config of this workspace.

Return type *str*

get(*self, name*)

Get a Graviti storage config with given name.

Parameters **name** (*str*) – The name of the storage config.

Returns The requested *storage_config* instance.

Raises *ResourceNameError* – When the given storage config name is invalid.

Return type *StorageConfig*

list(*self*)

List Graviti storage configs.

Returns The LazyPagingList of *StorageConfig* instances.

Return type *graviti.manager.lazy.LazyPagingList[StorageConfig]*

edit(*self*, *, *default_storage_config*)

Update Graviti storage config related configs.

Parameters *default_storage_config* (*str*) – The name of the new default storage config.

Raises *ResourceNameError* – When the given default storage config name is invalid.

Return type *None*

graviti.manager.tag

The implementation of the Tag and TagManager.

Module Contents

Classes

<i>Tag</i>	This class defines the structure of the tag of a commit.
<i>TagManager</i>	This class defines the operations on the tag in Graviti.

class *graviti.manager.tag.Tag*(*dataset*, *name*, *commit_id*)

Bases: *graviti.manager.commit.NamedCommit*

This class defines the structure of the tag of a commit.

Parameters

- **dataset** (*graviti.manager.dataset.Dataset*) – Class *Dataset* instance.
- **name** (*str*) – The name of the tag.
- **commit_id** (*Optional[str]*) – The commit id.

class *graviti.manager.tag.TagManager*(*dataset*)

This class defines the operations on the tag in Graviti.

Parameters *dataset* (*graviti.manager.dataset.Dataset*) – *Dataset* instance.

create(*self*, *name*, *revision=CURRENT_COMMIT*)

Create a tag for a commit.

Parameters

- **name** (*str*) – The tag name to be created for the specific commit.
- **revision** (*str*) – The information to locate the specific commit, which can be the commit id, the branch name, or the tag name. The default value is the current commit of the dataset.

Raises *NoCommitsError* – When create tags on the default branch without commit history.

Returns The *Tag* instance with the given name.

Return type *Tag*

get(*self*, *name*)

Get the certain tag with the given name.

Parameters *name* (*str*) – The required tag name.

Raises *ResourceNameError* – When the name is an empty string.

Returns The *Tag* instance with the given name.

Return type *Tag*

list(*self*)

List the information of tags.

Returns The LazyPagingList of *tags* instances.

Return type *graviti.manager.lazy.LazyPagingList[Tag]*

delete(*self*, *name*)

Delete a tag.

Parameters *name* (*str*) – The tag name to be deleted for the specific commit.

Raises *ResourceNameError* – When the name is an empty string.

Return type *None*

graviti.manager.workspace

The implementation of the Workspace.

Module Contents

Classes

<i>Workspace</i>	This class defines the initial client to interact between local and server.
------------------	---

class *graviti.manager.workspace.Workspace*(*access_key*, *url*="")

This class defines the initial client to interact between local and server.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.

property *datasets*(*self*)

Get class *DatasetManager* instance.

Returns Required *DatasetManager* instance.

Return type *graviti.manager.dataset.DatasetManager*

property `storage_configs(self)`

Get class *StorageConfigManager* instance.

Returns Required *StorageConfigManager* instance.

Return type *graviti.manager.storage_config.StorageConfigManager*

graviti.openapi

OpenAPI module.

Submodules

graviti.openapi.action

Interfaces about the actions.

Module Contents

Functions

<i>create_action</i> (access_key, url, workspace, dataset, *, name, payload)	Execute the OpenAPI <i>POST</i> <i>/v2/datasets/{workspace}/{dataset}/actions</i> .
<i>list_actions</i> (access_key, url, workspace, dataset, *, sort = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets/{workspace}/{dataset}/actions</i> .
<i>get_action</i> (access_key, url, workspace, dataset, *, action)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets/{workspace}/{dataset}/actions/{action}</i> .
<i>update_action</i> (access_key, url, workspace, dataset, *, action, name = None, state = None, payload = None)	Execute the OpenAPI <i>PATCH</i> <i>/v2/datasets/{workspace}/{dataset}/actions/{action}</i> .
<i>delete_action</i> (access_key, url, workspace, dataset, *, action)	Execute the OpenAPI <i>DELETE</i> <i>/v2/datasets/{workspace}/{dataset}/actions/{action}</i> .
<i>create_action_run</i> (access_key, url, workspace, dataset, *, action, arguments)	Execute the OpenAPI <i>POST</i> <i>/v2/datasets/{workspace}/{dataset}/actions/{action}/runs</i> .
<i>list_action_runs</i> (access_key, url, workspace, dataset, *, action, sort = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets/{workspace}/{dataset}/actions/{action}/runs</i> .
<i>get_action_run</i> (access_key, url, workspace, dataset, *, action, run_number)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets/{workspace}/{dataset}/actions/{action}/runs/{run_number}</i> .
<i>cancel_action_run</i> (access_key, url, workspace, dataset, *, action, run_number)	Execute the OpenAPI <i>POST</i> <i>/v2/datasets/{workspace}/{dataset}/actions/{action}/runs/{run_number}/cancel</i> .
<i>get_action_run_node_log</i> (access_key, url, workspace, dataset, *, action, run_number, node_id)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets/{workspace}/{dataset}/actions/{action}/runs/{run_number}/nodes/{node_id}/logs</i> .

`graviti.openapi.action.create_action(access_key, url, workspace, dataset, *, name, payload)`

Execute the OpenAPI *POST* */v2/datasets/{workspace}/{dataset}/actions*.

Parameters

- **access_key** (*str*) – User’s access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **name** (*str*) – The name of the action.
- **payload** (*str*) – The payload of the action.

Returns The response of OpenAPI.

Return type Dict[str, Any]

`graviti.openapi.action.list_actions(access_key, url, workspace, dataset, *, sort=None, offset=None, limit=None)`

Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/actions*.

Parameters

- **access_key** (*str*) – User’s access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **sort** (*graviti.utility.SortParam*) – The column and the direction the list result sorted by.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, Any]

`graviti.openapi.action.get_action(access_key, url, workspace, dataset, *, action)`

Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/actions/{action}*.

Parameters

- **access_key** (*str*) – User’s access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **action** (*str*) – The name of the action.

Returns The response of OpenAPI.

Return type Dict[str, Any]

`graviti.openapi.action.update_action(access_key, url, workspace, dataset, *, action, name=None, state=None, payload=None)`

Execute the OpenAPI *PATCH /v2/datasets/{workspace}/{dataset}/actions/{action}*.

Parameters

- **access_key** (*str*) – User’s access key.

- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **action** (*str*) – The name of the action.
- **name** (*Optional[str]*) – The new name of the action.
- **state** (*Optional[str]*) – The new state of the action.
- **payload** (*Optional[str]*) – The new payload of the action.

Returns The response of OpenAPI.

Return type Dict[str, Any]

`graviti.openapi.action.delete_action(access_key, url, workspace, dataset, *, action)`
Execute the OpenAPI *DELETE* `/v2/datasets/{workspace}/{dataset}/actions/{action}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **action** (*str*) – The name of the action.

Return type None

`graviti.openapi.action.create_action_run(access_key, url, workspace, dataset, *, action, arguments)`
Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{dataset}/actions/{action}/runs`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **action** (*str*) – The name of the action.
- **arguments** (*Optional[Dict[str, Any]]*) – The arguments of the action run.

Returns The response of OpenAPI.

Return type Dict[str, Any]

`graviti.openapi.action.list_action_runs(access_key, url, workspace, dataset, *, action, sort=None, offset=None, limit=None)`
Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/actions/{action}/runs`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.

- **action** (*str*) – The name of the action.
- **sort** (*graviti.utility.SortParam*) – The column and the direction the list result sorted by.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

`graviti.openapi.action.get_action_run(access_key, url, workspace, dataset, *, action, run_number)`
Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/actions/{action}/runs/{run_number}*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **action** (*str*) – The name of the action.
- **run_number** (*int*) – The number of the action run.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

`graviti.openapi.action.cancel_action_run(access_key, url, workspace, dataset, *, action, run_number)`
Execute the OpenAPI *POST /v2/datasets/{workspace}/{dataset}/actions/{action}/runs/{run_number}/cancel*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **action** (*str*) – The name of the action.
- **run_number** (*int*) – The number of the action run.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

`graviti.openapi.action.get_action_run_node_log(access_key, url, workspace, dataset, *, action, run_number, node_id)`
Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/actions/{action}/runs/{run_number}/nodes/{node_id}/logs*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.

- **dataset** (*str*) – Name of the dataset, unique for a user.
- **action** (*str*) – The name of the action.
- **run_number** (*int*) – The number of the action run.
- **node_id** (*str*) – The id of the action run node.

Returns The response of OpenAPI.

Return type `requests.models.Response`

`graviti.openapi.branch`

Interfaces about the branch.

Module Contents

Functions

<code>create_branch</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>name</i> , <i>revision</i>)	Execute the OpenAPI <i>POST</i> <code>/v2/datasets/{workspace}/{dataset}/branches.</code>
<code>list_branches</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>offset</i> = None, <i>limit</i> = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/branches.</code>
<code>get_branch</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>branch</i>)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/branches/{branch}.</code>
<code>delete_branch</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>branch</i>)	Execute the OpenAPI <i>DELETE</i> <code>/v2/datasets/{workspace}/{dataset}/branches/{branch}.</code>

`graviti.openapi.branch.create_branch`(*access_key*, *url*, *workspace*, *dataset*, *, *name*, *revision*)
Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{dataset}/branches.`

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **name** (*str*) – The name of the branch.
- **revision** (*str*) – The information to locate the specific commit, which can be the commit id, the branch name, or the tag name.

Returns The response of OpenAPI.

Return type `Dict[str, Any]`

Examples

```
>>> create_branch(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     name="branch-1",
...     revision="main"
... )
{
  "name": "main",
  "commit_id": "fde63f357daf46088639e9f57fd81cad",
  "parent_commit_id": "f68b1375454f459b8a486b8d1f4d9ddb",
  "title": "first commit",
  "description": "desc",
  "committer": "graviti-example",
  "committed_at": "2021-03-03T18:58:10Z"
}
```

`graviti.openapi.branch.list_branches(access_key, url, workspace, dataset, *, offset=None, limit=None)`
Execute the OpenAPI `GET /v2/datasets/{workspace}/{dataset}/branches`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, Any]

Examples

```
>>> list_branches(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST"
... )
{
  "branches": [
    {
      "name": "main",
      "commit_id": "fde63f357daf46088639e9f57fd81cad",
```

(continues on next page)

(continued from previous page)

```

        "parent_commit_id": "f68b1375454f459b8a486b8d1f4d9ddb",
        "title": "first commit",
        "description": "desc",
        "committer": "graviti-example",
        "committed_at": "2021-03-03T18:58:10Z"
    }
],
"offset": 0,
"record_size": 1,
"total_count": 1
}

```

`graviti.openapi.branch.get_branch(access_key, url, workspace, dataset, *, branch)`

Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/branches/{branch}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **branch** (*str*) – The name of the branch.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

Examples

```

>>> get_branch(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     branch="main",
... )
{
    "name": "main",
    "commit_id": "fde63f357daf46088639e9f57fd81cad",
    "parent_commit_id": "f68b1375454f459b8a486b8d1f4d9ddb",
    "title": "first commit",
    "description": "desc",
    "committer": "graviti-example",
    "committed_at": "2021-03-03T18:58:10Z"
}

```

`graviti.openapi.branch.delete_branch(access_key, url, workspace, dataset, *, branch)`

Execute the OpenAPI *DELETE* `/v2/datasets/{workspace}/{dataset}/branches/{branch}`.

Parameters

- **access_key** (*str*) – User's access key.

- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **branch** (*str*) – The name of the branch.

Return type None

Examples

```
>>> delete_branch(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     branch="branch-1",
... )
```

graviti.openapi.commit

Interfaces about the commit.

Module Contents

Functions

<code>commit_draft</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>draft_number</i> , <i>title</i> , <i>description</i> = None)	Execute the OpenAPI	<i>POST</i>
	<i>/v2/datasets/{workspace}/{dataset}/commits.</i>	
<code>list_commits</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>revision</i> = None, <i>offset</i> = None, <i>limit</i> = None)	Execute the OpenAPI	<i>GET</i>
	<i>/v2/datasets/{workspace}/{dataset}/commits.</i>	
<code>get_commit</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>commit_id</i>)	Execute the OpenAPI	<i>GET</i>
	<i>/v2/datasets/{workspace}/{dataset}/commits/{commit_id}.</i>	
<code>get_revision</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>revision</i>)	Execute the OpenAPI	<i>GET</i>
	<i>/v2/datasets/{workspace}/{dataset}/revisions/{revision}.</i>	

`graviti.openapi.commit.commit_draft`(*access_key*, *url*, *workspace*, *dataset*, *, *draft_number*, *title*, *description*=None)

Execute the OpenAPI *POST* */v2/datasets/{workspace}/{dataset}/commits.*

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **title** (*str*) – The draft title.

- **description** (*Optional[str]*) – The draft description.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> commit_draft(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     draft_number=2,
...     title="commit-2",
... )
{
  "commit_id": "85c57a7f03804ccc906632248dc8c359",
  "parent_commit_id": "784ba0d3bf0a41f6a7bfd771d8c00fcb",
  "title": "upload data",
  "description": "",
  "committer": "graviti-example",
  "committed_at": "2021-03-03T18:58:10Z"
}
```

`graviti.openapi.commit.list_commits(access_key, url, workspace, dataset, *, revision=None, offset=None, limit=None)`

Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/commits*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **revision** (*Optional[str]*) – The information to locate the specific commit, which can be the commit id, the branch name, or the tag name.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> list_commits(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
... )
{
  "commits": [
    {
      "commit_id": "85c57a7f03804ccc906632248dc8c359",
      "parent_commitId": "784ba0d3bf0a41f6a7bfd771d8c00fcb",
      "title": "upload data",
      "description": "",
      "committer": "graviti-example",
      "committed_at": "2021-03-03T18:58:10Z"
    }
  ],
  "offset": 0,
  "record_size": 1,
  "total_count": 1
}
```

`graviti.openapi.commit.get_commit(access_key, url, workspace, dataset, *, commit_id)`
 Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/commits/{commit_id}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **commit_id** (*str*) – The commit ID.

Returns The response of OpenAPI.

Return type Dict[str, Any]

Examples

```
>>> get_commit(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     commit_id="85c57a7f03804ccc906632248dc8c359"
... )
{
  "commit_id": "85c57a7f03804ccc906632248dc8c359",
  "parent_commit_id": "784ba0d3bf0a41f6a7bfd771d8c00fcb",
  "title": "upload data",
```

(continues on next page)

(continued from previous page)

```

    "description": "",
    "committer": "graviti-example",
    "committed_at": "2021-03-03T18:58:10Z"
  }

```

graviti.openapi.commit.get_revision(*access_key*, *url*, *workspace*, *dataset*, *, *revision*)
 Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/revisions/{revision}*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **revision** (*str*) – The information to locate the specific commit, which can be the commit id, the branch name, or the tag name.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

Examples

```

>>> get_revision(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "MNIST",
...     revision="branch-1"
... )
{
  "type": "BRANCH",
  "commit_id": "85c57a7f03804ccc906632248dc8c359",
  "parent_commit_id": "784ba0d3bf0a41f6a7bfd771d8c00fcb",
  "title": "upload data",
  "description": "",
  "committer": "graviti-example",
  "committed_at": "2021-03-03T18:58:10Z"
}

```

graviti.openapi.data

Interfaces about the data.

Module Contents

Functions

<code>list_draft_data</code> (access_key, url, workspace, dataset, *, draft_number, sheet, columns = None, order_by = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/data</code> .
<code>list_commit_data</code> (access_key, url, workspace, dataset, *, commit_id, sheet, columns = None, order_by = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/commits/{commit_id}/sheets/{sheet}/data</code> .
<code>update_data</code> (access_key, url, workspace, dataset, *, draft_number, sheet, data)	Execute the OpenAPI <i>PATCH</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/data</code> .
<code>add_data</code> (access_key, url, workspace, dataset, *, draft_number, sheet, data, strategy_arguments = None)	Execute the OpenAPI <i>POST</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/data</code> .
<code>delete_data</code> (access_key, url, workspace, dataset, *, draft_number, sheet, record_keys)	Execute the OpenAPI <i>DELETE</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/data</code> .

`graviti.openapi.data.list_draft_data`(access_key, url, workspace, dataset, *, draft_number, sheet, columns=None, order_by=None, offset=None, limit=None)
Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/data`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **columns** (*Optional[str]*) – The string of column names separated by |. Multiple indexes can be expressed using .. None means to get all columns.
- **order_by** (*Optional[str]*) – The string of column names separated by | whose order determines the precedence of the sort. The rest are sorted by `__record_key` first. Multiple indexes can be expressed using ..
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```

>>> list_draft_data(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     draft_number = 1,
...     sheet = "train",
...     order_by = "filename|attribute.weather",
... )
{
  "data": [
    {
      "__record_key": "123750493121329585",
      "filename": "0000f77c-6257be58.jpg",
      "image": {
        "url": "https://content-store-prod-vers",
        "checksum": "dcc197970e607f7576d978972f6fb312911ce005"
      },
      "attribute": {
        "weather": "clear",
        "scene": "city street",
        "timeofday": "daytime"
      },
      "box2ds": [
        {
          "xmin": 1125.902264,
          "xmax": 1156.978645,
          "ymin": 133.184488,
          "ymax": 210.875445,
          "category": "traffic light",
          "attribute": {
            "occluded": false,
            "truncated": false,
            "trafficLightColor": "G"
          }
        },
        {
          "xmin": 1156.978645,
          "xmax": 1191.50796,
          "ymin": 136.637417,
          "ymax": 210.875443,
          "category": "traffic light",
          "attribute": {
            "occluded": false,
            "truncated": false,
            "trafficLightColor": "G"
          }
        }
      ],
      ...
    ]
  },

```

(continues on next page)

(continued from previous page)

```

        ...(total 128 items)
    ],
    "offset": 0,
    "record_size": 128,
    "total_count": 700000
}

```

`graviti.openapi.data.list_commit_data(access_key, url, workspace, dataset, *, commit_id, sheet, columns=None, order_by=None, offset=None, limit=None)`

Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/commits/{commit_id}/sheets/{sheet}/data`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **commit_id** (*str*) – The commit id.
- **sheet** (*str*) – The sheet name.
- **columns** (*Optional[str]*) – The string of column names separated by |. Multiple indexes can be expressed using .. None means to get all columns.
- **order_by** (*Optional[str]*) – The string of column names separated by | whose order determines the precedence of the sort. The rest are sorted by `__record_key` first. Multiple indexes can be expressed using ..
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type `Dict[str, Any]`

Examples

```

>>> list_commit_data(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     commit_id = "fde63f357daf46088639e9f57fd81cad",
...     sheet = "train",
...     order_by = "filename|attribute.weather",
... )
{
  "data": [
    {
      "__record_key": "123750493121329585",

```

(continues on next page)

(continued from previous page)

```

        "filename": "0000f77c-6257be58.jpg",
        "image": {
            "url": "https://content-store-prod-vers",
            "checksum": "dcc197970e607f7576d978972f6fb312911ce005"
        },
        "attribute": {
            "weather": "clear",
            "scene": "city street",
            "timeofday": "daytime"
        },
        "box2ds": [
            {
                "xmin": 1125.902264,
                "xmax": 1156.978645,
                "ymin": 133.184488,
                "ymax": 210.875445,
                "category": "traffic light",
                "attribute": {
                    "occluded": false,
                    "truncated": false,
                    "trafficLightColor": "G"
                }
            },
            {
                "xmin": 1156.978645,
                "xmax": 1191.50796,
                "ymin": 136.637417,
                "ymax": 210.875443,
                "category": "traffic light",
                "attribute": {
                    "occluded": false,
                    "truncated": false,
                    "trafficLightColor": "G"
                }
            }
        ],
        ...
    ],
    "offset": 0,
    "record_size": 128,
    "total_count": 70000
}

```

`graviti.openapi.data.update_data(access_key, url, workspace, dataset, *, draft_number, sheet, data)`

Execute the OpenAPI *PATCH* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/data`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.

- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **data** (*Union[List[Dict[str, Any]], Tuple[Dict[str, Any], Ellipsis]*) – The update data.

Return type None

Examples

```
>>> update_data(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "OxfordIIITPet",
...     draft_number = 1,
...     sheet = "train",
...     data = [
...         {
...             "__record_key": "123750493121329585",
...             "filename": "0000f77c-6257be58.jpg",
...             "image": {
...                 "checksum": "dcc197970e607f7576d978972f6fb312911ce005"
...             },
...             "attribute": {
...                 "weather": "clear",
...                 "scene": "city street",
...                 "timeofday": "daytime"
...             },
...         },
...         {
...             "__record_key": "123750493121329585",
...             "filename": "0000f77c-62c2a288.jpg",
...             "image": {
...                 "checksum": "dcc197970e607f7576d978972f6fb2a2881ce004"
...             },
...             "attribute": {
...                 "weather": "clear",
...                 "scene": "highway",
...                 "timeofday": "dawn/dusk"
...             },
...         },
...     ],
... )
```

`graviti.openapi.data.add_data(access_key, url, workspace, dataset, *, draft_number, sheet, data, strategy_arguments=None)`

Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/data`.

Parameters

- **access_key** (*str*) – User's access key.

- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **data** (*Union[List[Dict[str, Any]], Tuple[Dict[str, Any], Ellipsis]*) – The update data.
- **strategy_arguments** (*Optional[Dict[str, Any]]*) – Arguments required by the `__record_key` generation strategy of the sheet.

Return type None

Examples

```
>>> add_data(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "OxfordIIITPet",
...     draft_number = 1,
...     sheet = "train",
...     data = [
...         {
...             "filename": "0000f77c-6257be58.jpg",
...             "image": {
...                 "checksum": "dcc197970e607f7576d978972f6fb312911ce005"
...             },
...             "attribute": {
...                 "weather": "clear",
...                 "scene": "city street",
...                 "timeofday": "daytime"
...             },
...         },
...         {
...             "filename": "0000f77c-62c2a288.jpg",
...             "image": {
...                 "checksum": "dcc197970e607f7576d978972f6fb2a2881ce004"
...             },
...             "attribute": {
...                 "weather": "clear",
...                 "scene": "highway",
...                 "timeofday": "dawn/dusk"
...             },
...         },
...     ],
... )
```

`graviti.openapi.data.delete_data(access_key, url, workspace, dataset, *, draft_number, sheet, record_keys)`
 Execute the OpenAPI `DELETE /v2/datasets/{workspace}/{dataset}/drafts/{draft_number} /sheets/{sheet}/data`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **record_keys** (*List[str]*) – The record keys of the data to be deleted.

Return type None

Examples

```
>>> delete_data(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "OxfordIIITPet",
...     draft_number = 1,
...     sheet = "train",
...     record_keys = ["123750493121329585", "123750493121329586"],
... )
```

graviti.openapi.dataset

Interfaces about the dataset.

Module Contents

Functions

<code>create_dataset</code> (access_key, url, name, *, alias = "", storage_config = None, with_draft = None)	Execute the OpenAPI <i>POST</i> <i>/v2/datasets</i> .
<code>get_dataset</code> (access_key, url, workspace, dataset)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets/{workspace}/{dataset}</i> .
<code>list_datasets</code> (access_key, url, *, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets</i> .
<code>update_dataset</code> (access_key, url, workspace, dataset, *, name = None, alias = None, default_branch = None)	Execute the OpenAPI <i>PATCH</i> <i>/v2/datasets/{workspace}/{dataset}</i> .
<code>delete_dataset</code> (access_key, url, workspace, dataset)	Execute the OpenAPI <i>DELETE</i> <i>/v2/datasets/{workspace}/{dataset}</i> .

`graviti.openapi.dataset.create_dataset`(access_key, url, name, *, alias="", storage_config=None, with_draft=None)

Execute the OpenAPI *POST* */v2/datasets*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **name** (*str*) – Name of the dataset, unique for a user.
- **alias** (*str*) – Alias of the dataset, default is "".
- **storage_config** (*Optional[str]*) – The auth storage config name.
- **with_draft** (*Optional[bool]*) – Whether to create a draft after the dataset is created. The default value of this parameter in OpenAPIv2 is False.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> create_dataset(  
...     "ACCESSKEY-*****",  
...     "https://api.graviti.com",  
...     "MNIST",  
... )  
{  
  "id": "2bc95d506db2401b898067f1045d7f68",  
  "name": "OxfordIIITPet",  
  "alias": "",  
  "workspace": "graviti-example",  
  "default_branch": "main",  
  "commit_id": None,  
  "cover_url": "https://tutu.s3.cn-northwest-1.amazonaws.com.cn/",  
  "creator": "czhual",  
  "created_at": "2021-03-03T18:58:10Z",  
  "updated_at": "2021-03-03T18:58:10Z",  
  "is_public": false,  
  "storage_config": "exampleConfigName",  
  "backend_type": "OSS"  
}
```

`graviti.openapi.dataset.get_dataset(access_key, url, workspace, dataset)`

Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> get_dataset(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "OxfordIIITPet"
... )
{
  "id": "2bc95d506db2401b898067f1045d7f68",
  "name": "OxfordIIITPet",
  "alias": "Oxford-IIIT Pet",
  "workspace": "graviti-example",
  "default_branch": "main",
  "commit_id": "a0d4065872f245e4ad1d0d1186e3d397",
  "cover_url": "https://tutu.s3.cn-northwest-1.amazonaws.com.cn/",
  "creator": "czhual",
  "created_at": "2021-03-03T18:58:10Z",
  "updated_at": "2021-03-03T18:58:10Z",
  "is_public": false,
  "storage_config": "exampleConfigName",
  "backend_type": "OSS"
}
```

`graviti.openapi.dataset.list_datasets(access_key, url, *, offset=None, limit=None)`

Execute the OpenAPI *GET /v2/datasets*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> list_datasets("ACCESSKEY-*****", "https://api.graviti.com")
{
  "datasets": [
    {
      "id": "2bc95d506db2401b898067f1045d7f68",
      "name": "OxfordIIITPet",
      "alias": "Oxford-IIIT Pet",
      "workspace": "graviti-example",
      "default_branch": "main",
      "commit_id": "a0d4065872f245e4ad1d0d1186e3d397",
```

(continues on next page)

(continued from previous page)

```

        "cover_url": "https://tutu.s3.cn-northwest-1.amazonaws.com.cn/",
        "created_at": "2021-03-03T18:58:10Z",
        "updated_at": "2021-03-03T18:58:10Z",
        "creator": "czhual",
        "is_public": false,
        "storage_config": "exampleConfigName",
        "backend_type": "OSS"
    }
],
"offset": 0,
"record_size": 1,
"total_count": 1
}

```

`graviti.openapi.dataset.update_dataset(access_key, url, workspace, dataset, *, name=None, alias=None, default_branch=None)`

Execute the OpenAPI *PATCH* `/v2/datasets/{workspace}/{dataset}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **name** (*Optional[str]*) – New name of the dataset, unique for a user.
- **alias** (*Optional[str]*) – New alias of the dataset.
- **default_branch** (*Optional[str]*) – User's chosen branch.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

Examples

```

>>> update_dataset(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "OxfordIIITPet",
...     name="OxfordIIITPets",
...     alias="Oxford-IIIT Pet",
...     default_branch="main",
... )
{
  "id": "2bc95d506db2401b898067f1045d7f68",
  "name": "OxfordIIITPet",
  "alias": "Oxford-IIIT Pet",
  "workspace": "graviti-example",
  "default_branch": "main",
  "commit_id": "a0d4065872f245e4ad1d0d1186e3d397",

```

(continues on next page)

(continued from previous page)

```

    "cover_url": "https://tutu.s3.cn-northwest-1.amazonaws.com.cn/",
    "created_at": "2021-03-03T18:58:10Z",
    "updated_at": "2021-03-03T18:58:10Z",
    "creator": "czhual",
    "is_public": false,
    "storage_config": "exampleConfigName",
    "backend_type": "OSS"
}

```

graviti.openapi.dataset.delete_dataset(*access_key*, *url*, *workspace*, *dataset*)

Execute the OpenAPI *DELETE* `/v2/datasets/{workspace}/{dataset}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.

Return type None

Examples

```

>>> delete_dataset(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "OxfordIIITPet",
... )

```

graviti.openapi.draft

Interfaces about the draft.

Module Contents

Functions

<code>create_draft</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, title, branch = None, description = None)	Execute the OpenAPI <i>POST</i> <code>/v2/datasets/{workspace}/{dataset}/drafts</code> .
<code>list_drafts</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, state = None, branch = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/drafts</code> .
<code>get_draft</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, draft_number)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}</code> .

continues on next page

Table 1.46 – continued from previous page

<code>update_draft</code> (<code>access_key</code> , <code>url</code> , <code>workspace</code> , <code>dataset</code> , *, draft_number, state = None, title = None, description = None)	Execute the OpenAPI <i>PATCH</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}</code> .
---	---

`graviti.openapi.draft.create_draft`(`access_key`, `url`, `workspace`, `dataset`, *, `title`, `branch=None`,
`description=None`)

Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{dataset}/drafts`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **title** (*str*) – The draft title.
- **branch** (*Optional[str]*) – The specified branch name. None means the default branch of the dataset.
- **description** (*Optional[str]*) – The draft description.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

Examples

```
>>> create_draft(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     title="draft-2",
...     branch="main",
... )
{
  "number": 2,
  "title": "draft-2",
  "description": "",
  "branch": "main",
  "state": "OPEN",
  "parent_commit_id": "85c57a7f03804ccc906632248dc8c359",
  "creator": "graviti-example",
  "created_at": "2021-03-03T18:58:10Z",
  "updated_at": "2021-03-03T18:58:10Z"
}
```

`graviti.openapi.draft.list_drafts`(`access_key`, `url`, `workspace`, `dataset`, *, `state=None`, `branch=None`,
`offset=None`, `limit=None`)

Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/drafts`.

Parameters

- **access_key** (*str*) – User's access key.

- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **state** (*Optional[str]*) – The draft state which includes “OPEN”, “CLOSED”, “COMMITTED”, “ALL” and None. None means listing open drafts.
- **branch** (*Optional[str]*) – The branch name. None means listing drafts from all branches.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> list_drafts(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
... )
{
  "drafts": [
    {
      "number": 2,
      "title": "draft-2",
      "description": "",
      "branch": "main",
      "state": "OPEN",
      "parent_commit_id": "85c57a7f03804ccc906632248dc8c359",
      "creator": "graviti-example",
      "created_at": "2021-03-03T18:58:10Z",
      "updated_at": "2021-03-03T18:58:10Z"
    }
  ],
  "offset": 0,
  "record_size": 1,
  "total_count": 1
}
```

`graviti.openapi.draft.get_draft(access_key, url, workspace, dataset, *, draft_number)`
 Execute the OpenAPI `GET /v2/datasets/{workspace}/{dataset}/drafts/{draft_number}`.

Parameters

- **access_key** (*str*) – User’s access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.

- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – Number of the draft.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> get_draft(  
...     "ACCESSKEY-*****",  
...     "https://api.graviti.com",  
...     "MNIST",  
...     "graviti-example",  
...     draft_number=2,  
... )  
{  
    "number": 2,  
    "title": "draft-2",  
    "description": "",  
    "branch": "main",  
    "state": "OPEN",  
    "parent_commit_id": "85c57a7f03804ccc906632248dc8c359",  
    "creator": "graviti-example",  
    "created_at": "2021-03-03T18:58:10Z",  
    "updated_at": "2021-03-03T18:58:10Z"  
}
```

`graviti.openapi.draft.update_draft(access_key, url, workspace, dataset, *, draft_number, state=None, title=None, description=None)`

Execute the OpenAPI *PATCH* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The updated draft number.
- **state** (*Optional* [*str*]) – The updated draft state which could be "CLOSED" or None. Where None means no change in state.
- **title** (*Optional* [*str*]) – The draft title.
- **description** (*Optional* [*str*]) – The draft description.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

Update the title or description of the draft:

```
>>> update_draft(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "MNIST",
...     draft_number=2,
...     title="draft-3"
... )
{
  "number": 2,
  "title": "draft-3",
  "description": "",
  "branch": "main",
  "state": "OPEN",
  "parent_commit_id": "85c57a7f03804ccc906632248dc8c359",
  "creator": "graviti-example",
  "created_at": "2021-03-03T18:58:10Z",
  "updated_at": "2021-03-04T18:58:10Z"
}
```

Close the draft:

```
>>> update_draft(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "MNIST",
...     draft_number=2,
...     state="CLOSED"
... )
{
  "number": 2,
  "title": "draft-3",
  "description": "",
  "branch": "main",
  "state": "CLOSED",
  "parent_commit_id": "85c57a7f03804ccc906632248dc8c359",
  "creator": "graviti-example",
  "created_at": "2021-03-03T18:58:10Z",
  "updated_at": "2021-03-05T18:58:10Z"
}
```

graviti.openapi.object

Interfaces about the dataset object.

Module Contents**Functions**

<code>get_object_permission</code>	(access_key, url, workspace, dataset, *, actions, is_internal = None, expired = None)	Execute the OpenAPI <i>GET</i> /v2/datasets/{workspace}/{dataset}/objects/permissions.
<code>copy_objects</code>	(access_key, url, workspace, target_dataset, *, source_dataset, keys)	Execute the OpenAPI <i>POST</i> /v2/datasets/{workspace}/{target_dataset}/objects/copy.

`graviti.openapi.object.get_object_permission`(access_key, url, workspace, dataset, *, actions, is_internal=None, expired=None)

Execute the OpenAPI *GET* /v2/datasets/{workspace}/{dataset}/objects/permissions.

Parameters

- **access_key** (*str*) – User’s access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **actions** (*str*) – The specific actions including “GET” and “PUT”. Supports multiple actions, which need to be separated by |, like “GET|PUT”.
- **is_internal** (*Optional[bool]*) – Whether to return the intranet upload address, the default value in the OpenAPI is False.
- **expired** (*Optional[int]*) – Token expiry time in seconds. It cannot be negative.

Returns The response of OpenAPI.

Return type Dict[str, Any]

Examples

Request permission to get dataset data from OSS:

```
>>> get_object_permission(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     actions="GET",
... )
{
  "backend_type": "OSS",
  "expire_at": "2022-07-12T06:07:52Z",
  "permission": {
```

(continues on next page)

(continued from previous page)

```

    "AccessKeyId": "LTAI4FjgXD3yFJUasdasd",
    "AccessKeySecret": "LTAI4FjgXD3yFJJKasdad",
    "SecurityToken": "CAISrgJ1q6Ft5B2yfSjIr5bkKILDaseqw",
    "bucket": "content-store-dev",
    "endpoint": "content-store-dev.oss-cn-qingdao.aliyuncs.com"
  }
}

```

Request permission to put dataset data to OSS:

```

>>> get_object_permission(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     actions="PUT",
... )
{
  "backend_type": "OSS",
  "expire_at": "2022-07-12T06:07:52Z",
  "permission": {
    "AccessKeyId": "LTAI4FjgXD3yFJUasdasd",
    "AccessKeySecret": "LTAI4FjgXD3yFJJKasdad",
    "SecurityToken": "CAISrgJ1q6Ft5B2yfSjIr5bkKILDaseqw",
    "bucket": "content-store-dev",
    "endpoint": "content-store-dev.oss-cn-qingdao.aliyuncs.com",
    "prefix": "051dd0676cc74f548a7e9b7ace45c26b/"
  }
}

```

Request permission to get dataset data from AZURE:

```

>>> get_object_permission(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     actions="GET",
... )
{
  "backend_type": "AZURE",
  "expire_at": "2022-07-12T06:07:52Z",
  "permission": {
    "container_name": "graviti210304",
    "account_name": "gra220303",
    "sas_param": "se=2022-07-21T10%3A07Z&sig=*****",
    "endpoint_prefix": "https://gra220303.blob.core.window.net/graviti210304/"
  }
}

```

Request permission to put dataset data to AZURE:

```
>>> get_object_permission(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     actions="PUT",
... )
{
  "backend_type": "AZURE",
  "expire_at": "2022-07-12T06:07:52Z",
  "permission": {
    "container_name": "graviti210304",
    "account_name": "gra220303",
    "prefix": "examplePrefix/",
    "sas_param": "se=2022-07-21T10%3A07Z&sig=*****",
    "endpoint_prefix": "https://gra220303.blob.core.window.net/graviti210304/"
  }
}
```

Request permission to get dataset data from S3:

```
>>> get_object_permission(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     actions="GET",
... )
{
  "backend_type": "S3",
  "expire_at": "2022-07-12T06:07:52Z",
  "permission": {
    "AccessKeyId": "ASIAQHT*****",
    "AccessKeySecret": "Y6x2a2cHlJdx*****",
    "SecurityToken": "FwoGZXIvYXdzEH0aDGYBu*****",
    "bucket": "fat-dataplatform",
    "endpoint": "s3.amazonaws.com",
    "region": "us-west-1"
  }
}
```

Request permission to put dataset data to S3:

```
>>> get_object_permission(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     actions="PUT",
... )
{
  "backend_type": "S3",
  "expire_at": "2022-07-12T06:07:52Z",
```

(continues on next page)

(continued from previous page)

```

"permission": {
  "AccessKeyId": "ASIAQHT*****",
  "AccessKeySecret": "Y6x2a2cHI1Jdx*****",
  "SecurityToken": "FwoGZXIvYXdzEH0aDGYBu*****",
  "bucket": "fat-dataplatform",
  "endpoint": "s3.amazonaws.com",
  "prefix": "051dd0676cc74f548a7e9b7ace45c26b/",
  "region": "us-west-1"
}
}

```

`graviti.openapi.object.copy_objects(access_key, url, workspace, target_dataset, *, source_dataset, keys)`
 Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{target_dataset}/objects/copy`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **target_dataset** (*str*) – The name of the target dataset.
- **source_dataset** (*str*) – The name of the source dataset.
- **keys** (*List[str]*) – The keys of the objects which need to be copied.

Returns The response of OpenAPI.

Return type Dict[str, List[str]]

Examples

```

>>> copy_objects(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     source_dataset="EMINST",
...     keys=["xxxxx/xxxxx", "xxxxx/xxxxx"]
... )
{
  keys: [
    "yyyyyyy/yyyyyy",
    "yyyyyyy/yyyyyy"
  ]
}

```

graviti.openapi.record

Interfaces about the record.

Module Contents**Functions**

<code>list_draft_records</code> (access_key, url, workspace, dataset, *, draft_number, sheet, columns = None, sort = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/records.</code>
<code>list_commit_records</code> (access_key, url, workspace, dataset, *, commit_id, sheet, columns = None, sort = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/commits/{commit_id}/sheets/{sheet}/records.</code>
<code>update_records</code> (access_key, url, workspace, dataset, *, draft_number, sheet, records)	Execute the OpenAPI <i>PATCH</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/records.</code>
<code>add_records</code> (access_key, url, workspace, dataset, *, draft_number, sheet, records, strategy_arguments = None)	Execute the OpenAPI <i>POST</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/records.</code>
<code>delete_records</code> (access_key, url, workspace, dataset, *, draft_number, sheet, record_keys)	Execute the OpenAPI <i>DELETE</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/records.</code>

`graviti.openapi.record.list_draft_records`(access_key, url, workspace, dataset, *, draft_number, sheet, columns=None, sort=None, offset=None, limit=None)

Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/records.`

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **columns** (*Optional[str]*) – The string of column names separated by `.`. Multiple indexes can be expressed using `..`. None means to get all columns.
- **sort** (*graviti.utility.typing.SortParam*) – The column and the direction the list result sorted by.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```

>>> list_draft_records(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     draft_number=1,
...     sheet="train",
... )
{
  "records": [
    {
      "__record_key": "123750493121329585",
      "filename": "0000f77c-6257be58.jpg",
      "image": {
        "url": "https://content-store-prod-vers",
        "checksum": "dcc197970e607f7576d978972f6fb312911ce005"
      },
      "attribute": {
        "weather": "clear",
        "scene": "city street",
        "timeofday": "daytime"
      },
      "box2ds": [
        {
          "xmin": 1125.902264,
          "xmax": 1156.978645,
          "ymin": 133.184488,
          "ymax": 210.875445,
          "category": "traffic light",
          "attribute": {
            "occluded": false,
            "truncated": false,
            "trafficLightColor": "G"
          }
        },
        {
          "xmin": 1156.978645,
          "xmax": 1191.50796,
          "ymin": 136.637417,
          "ymax": 210.875443,
          "category": "traffic light",
          "attribute": {
            "occluded": false,
            "truncated": false,
            "trafficLightColor": "G"
          }
        }
      ],
      ...
    ]
  },
  ...(total 128 items)

```

(continues on next page)

(continued from previous page)

```

],
"offset": 0,
"record_size": 128,
"total_count": 700000
}

```

`graviti.openapi.record.list_commit_records(access_key, url, workspace, dataset, *, commit_id, sheet, columns=None, sort=None, offset=None, limit=None)`

Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/commits/{commit_id}/sheets/{sheet}/records`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **commit_id** (*str*) – The commit id.
- **sheet** (*str*) – The sheet name.
- **columns** (*Optional[str]*) – The string of column names separated by `.`. Multiple indexes can be expressed using `..`. `None` means to get all columns.
- **sort** (*graviti.utility.typing.SortParam*) – The column and the direction the list result sorted by.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type `Dict[str, Any]`

Examples

```

>>> list_commit_records(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     commit_id="fde63f357daf46088639e9f57fd81cad",
...     sheet="train",
... )
{
  "records": [
    {
      "__record_key": "123750493121329585",
      "filename": "0000f77c-6257be58.jpg",
      "image": {
        "url": "https://content-store-prod-vers",

```

(continues on next page)

(continued from previous page)

```

        "checksum": "dcc197970e607f7576d978972f6fb312911ce005"
    },
    "attribute": {
        "weather": "clear",
        "scene": "city street",
        "timeofday": "daytime"
    },
    "box2ds": [
        {
            "xmin": 1125.902264,
            "xmax": 1156.978645,
            "ymin": 133.184488,
            "ymax": 210.875445,
            "category": "traffic light",
            "attribute": {
                "occluded": false,
                "truncated": false,
                "trafficLightColor": "G"
            }
        },
        {
            "xmin": 1156.978645,
            "xmax": 1191.50796,
            "ymin": 136.637417,
            "ymax": 210.875443,
            "category": "traffic light",
            "attribute": {
                "occluded": false,
                "truncated": false,
                "trafficLightColor": "G"
            }
        },
        ...
    ]
},
...(total 128 items)
],
"offset": 0,
"record_size": 128,
"total_count": 70000
}

```

`graviti.openapi.record.update_records`(*access_key*, *url*, *workspace*, *dataset*, *, *draft_number*, *sheet*, *records*)

Execute the OpenAPI *PATCH* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/records`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.

- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **records** (*Union[List[Dict[str, Any]], Tuple[Dict[str, Any], Ellipsis]]*) – The records to be updated.

Return type None

Examples

```
>>> update_records(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "OxfordIIITPet",
...     draft_number=1,
...     sheet="train",
...     records=[
...         {
...             "__record_key": "123750493121329585",
...             "filename": "0000f77c-6257be58.jpg",
...             "image": {
...                 "checksum": "dcc197970e607f7576d978972f6fb312911ce005"
...             },
...             "attribute": {
...                 "weather": "clear",
...                 "scene": "city street",
...                 "timeofday": "daytime"
...             },
...         },
...         {
...             "__record_key": "123750493121329585",
...             "filename": "0000f77c-62c2a288.jpg",
...             "image": {
...                 "checksum": "dcc197970e607f7576d978972f6fb2a2881ce004"
...             },
...             "attribute": {
...                 "weather": "clear",
...                 "scene": "highway",
...                 "timeofday": "dawn/dusk"
...             },
...         },
...     ],
... )
```

`graviti.openapi.record.add_records(access_key, url, workspace, dataset, *, draft_number, sheet, records, strategy_arguments=None)`

Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/records`.

Parameters

- **access_key** (*str*) – User's access key.

- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **records** (*Union[List[Dict[str, Any]], Tuple[Dict[str, Any], Ellipsis]*) – The records to be added.
- **strategy_arguments** (*Optional[Dict[str, Any]]*) – Arguments required by the `__record_key` generation strategy of the sheet.

Return type None

Examples

```
>>> add_records(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "OxfordIIITPet",
...     draft_number=1,
...     sheet="train",
...     records=[
...         {
...             "filename": "0000f77c-6257be58.jpg",
...             "image": {
...                 "checksum": "dcc197970e607f7576d978972f6fb312911ce005"
...             },
...             "attribute": {
...                 "weather": "clear",
...                 "scene": "city street",
...                 "timeofday": "daytime"
...             },
...         },
...         {
...             "filename": "0000f77c-62c2a288.jpg",
...             "image": {
...                 "checksum": "dcc197970e607f7576d978972f6fb2a2881ce004"
...             },
...             "attribute": {
...                 "weather": "clear",
...                 "scene": "highway",
...                 "timeofday": "dawn/dusk"
...             },
...         },
...     ],
... )
```

`graviti.openapi.record.delete_records(access_key, url, workspace, dataset, *, draft_number, sheet,`
`record_keys)`

Execute the OpenAPI *DELETE* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}/records`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **record_keys** (*List[str]*) – The keys of the records to be deleted.

Return type None

Examples

```
>>> delete_records(  
...     "ACCESSKEY-*****",  
...     "https://api.graviti.com",  
...     "graviti-example",  
...     "OxfordIIITPet",  
...     draft_number=1,  
...     sheet="train",  
...     record_keys=["123750493121329585", "123750493121329586"],  
... )
```

graviti.openapi.requests

The basic concepts and methods of the Graviti OpenAPI.

Module Contents**Functions**

<code>do(method, url, **kwargs)</code>	Send a request.
<code>open_api_do(method, access_key, url, **kwargs)</code>	Send a request to the Graviti OpenAPI.

Attributes

<code>RESPONSE_ERROR_DISTRIBUTOR</code>

`graviti.openapi.requests.RESPONSE_ERROR_DISTRIBUTOR`

`graviti.openapi.requests.do(method, url, **kwargs)`
Send a request.

Parameters

- **method** (*str*) – The method of the request.
- **url** (*str*) – The URL of the request.
- ****kwargs** – Extra keyword arguments to send in the GET request.
- **kwargs** (*Any*) –

Returns Response of the request.

Return type requests.models.Response

`graviti.openapi.requests.open_api_do(method, access_key, url, **kwargs)`

Send a request to the Graviti OpenAPI.

Parameters

- **method** (*str*) – The method of the request.
- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- ****kwargs** – Extra keyword arguments to send in the POST request.
- **kwargs** (*Any*) –

Raises [ResponseError](#) – When the status code OpenAPI returns is unexpected.

Returns Response of the request.

Return type requests.models.Response

graviti.openapi.schema

Interfaces about the schema.

Module Contents

Functions

<code>update_schema</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , <i>dataset</i> , *, <i>draft_number</i> , <i>sheet</i> , <i>patch</i> = None, <i>_schema</i> , <i>_avro_schema</i> , <i>_arrow_schema</i> = None)	Execute the OpenAPI <i>PATCH</i> <i>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}</i> <i>/sheets/{sheet}/schema</i> .
--	--

`graviti.openapi.schema.update_schema(access_key, url, workspace, dataset, *, draft_number, sheet,
patch=None, _schema, _avro_schema, _arrow_schema=None)`
Execute the OpenAPI *PATCH* */v2/datasets/{workspace}/{dataset}/drafts/{draft_number}*
/sheets/{sheet}/schema.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.

- **sheet** (*str*) – The sheet name.
- **patch** (*Optional[List[Dict[str, Any]]]*) – The list of patch operations which describe the changes to the json portex schema.
- **_schema** (*str*) –
- **_avro_schema** (*str*) –
- **_arrow_schema** (*Optional[str]*) –

Return type None

Examples

```
>>> update_schema(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     draft_number = 1,
...     sheet = "train",
...     _schema = '{"imports": [{"repo": "https://github.com/Project-OpenBytes/
↪portex-standard@main", "types": [{"name": "file.Image"}]}, {"type": "record",
↪"fields": [{"name": "filename", "type": "string"}, {"name": "image", "type":
↪"file.Image"}]}]',
...     _avro_schema = '{"type": "record", "name": "root", "namespace": "cn.graviti.
↪portex", "aliases": [], "fields": [{"name": "filename", "type": "string"}, {"name
↪": "image", "type": {"type": "record", "name": "image", "namespace": "cn.graviti.
↪portex.root", "aliases": [], "fields": [{"name": "checksum", "type": [null,
↪"string"]}]}]}]',
... )
```

graviti.openapi.search

Interfaces about the search.

Module Contents

Functions

<code>create_search_history</code> (access_key, url, workspace, dataset, *, commit_id = None, draft_number = None, sheet, criteria)	Execute the OpenAPI <i>POST</i> <i>/v2/datasets/{workspace}/{dataset}/searches.</i>
<code>list_search_histories</code> (access_key, url, workspace, dataset, *, commit_id = None, draft_number = None, sheet = None, sort = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets/{workspace}/{dataset}/searches.</i>
<code>get_search_history</code> (access_key, url, workspace, dataset, *, search_id)	Execute the OpenAPI <i>GET</i> <i>/v2/datasets/{workspace}/{dataset}/searches/{search_id}.</i>
<code>delete_search_history</code> (access_key, url, workspace, dataset, *, search_id)	Execute the OpenAPI <i>DELETE</i> <i>/v2/datasets/{workspace}/{dataset}/searches/{search_id}.</i>

continues on next page

Table 1.52 – continued from previous page

<code>get_search_record_count</code> (access_key, url, workspace, dataset, *, search_id)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/searches/{search_id}/record-count.</code>
<code>list_search_records</code> (access_key, url, workspace, dataset, *, search_id, sort = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/searches/{search_id}/records.</code>

`graviti.openapi.search.create_search_history`(access_key, url, workspace, dataset, *, commit_id=None, draft_number=None, sheet, criteria)

Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{dataset}/searches.`

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **dataset** (*str*) – The name of the dataset.
- **commit_id** (*Optional[str]*) – The commit id.
- **draft_number** (*Optional[int]*) – The draft number.
- **sheet** (*str*) – The name of the sheet.
- **criteria** (*Dict[str, Any]*) – The criteria of the search.

Returns The response of OpenAPI.

Return type `Dict[str, Any]`

Examples

```
>>> create_search_history(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "portex-test",
...     "BDD100K",
...     commit_id="89c33716f3834e188ac1ff749c6c270d",
...     sheet="train",
...     criteria={"where": {"$any_match": [{"$.box2ds", {"$eq": [{"$.category", 7}]}}]}
... )
{
  "id": "53dbbedf35064f21a7b85def60de840e",
  "commit_id": "89c33716f3834e188ac1ff749c6c270d",
  "sheet": "train",
  "criteria": {
    "where": {
      "$any_match": [{"$.box2ds", { "$eq": [{"$.category", 7] }}]
    }
  },
  "creator": "linjiX",
  "created_at": "2021-03-05T18:58:10Z",
```

(continues on next page)

(continued from previous page)

```

    "record_count": null
}

```

`graviti.openapi.search.list_search_histories(access_key, url, workspace, dataset, *, commit_id=None, draft_number=None, sheet=None, sort=None, offset=None, limit=None)`

Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/searches`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **dataset** (*str*) – The name of the dataset.
- **commit_id** (*Optional[str]*) – The commit id.
- **draft_number** (*Optional[int]*) – The draft number.
- **sheet** (*Optional[str]*) – The name of the sheet.
- **sort** (*graviti.utility.SortParam*) – The column and the direction the list result sorted by.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type `Dict[str, Any]`

Examples

```

>>> list_search_histories(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "portex-test",
...     "BDD100K",
... )
{
  "searches": [
    {
      "id": "a97a31b29c154b82b3049b7f46904b69",
      "draft_number": 2,
      "sheet": "test",
      "criteria": {
        "where": {
          "$any_match": ["$.box2ds", { "$eq": ["$.category", 7] }]
        }
      },
      "creator": "linjiX",

```

(continues on next page)

(continued from previous page)

```

        "created_at": "2021-03-06T18:58:10Z",
        "record_count": 200
    },
    {
        "id": "53dbbedf35064f21a7b85def60de840e",
        "commit_id": "89c33716f3834e188ac1ff749c6c270d",
        "sheet": "train",
        "criteria": {
            "where": {
                "$any_match": ["$.box2ds", { "$eq": ["$.category", 7] }]
            }
        },
        "creator": "linjiX",
        "created_at": "2021-03-05T18:58:10Z",
        "record_count": 1000
    }
],
"offset": 0,
"record_size": 2,
"total_count": 2
}

```

`graviti.openapi.search.get_search_history(access_key, url, workspace, dataset, *, search_id)`
 Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/searches/{search_id}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **dataset** (*str*) – The name of the dataset.
- **search_id** (*str*) – The search id.

Returns The response of OpenAPI.

Return type Dict[str, Any]

Examples

```

>>> get_search_history(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "portex-test",
...     "BDD100K",
...     search_id="53dbbedf35064f21a7b85def60de840e",
... )
{
    "id": "53dbbedf35064f21a7b85def60de840e",
    "commit_id": "89c33716f3834e188ac1ff749c6c270d",
    "sheet": "train",
    "criteria": {

```

(continues on next page)

(continued from previous page)

```

        "where": {
            "$any_match": [ "$.box2ds", { "$eq": [ "$.category", 7 ] } ]
        },
        "creator": "linjiX",
        "created_at": "2021-03-05T18:58:10Z",
        "record_count": 1000
    }
}

```

`graviti.openapi.search.delete_search_history(access_key, url, workspace, dataset, *, search_id)`
 Execute the OpenAPI *DELETE* `/v2/datasets/{workspace}/{dataset}/searches/{search_id}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **dataset** (*str*) – The name of the dataset.
- **search_id** (*str*) – The search id.

Return type None

Examples

```

>>> delete_search_history(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "portex-test",
...     "BDD100K",
...     search_id="53dbbedf35064f21a7b85def60de840e",
... )

```

`graviti.openapi.search.get_search_record_count(access_key, url, workspace, dataset, *, search_id)`
 Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/searches/{search_id}/record-count`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **dataset** (*str*) – The name of the dataset.
- **search_id** (*str*) – The search id.

Returns The response of OpenAPI.

Return type int

Examples

```
>>> get_search_record_count(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "portex-test",
...     "BDD100K",
...     search_id="53dbbedf35064f21a7b85def60de840e",
... )
1000
```

`graviti.openapi.search.list_search_records(access_key, url, workspace, dataset, *, search_id, sort=None, offset=None, limit=None)`

Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/searches/{search_id}/records`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **dataset** (*str*) – The name of the dataset.
- **search_id** (*str*) – The search id.
- **sort** (*graviti.utility.SortParam*) – The column and the direction the list result sorted by.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type `Dict[str, Any]`

Examples

```
>>> list_search_records(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "portex-test",
...     "BDD100K",
...     search_id="53dbbedf35064f21a7b85def60de840e",
... )
{
  "records": [
    {
      "__record_key": "2312312312321",
      "filename": "0000f77c-6257be58.jpg",
      "image": {
        "key": "dcc197970e607f7576d978972f6fb312911ce005",
        "extension": ".jpg",
```

(continues on next page)

(continued from previous page)

```

        "size": 52344,
        "width": 800,
        "height": 600
    },
    "attribute": {
        "weather": "clear",
        "scene": "city street",
        "timeofday": "daytime"
    }
},
...(total 5 items)
]
}

```

graviti.openapi.sheet

Interfaces about the sheet.

Module Contents

Functions

<code>create_sheet</code> (access_key, url, workspace, dataset, *, draft_number, name, schema, _avro_schema, _arrow_schema = None, record_key_strategy = None)	Execute the OpenAPI <i>POST</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets.</code>
<code>list_draft_sheets</code> (access_key, url, workspace, dataset, *, draft_number, with_record_count = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets.</code>
<code>list_commit_sheets</code> (access_key, url, workspace, dataset, *, commit_id, with_record_count = None, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/commits/{commit_id}/sheets.</code>
<code>get_draft_sheet</code> (access_key, url, workspace, dataset, *, draft_number, sheet, with_record_count = None, schema_format = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets.</code>
<code>get_commit_sheet</code> (access_key, url, workspace, dataset, *, commit_id, sheet, with_record_count = None, schema_format = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/commits/{commit_id}/sheets/{sheet}.</code>
<code>delete_sheet</code> (access_key, url, workspace, dataset, *, draft_number, sheet)	Execute the OpenAPI <i>DELETE</i> <code>/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}.</code>

`graviti.openapi.sheet.create_sheet`(access_key, url, workspace, dataset, *, draft_number, name, schema, _avro_schema, _arrow_schema=None, record_key_strategy=None)
Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets.`

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.

- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **name** (*str*) – The sheet name.
- **schema** (*str*) – The portex schema of the sheet.
- **record_key_strategy** (*Optional[str]*) – The `__record_key` generation strategy. If None, it is batch auto-increment sorting record key.
- **_avro_schema** (*str*) –
- **_arrow_schema** (*Optional[str]*) –

Return type None

Examples

```
>>> create_sheet(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     draft_number = 1,
...     name = "val",
...     schema = '{"imports": [{"repo": "https://github.com/Project-OpenBytes/
↪portex-standard@main", "types": [{"name": "file.Image"}]}], "type": "record",
↪"fields": [{"name": "filename", "type": "string"}, {"name": "image", "type":
↪"file.Image"}]}',
...     _avro_schema = '{"type": "record", "name": "root", "namespace": "cn.graviti.
↪portex", "aliases": [], "fields": [{"name": "filename", "type": "string"}, {"name
↪": "image", "type": {"type": "record", "name": "image", "namespace": "cn.graviti.
↪portex.root", "aliases": [], "fields": [{"name": "checksum", "type": [null,
↪"string"]}]}]}',
... )
```

`graviti.openapi.sheet.list_draft_sheets(access_key, url, workspace, dataset, *, draft_number, with_record_count=None, offset=None, limit=None)`

Execute the OpenAPI `GET /v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **with_record_count** (*Optional[bool]*) – Whether return the record count of each sheet. The default value of this param in OpenAPI is False.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.

- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> list_draft_sheets(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     draft_number = 1,
... )
{
  "sheets": [
    {
      "name": "test",
      "created_at": "2021-03-03T18:58:10Z",
      "updated_at": "2021-03-04T18:58:10Z",
    },
    {
      "name": "trainval",
      "created_at": "2021-03-05T18:58:10Z",
      "updated_at": "2021-03-06T18:58:10Z",
    }
  ],
  "offset": 0,
  "record_size": 2,
  "total_count": 2
}
```

`graviti.openapi.sheet.list_commit_sheets(access_key, url, workspace, dataset, *, commit_id, with_record_count=None, offset=None, limit=None)`

Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/commits/{commit_id}/sheets*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **commit_id** (*str*) – The commit id.
- **with_record_count** (*Optional[bool]*) – Whether return the record count of each sheet. The default value of this param in OpenAPI is False.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> list_commit_sheets(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     commit_id = "fde63f357daf46088639e9f57fd81cad",
... )
{
  "sheets": [
    {
      "name": "test",
      "created_at": "2021-03-03T18:58:10Z",
      "updated_at": "2021-03-04T18:58:10Z",
    },
    {
      "name": "trainval",
      "created_at": "2021-03-05T18:58:10Z",
      "updated_at": "2021-03-06T18:58:10Z",
    }
  ],
  "offset": 0,
  "record_size": 2,
  "total_count": 2
}
```

`graviti.openapi.sheet.get_draft_sheet(access_key, url, workspace, dataset, *, draft_number, sheet, with_record_count=None, schema_format=None)`

Execute the OpenAPI `GET /v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets`.

Parameters

- **access_key** (*str*) – User’s access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **with_record_count** (*Optional[bool]*) – Whether return the record count of each sheet. The default value of this param in OpenAPI is False.
- **schema_format** (*Optional[str]*) – Fill “JSON”/“YAML” to determine whether the schema_format of the returned schema is json or yaml. None means “JSON” format.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> get_draft_sheet(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     draft_number = 1,
...     sheet = "sheet-2",
...     with_record_count=True,
... )
{
  "name": "trainval",
  "created_at": "2021-03-05T18:58:10Z",
  "updated_at": "2021-03-06T18:58:10Z",
  "record_count": 10000,
  "schema": '{"imports": [{"repo": "https://github.com/Project-OpenBytes/..."}]}'
}
```

`graviti.openapi.sheet.get_commit_sheet(access_key, url, workspace, dataset, *, commit_id, sheet, with_record_count=None, schema_format=None)`

Execute the OpenAPI *GET* `/v2/datasets/{workspace}/{dataset}/commits/{commit_id}/sheets/{sheet}`.

Parameters

- **access_key** (*str*) – User’s access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **commit_id** (*str*) – The commit id..
- **sheet** (*str*) – The sheet name.
- **with_record_count** (*Optional[bool]*) – Whether return the record count of each sheet. The default value of this param in OpenAPI is False.
- **schema_format** (*Optional[str]*) – Fill “JSON”/“YAML” to determine whether the schema_format of the returned schema is json or yaml. None means “JSON” format.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> get_commit_sheet(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     commit_id = "fde63f357daf46088639e9f57fd81cad",
...     sheet = "sheet-2",
...     with_record_count=True,
... )
```

(continues on next page)

(continued from previous page)

```

... )
{
  "name": "trainval",
  "created_at": "2021-03-05T18:58:10Z",
  "updated_at": "2021-03-06T18:58:10Z",
  "record_count": 10000,
  "schema": '{"imports": [{"repo": "https://github.com/Project-OpenBytes/...'}
}

```

graviti.openapi.sheet.delete_sheet(*access_key*, *url*, *workspace*, *dataset*, *, *draft_number*, *sheet*)
 Execute the OpenAPI *DELETE* `/v2/datasets/{workspace}/{dataset}/drafts/{draft_number}/sheets/{sheet}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The name of the sheet to be deleted.

Return type None

Examples

```

>>> delete_sheet(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     draft_number=1,
...     sheet="sheet-2"
... )

```

graviti.openapi.storage_config

Interfaces about the storage config.

Module Contents

Functions

<code>list_storage_configs</code> (<i>access_key</i> , <i>url</i> , <i>workspace</i> , *, <i>sort</i> = None, <i>offset</i> = None, <i>limit</i> = None)	Execute the OpenAPI <i>GET</i> <code>/v2/workspaces/{workspace}/storage-configs</code> .
---	--

continues on next page

Table 1.54 – continued from previous page

<code>get_storage_config</code> (<code>access_key</code> , <code>url</code> , <code>workspace</code> , <code>storage_config</code>)	Execute the OpenAPI <i>GET</i> <code>/v2/workspaces/{workspace}/storage-configs/{storage_config}</code> .
<code>update_storage_configs</code> (<code>access_key</code> , <code>url</code> , <code>workspace</code> , <code>*</code> , <code>default_storage_config</code>)	Execute the OpenAPI <i>PATCH</i> <code>/v2/workspaces/{workspace}/storage-configs</code> .

`graviti.openapi.storage_config.list_storage_configs`(`access_key`, `url`, `workspace`, `*`, `sort=None`, `offset=None`, `limit=None`)

Execute the OpenAPI *GET* `/v2/workspaces/{workspace}/storage-configs`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **sort** (*graviti.utility.SortParam*) – The column and the direction the list result sorted by.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type `Dict[str, Any]`

Examples

```
>>> list_storage_configs("ACCESSKEY-*****", "https://api.graviti.com", "portex-
↪test")
{
  "default_storage_config": "AliCloud-oss-cn-shanghai",
  "storage_configs": [
    {
      "id": "2bc95d506db2401b898067f1045d7f60",
      "name": "AliCloud-oss-cn-shanghai",
      "config_type": "GRAVITI",
      "backend_type": "OSS"
    },
    {
      "id": "2bc95d506db2401b898067f1045d7f61",
      "name": "OSSConfig",
      "config_type": "AUTHORIZED",
      "backend_type": "OSS"
    }
  ],
  "offset": 0,
  "record_size": 2,
  "total_count": 2
}
```

`graviti.openapi.storage_config.get_storage_config(access_key, url, workspace, storage_config)`
 Execute the OpenAPI *GET* `/v2/workspaces/{workspace}/storage-configs/{storage_config}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **storage_config** (*str*) – The name of the storage config.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

Examples

```
>>> get_storage_config(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "portex-test",
...     "AliCloud-oss-cn-shanghai",
... )
{
  "id": "2bc95d506db2401b898067f1045d7f60",
  "name": "AliCloud-oss-cn-shanghai",
  "config_type": "GRAVITI",
  "backend_type": "OSS",
}
```

`graviti.openapi.storage_config.update_storage_configs(access_key, url, workspace, *, default_storage_config)`

Execute the OpenAPI *PATCH* `/v2/workspaces/{workspace}/storage-configs`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.
- **default_storage_config** (*str*) – New default storage config.

Return type None

Examples

```
>>> update_storage_config(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "portex-test",
...     "AliCloud-oss-cn-shanghai",
... )
```

graviti.openapi.tag

Interfaces about the tag.

Module Contents**Functions**

<code>create_tag</code> (access_key, url, workspace, dataset, *, name, revision)	Execute the OpenAPI <i>POST</i> <code>/v2/datasets/{workspace}/{dataset}/tags</code> .
<code>list_tags</code> (access_key, url, workspace, dataset, *, offset = None, limit = None)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/tags</code> .
<code>get_tag</code> (access_key, url, workspace, dataset, *, tag)	Execute the OpenAPI <i>GET</i> <code>/v2/datasets/{workspace}/{dataset}/tags/{tag}</code> .
<code>delete_tag</code> (access_key, url, workspace, dataset, *, tag)	Execute the OpenAPI <i>DELETE</i> <code>/v2/datasets/{workspace}/{dataset}/tags/{tag}</code> .

`graviti.openapi.tag.create_tag`(access_key, url, workspace, dataset, *, name, revision)

Execute the OpenAPI *POST* `/v2/datasets/{workspace}/{dataset}/tags`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **name** (*str*) – The tag name to be created for the specific commit.
- **revision** (*str*) – The information to locate the specific commit, which can be the commit id, the branch name, or the tag name.

Returns The response of OpenAPI.

Return type Dict[str, Any]

Examples

```
>>> create_tag(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     name="tag-2",
...     revision="986d8ea00da842ed85dd5d5cd14b5aef"
... )
{
  "name": "tag-2",
  "commit_id": "986d8ea00da842ed85dd5d5cd14b5aef",
  "parent_commit_id": "a0d4065872f245e4ad1d0d1186e3d397",
  "title": "commit-1",
```

(continues on next page)

(continued from previous page)

```

    "description": "",
    "committer": "graviti-example",
    "committed_at": "2021-03-03T18:58:10Z"
}

```

graviti.openapi.tag.list_tags(*access_key*, *url*, *workspace*, *dataset*, *, *offset=None*, *limit=None*)
 Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/tags*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **offset** (*Optional[int]*) – The offset of the page. The default value of this param in OpenAPIv2 is 0.
- **limit** (*Optional[int]*) – The limit of the page. The default value of this param in OpenAPIv2 is 128.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```

>>> list_tags(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST"
... )
{
  "tags": [
    {
      "name": "tag-2",
      "commit_id": "986d8ea00da842ed85dd5d5cd14b5aef",
      "parent_commit_id": "a0d4065872f245e4ad1d0d1186e3d397",
      "title": "commit-1",
      "description": "",
      "committer": "graviti-example",
      "committed_at": "2021-03-03T18:58:10Z"
    }
  ],
  "offset": 0,
  "record_size": 1,
  "total_count": 1
}

```

graviti.openapi.tag.get_tag(*access_key*, *url*, *workspace*, *dataset*, *, *tag*)
 Execute the OpenAPI *GET /v2/datasets/{workspace}/{dataset}/tags/{tag}*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **tag** (*str*) – The name of the tag to be got.

Returns The response of OpenAPI.

Return type Dict[*str*, *Any*]

Examples

```
>>> get_tag(  
...     "ACCESSKEY-*****",  
...     "https://api.graviti.com",  
...     "graviti-example",  
...     "MNIST",  
...     tag="tag-2"  
... )  
{  
    "name": "tag-2",  
    "commit_id": "986d8ea00da842ed85dd5d5cd14b5aef",  
    "parent_commit_id": "a0d4065872f245e4ad1d0d1186e3d397",  
    "title": "commit-1",  
    "description": "",  
    "committer": "graviti-example",  
    "committed_at": "2021-03-03T18:58:10Z"  
}
```

`graviti.openapi.tag.delete_tag(access_key, url, workspace, dataset, *, tag)`
Execute the OpenAPI *DELETE* `/v2/datasets/{workspace}/{dataset}/tags/{tag}`.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The workspace of the dataset.
- **dataset** (*str*) – Name of the dataset, unique for a user.
- **tag** (*str*) – The name of the tag to be deleted.

Return type None

Examples

```
>>> delete_tag(
...     "ACCESSKEY-*****",
...     "https://api.graviti.com",
...     "graviti-example",
...     "MNIST",
...     tag="tag-2"
... )
```

graviti.openapi.user

Interfaces about the user.

Module Contents

Functions

<code>get_current_user(access_key, url)</code>	Execute the OpenAPI <i>GET /v2/current-user</i> .
--	---

`graviti.openapi.user.get_current_user(access_key, url)`
Execute the OpenAPI *GET /v2/current-user*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> get_current_user("ACCESSKEY-*****", "https://api.graviti.com")
{
    "id": "41438e9df9a82a194e1e76cc31c1d8d4",
    "nickname": "czh ual",
    "email": "*****@graviti.com",
    "mobile": null,
    "description": "",
    "workspace": "graviti-example",
    "team": null
}
```

graviti.openapi.workspace

Interfaces about the workspace.

Module Contents**Functions**

<code>get_current_workspace</code> (access_key, url)	Execute the OpenAPI <i>GET /v2/current-workspace</i> .
<code>get_workspace</code> (access_key, url, workspace)	Execute the OpenAPI <i>GET /v2/workspaces/{workspace}</i> .

`graviti.openapi.workspace.get_current_workspace`(access_key, url)
Execute the OpenAPI *GET /v2/current-workspace*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> get_current_workspace("ACCESSKEY-*****", "https://api.graviti.com")
{
  "type": "TEAM",
  "id": "41438e9df9a82a194e1e76cc31c1d8d4",
  "name": "portex-test",
  "alias": "PortexTest",
  "description": "xxx",
  "email": "xxxx@xx.com",
  "location": "xxx",
}
```

`graviti.openapi.workspace.get_workspace`(access_key, url, workspace)
Execute the OpenAPI *GET /v2/workspaces/{workspace}*.

Parameters

- **access_key** (*str*) – User's access key.
- **url** (*str*) – The URL of the graviti website.
- **workspace** (*str*) – The name of the workspace.

Returns The response of OpenAPI.

Return type Dict[str, *Any*]

Examples

```
>>> get_workspace("ACCESSKEY-*****", "https://api.graviti.com", "portex-test")
{
  "type": "TEAM",
  "id": "41438e9df9a82a194e1e76cc31c1d8d4",
  "name": "portex-test",
  "alias": "PortexTest",
  "description": "xxx",
  "email": "xxxx@xx.com",
  "location": "xxx",
}
```

graviti.operation

Operation module.

Submodules

graviti.operation.common

Common tools.

Module Contents

Functions

<code>get_schema(schema)</code>	Get portex schema, avro schema and arrow schema.
---------------------------------	--

`graviti.operation.common.get_schema(schema)`
Get portex schema, avro schema and arrow schema.

Parameters `schema` (`graviti.portex.record`) – The portex schema.

Returns The tuple of portex schema, avro schema and arrow schema.

Return type Tuple[str, str, str]

graviti.operation.frame

Definitions of different operations on a DataFrame.

Module Contents

Classes

<i>DataFrameOperation</i>	This class defines the basic method of the operation on a DataFrame.
<i>DataOperation</i>	This class defines the basic method of the data operation on a DataFrame.
<i>AddData</i>	This class defines the operation that add data to a DataFrame.
<i>UpdateSchema</i>	This class defines the operation that update the schema of a DataFrame.
<i>UpdateData</i>	This class defines the operation that updates the data of a DataFrame.
<i>DeleteData</i>	This class defines the operation that delete the data of a DataFrame.

class graviti.operation.frame.DataFrameOperation

This class defines the basic method of the operation on a DataFrame.

get_file_count(self)

Get the file amount to be uploaded.

Returns The file amount to be uploaded.

Return type int

get_data_count(self)

Get the data amount to be uploaded.

Returns The data amount to be uploaded.

Return type int

abstract execute(self, dataset, *, draft_number, sheet, jobs, data_pbar, file_pbar)

Execute the OpenAPI create sheet.

Parameters

- **dataset** (*graviti.manager.Dataset*) – The Dataset instance.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **jobs** (*int*) – The number of the max workers in multi-thread operation.
- **data_pbar** (*tqdm.tqdm*) – The process bar for uploading structured data.
- **file_pbar** (*tqdm.tqdm*) – The process bar for uploading binary files.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type None

```
class graviti.operation.frame.DataOperation(data)
```

Bases: [DataFrameOperation](#)

This class defines the basic method of the data operation on a DataFrame.

Parameters *data* (*graviti.dataframe.DataFrame*) –

```
get_file_count(self)
```

Get the file amount to be uploaded.

Returns The file amount to be uploaded.

Return type int

```
get_data_count(self)
```

Get the data amount to be uploaded.

Returns The data amount to be uploaded.

Return type int

```
class graviti.operation.frame.AddData(data)
```

Bases: [DataOperation](#)

This class defines the operation that add data to a DataFrame.

Parameters *data* (*graviti.dataframe.DataFrame*) – The data to be added.

```
execute(self, dataset, *, draft_number, sheet, jobs, data_pbar, file_pbar)
```

Execute the OpenAPI add data.

Parameters

- **dataset** (*graviti.manager.Dataset*) – The Dataset instance.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **jobs** (*int*) – The number of the max workers in multi-thread operation.
- **data_pbar** (*tqdm.tqdm*) – The process bar for uploading structured data.
- **file_pbar** (*tqdm.tqdm*) – The process bar for uploading binary files.

Return type None

```
class graviti.operation.frame.UpdateSchema(schema, data)
```

Bases: [DataFrameOperation](#)

This class defines the operation that update the schema of a DataFrame.

Parameters

- **schema** (*graviti.portex.record*) – New portex schema after updated.
- **data** (*graviti.dataframe.DataFrame*) –

```
execute(self, dataset, *, draft_number, sheet, jobs, data_pbar, file_pbar)
```

Execute the OpenAPI update schema.

Parameters

- **dataset** (*graviti.manager.Dataset*) – The Dataset instance.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.

- **jobs** (*int*) – The number of the max workers in multi-thread operation.
- **data_pbar** (*tqdm. tqdm*) – The process bar for uploading structured data.
- **file_pbar** (*tqdm. tqdm*) – The process bar for uploading binary files.

Return type None

class graviti.operation.frame.UpdateData(*data*)

Bases: *DataOperation*

This class defines the operation that updates the data of a DataFrame.

Parameters **data** (*graviti.dataframe.DataFrame*) – The data for updating.

execute(*self, dataset, *, draft_number, sheet, jobs, data_pbar, file_pbar*)

Execute the OpenAPI add data.

Parameters

- **dataset** (*graviti.manager.Dataset*) – The Dataset instance.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **jobs** (*int*) – The number of the max workers in multi-thread operation.
- **data_pbar** (*tqdm. tqdm*) – The process bar for uploading structured data.
- **file_pbar** (*tqdm. tqdm*) – The process bar for uploading binary files.

Return type None

class graviti.operation.frame.DeleteData(*record_keys*)

Bases: *DataFrameOperation*

This class defines the operation that delete the data of a DataFrame.

Parameters **record_keys** (*List[str]*) – The record keys of the data to be deleted.

execute(*self, dataset, *, draft_number, sheet, jobs, data_pbar, file_pbar*)

Execute the OpenAPI delete data.

Parameters

- **dataset** (*graviti.manager.Dataset*) – The Dataset instance.
- **draft_number** (*int*) – The draft number.
- **sheet** (*str*) – The sheet name.
- **jobs** (*int*) – The number of the max workers in multi-thread operation.
- **data_pbar** (*tqdm. tqdm*) – The process bar for uploading structured data.
- **file_pbar** (*tqdm. tqdm*) – The process bar for uploading binary files.

Return type None

graviti.operation.sheet

Definitions of different operations about the sheet on a draft.

Module Contents

Classes

<i>SheetOperation</i>	This class defines the basic method of the operation about the sheet on a draft.
<i>CreateSheet</i>	This class defines the operation that create a sheet.
<i>DeleteSheet</i>	This class defines the operation that delete a sheet.

class graviti.operation.sheet.**SheetOperation**(*sheet*)

This class defines the basic method of the operation about the sheet on a draft.

Parameters **sheet** (*str*) – The sheet name.

abstract execute(*self, dataset, draft_number*)

Execute the OpenAPI create sheet.

Parameters

- **dataset** (*graviti.manager.Dataset*) – The Dataset instance.
- **draft_number** (*int*) – The draft number.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type None

class graviti.operation.sheet.**CreateSheet**(*sheet, schema*)

Bases: [*SheetOperation*](#)

This class defines the operation that create a sheet.

Parameters

- **sheet** (*str*) – The sheet name.
- **schema** (*graviti.portex.record*) – The schema of the DataFrame.

execute(*self, dataset, draft_number*)

Execute the OpenAPI create sheet.

Parameters

- **dataset** (*graviti.manager.Dataset*) – The Dataset instance.
- **draft_number** (*int*) – The draft number.

Return type None

class graviti.operation.sheet.**DeleteSheet**(*sheet*)

Bases: [*SheetOperation*](#)

This class defines the operation that delete a sheet.

Parameters **sheet** (*str*) –

execute(*self, dataset, draft_number*)

Execute the OpenAPI delete sheet.

Parameters

- **dataset** (*graviti.manager.Dataset*) – The Dataset instance.
- **draft_number** (*int*) – The draft number.

Return type None

graviti.paging

Paging module.

Submodules**graviti.paging.factory**

Paging list related class.

Module Contents**Classes**

<i>LazyFactoryBase</i>	LazyFactoryBase is the base class of the lazy facotry.
<i>LazyFactory</i>	LazyFactory is a factory for requesting source data and creating paging lists.
<i>LazySubFactory</i>	LazySubFactory is a factory for creating paging lists.
<i>LazyLowerCaseFactory</i>	LazyLowerCaseFactory is a factory to handle the case insensitive data from graviti back-end.
<i>LazyLowerCaseSubFactory</i>	LazyLowerCaseSubFactory is a sub-factory to handle the case insensitive data.

class graviti.paging.factory.LazyFactoryBase

LazyFactoryBase is the base class of the lazy facotry.

abstract create_list(self, mapper)

Create a paging list from the factory.

Parameters **mapper** (*Callable[[Any], _T]*) – A callable object to convert every item in the pyarrow array.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type *graviti.paging.lists.PagingList[_T]*

abstract create_mapped_list(self, mapper)

Create a paging list from the factory.

Parameters **mapper** (*Callable[[Any], _T]*) – A callable object to convert every item in the pyarrow array.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type *graviti.paging.lists.MappedPagingList[_T]*

abstract create_pyarrow_list(*self*)

Create a paging list from the factory.

Raises `NotImplementedError` – The method of the base class should not be called.

Return type `graviti.paging.lists.PyArrowPagingList[Any]`

class `graviti.paging.factory.LazyFactory`(*total_count*, *limit*, *getter*, *patype*)

Bases: `LazyFactoryBase`

`LazyFactory` is a factory for requesting source data and creating paging lists.

Parameters

- **total_count** (*int*) – The total count of the elements in the paging lists.
- **limit** (*int*) – The size of each lazy load page.
- **getter** (`Callable[[int, int], Any]`) – A callable object to get the source data.
- **patype** (`pyarrow.DataType`) – The pyarrow `DataType` of the data in the factory.

Examples

```
>>> import pyarrow as pa
>>> patype = pa.struct(
...     {
...         "remotePath": pa.string(),
...         "label": pa.struct({"CLASSIFICATION": pa.struct({"category": pa.
↪ string()})}),
...     }
... )
>>> TOTAL_COUNT = 10000
>>> def getter(offset: int, limit: int) -> List[Dict[str, Any]]:
...     stop = min(offset + limit, TOTAL_COUNT)
...     return [
...         {
...             "remotePath": f"{i:06}.jpg",
...             "label": {"CLASSIFICATION": {"category": "cat" if i % 2 else "dog"}}
↪ ,
...         }
...         for i in range(offset, stop)
...     ]
...
>>> factory = LazyFactory(TOTAL_COUNT, 128, getter, patype)
>>> paths = factory["remotePath"].create_pyarrow_list()
>>> categories = factory["label"]["CLASSIFICATION"]["category"].create_pyarrow_
↪ list()
>>> len(paths)
10000
>>> list(paths)
[<pyarrow.StringScalar: '000000.jpg'>,
 <pyarrow.StringScalar: '000001.jpg'>,
 <pyarrow.StringScalar: '000002.jpg'>,
 <pyarrow.StringScalar: '000003.jpg'>,
 <pyarrow.StringScalar: '000004.jpg'>,
 <pyarrow.StringScalar: '000005.jpg'>,
```

(continues on next page)

(continued from previous page)

```

...
...
<pyarrow.StringScalar: '000999.jpg'>]
>>> len(categories)
1000
>>> list(categories)
[<pyarrow.StringScalar: 'dog'>,
 <pyarrow.StringScalar: 'cat'>,
 <pyarrow.StringScalar: 'dog'>,
 <pyarrow.StringScalar: 'cat'>,
 <pyarrow.StringScalar: 'dog'>,
 ...
 ...
 <pyarrow.StringScalar: 'cat'>]

```

get_array(*self*, *pos*, *keys*)

Get the array from the factory.

Parameters

- **pos** (*int*) – The page number.
- **keys** (*Tuple[str, Ellipsis]*) – The keys to access the array from factory.

Returns The requested pyarrow array.

Return type pyarrow.Array

create_list(*self*, *mapper*)

Create a paging list from the factory.

Parameters **mapper** (*Callable[[Any], _T]*) – A callable object to convert every item in the pyarrow array.

Returns A paging list created from the factory.

Return type *graviti.paging.lists.PagingList[_T]*

create_mapped_list(*self*, *mapper*)

Create a paging list from the factory.

Parameters **mapper** (*Callable[[Any], _T]*) – A callable object to convert every item in the pyarrow array.

Returns A paging list created from the factory.

Return type *graviti.paging.lists.MappedPagingList[_T]*

create_pyarrow_list(*self*)

Create a paging list from the factory.

Returns A paging list created from the factory.

Return type *graviti.paging.lists.PyArrowPagingList[Any]*

get_page_lengths(*self*)

A Generator which generates the length of the pages in the factory.

Yields The page lengths.

Return type *Iterator[int]*

get_offsets(self)

Get the Offsets instance created by the total_count and limit of this factory.

Returns The Offsets instance created by the total_count and limit of this factory.

Return type *graviti.paging.offset.Offsets*

class *graviti.paging.factory.LazySubFactory*(factory, keys, patype)

Bases: *LazyFactoryBase*

LazySubFactory is a factory for creating paging lists.

Parameters

- **factory** (*LazyFactory*) – The source LazyFactory instance.
- **keys** (*Tuple[str, Ellipsis]*) – The keys to access the array from the source LazyFactory.
- **patype** (*pyarrow.DataType*) – The pyarrow DataType of the data in the sub-factory.

create_list(self, mapper)

Create a paging list from the factory.

Parameters **mapper** (*Callable[[Any], _T]*) – A callable object to convert every item in the pyarrow array.

Returns A paging list created from the factory.

Return type *graviti.paging.lists.PagingList[_T]*

create_mapped_list(self, mapper)

Create a paging list from the factory.

Parameters **mapper** (*Callable[[Any], _T]*) – A callable object to convert every item in the pyarrow array.

Returns A paging list created from the factory.

Return type *graviti.paging.lists.MappedPagingList[_T]*

create_pyarrow_list(self)

Create a paging list from the factory.

Returns A paging list created from the factory.

Return type *graviti.paging.lists.PyArrowPagingList[Any]*

class *graviti.paging.factory.LazyLowerCaseFactory*(total_count, limit, getter, patype)

Bases: *LazyFactory*

LazyLowerCaseFactory is a factory to handle the case insensitive data from graviti back-end.

Parameters

- **total_count** (*int*) – The total count of the elements in the paging lists.
- **limit** (*int*) – The size of each lazy load page.
- **getter** (*Callable[[int, int], Any]*) – A callable object to get the source data.
- **patype** (*pyarrow.DataType*) – The pyarrow DataType of the data in the factory.

get_array(self, pos, keys)

Get the array from the factory.

Parameters

- **pos** (*int*) – The page number.
- **keys** (*Tuple[str, Ellipsis]*) – The keys to access the array from factory.

Returns The requested pyarrow array.

Return type `pyarrow.Array`

class `graviti.paging.factory.LazyLowerCaseSubFactory`(*factory, keys, patype*)

Bases: `LazySubFactory`

`LazyLowerCaseSubFactory` is a sub-factory to handle the case insensitive data.

Parameters

- **factory** (`LazyFactory`) – The source `LazyFactory` instance.
- **keys** (*Tuple[str, Ellipsis]*) – The keys to access the array from the source `LazyFactory`.
- **patype** (`pyarrow.DataType`) – The `pyarrow.DataType` of the data in the sub-factory.

`graviti.paging.lists`

Paging list related class.

Module Contents

Classes

<code>PagingListBase</code>	<code>PagingListBase</code> is the base class of the paging list related classes.
<code>PagingList</code>	<code>PagingList</code> is a list composed of multiple lists (pages).
<code>MappedPagingList</code>	<code>MappedPagingList</code> is a list composed of multiple mapped pages.
<code>PyArrowPagingList</code>	<code>PyArrowPagingList</code> is a list composed of multiple <code>pyarrow</code> arrays (pages).

class `graviti.paging.lists.PagingListBase`(*iterable*)

Bases: `Sequence[_T]`, `graviti.utility.ReprMixin`

`PagingListBase` is the base class of the paging list related classes.

Parameters

- **array** – The input sequence.
- **iterable** (*Iterable[_T]*) –

get_item(*self, index*)

Get the element in `PagingList` at the given index.

Parameters **index** (*int*) – The input index.

Returns The element at the given index.

Return type `_T`

get_slice(*self*, *index*)

Get the sliced PagingList at the given slice.

Parameters

- **index** (*slice*) – The input slice.
- **self** (*_PLB*) –

Returns The sliced PagingList at the given slice.

Return type *_PLB*

set_item(*self*, *index*, *value*)

Update the element value in PagingList at the given index.

Parameters

- **index** (*int*) – The element index.
- **value** (*_T*) – The value needs to be set into the PagingList.

Return type *None*

set_slice(*self*, *index*, *values*)

Update the element values at the given slice with input PagingList.

Parameters

- **index** (*slice*) – The element slice.
- **values** (*_PLB*) – The PagingList which contains the elements to be set.
- **self** (*_PLB*) –

Raises **ValueError** – When the input size mismatches with the slice size (when step != 1).

Return type *None*

set_slice_iterable(*self*, *index*, *values*)

Update the element values in PagingList at the given slice with iterable object.

Parameters

- **index** (*slice*) – The element slice.
- **values** (*Iterable[_T]*) – The iterable object which contains the elements to be set.

Raises **ValueError** – When the assign input size mismatches with the slice size (when step != 1).

Return type *None*

extend(*self*, *values*)

Extend PagingList by appending elements from another PagingList.

Parameters

- **values** (*_PLB*) – The PagingList which contains the elements to be extended.
- **self** (*_PLB*) –

Return type *None*

extend_iterable(*self*, *values*)

Extend PagingList by appending elements from the iterable.

Parameters **values** (*Iterable[_T]*) – Elements to be extended into the PagingList.

Return type None

extend_nulls(*self*, *size*)

Extend PagingList by appending nulls.

Parameters **size** (*int*) – The size of the nulls to be extended.

Return type None

copy(*self*)

Return a copy of the paging list.

Returns A copy of the paging list.

Parameters **self** (*_PLB*) –

Return type *_PLB*

class graviti.paging.lists.**PagingList**(*iterable*)

Bases: *PagingListBase*[*_T*]

PagingList is a list composed of multiple lists (pages).

Parameters **iterable** (*Iterable*[*_T*]) –

classmethod **from_factory**(*cls*, *factory*, *keys*, *mapper*)

Create PagingList from LazyFactory.

Parameters

- **factory** (*graviti.paging.factory.LazyFactory*) – The parent LazyFactory instance.
- **keys** (*Tuple*[*str*, *Ellipsis*]) – The keys to access the array from factory.
- **mapper** (*Callable*[[*Any*], *_T*]) – A callable object to convert every item in the pyarrow array.
- **cls** (*Type*[*_PL*]) –

Returns The PagingList instance created from given factory.

Return type *_PL*

class graviti.paging.lists.**MappedPagingList**(*iterable*)

Bases: *PagingListBase*[*_T*]

MappedPagingList is a list composed of multiple mapped pages.

Parameters **iterable** (*Iterable*[*_T*]) –

classmethod **from_array**(*cls*, *array*, *mapper*)

Create MappedPagingList from the source array.

Parameters

- **array** (*Sequence*[*_T*]) – The source array of the paging list.
- **mapper** (*Callable*[[*Any*], *_T*]) – A callable object to convert every item in the pyarrow array.
- **cls** (*Type*[*_MPL*]) –

Returns The PagingList instance created from the given array.

Return type *_MPL*

classmethod from_factory(cls, factory, keys, mapper)

Create MappedPagingList from LazyFactory.

Parameters

- **factory** (graviti.paging.factory.LazyFactory) – The parent LazyFactory instance.
- **keys** (Tuple[str, Ellipsis]) – The keys to access the array from factory.
- **mapper** (Callable[[Any], _T]) – A callable object to convert every item in the pyarrow array.
- **cls** (Type[_MPL]) –

Returns The PagingList instance created from given factory.

Return type _MPL

copy(self, copier, mapper)

Return a copy of the paging list.

Parameters

- **copier** (Callable[[_T], _T]) – A callable object to convert loaded items in the source page to the copied page.
- **mapper** (Callable[[Any], _T]) – The mapper of the new mapped page.
- **self** (_MPL) –

Returns A copy of the paging list.

Return type _MPL

class graviti.paging.lists.PyArrowPagingList(iterable)

Bases: [PagingListBase](#)[_T]

PyArrowPagingList is a list composed of multiple pyarrow arrays (pages).

Parameters

- **array** – The input pyarrow array.
- **iterable** (Iterable[_T]) –

classmethod from_pyarrow(cls, array)

Create PyArrowPagingList from pyarrow array.

Parameters

- **array** (pyarrow.Array) – The input pyarrow array.
- **cls** (Type[_PPL]) –

Returns The PyArrowPagingList instance created from given pyarrow array.

Return type _PPL

classmethod from_factory(cls, factory, keys, patype)

Create PyArrowPagingList from LazyFactory.

Parameters

- **factory** (graviti.paging.factory.LazyFactory) – The parent LazyFactory instance.
- **keys** (Tuple[str, Ellipsis]) – The keys to access the array from factory.

- **patype** (*pyarrow.DataType*) – The pyarrow *DataType* of the elements in the list.
- **cls** (*Type[_PPL]*) –

Returns The *PyArrowPagingList* instance created from given factory.

Return type *_PPL*

get_slice(*self, index*)

Get the sliced *PyArrowPagingList* at the given slice.

Parameters

- **index** (*slice*) – The input slice.
- **self** (*_PPL*) –

Returns The sliced *PyArrowPagingList* at the given slice.

Return type *_PPL*

set_slice(*self, index, values*)

Update the element values at the given slice with input *PyArrowPagingList*.

Parameters

- **index** (*slice*) – The element slice.
- **values** (*_PPL*) – The *PyArrowPagingList* which contains the elements to be set.
- **self** (*_PPL*) –

Raises **ArrowTypeError** – When two pyarrow types mismatch.

Return type *None*

extend(*self, values*)

Extend *PyArrowPagingList* by appending elements from another *PyArrowPagingList*.

Parameters

- **values** (*_PPL*) – The *PyArrowPagingList* which contains the elements to be extended.
- **self** (*_PPL*) –

Raises **ArrowTypeError** – When two pyarrow types mismatch.

Return type *None*

extend_nulls(*self, size*)

Extend *PyArrowPagingList* by appending nulls.

Parameters **size** (*int*) – The size of the nulls to be extended.

Return type *None*

copy(*self*)

Return a copy of the paging list.

Returns A copy of the paging list.

Parameters **self** (*_PPL*) –

Return type *_PPL*

to_pyarrow(*self*)

Convert the paging list to pyarrow *ChunkedArray*.

Returns The pyarrow *ChunkedArray*.

Return type pyarrow.ChunkedArray

graviti.paging.offset

Paging list offset related class.

Module Contents

Classes

<i>Offsets</i>	The offsets manager of the paging list.
class graviti.paging.offset. Offsets (<i>total_count</i> , <i>limit</i>) The offsets manager of the paging list.	
Parameters • total_count (<i>int</i>) – The total count of the elements in the paging list. • limit (<i>int</i>) – The size of each page.	
update (<i>self</i> , <i>start</i> , <i>stop</i> , <i>lengths</i>) Update the offsets when setting or deleting paging list items.	
Parameters • start (<i>int</i>) – The start index. • stop (<i>int</i>) – The stop index. • lengths (<i>Iterable[int]</i>) – The length of the set values.	
Return type None	
get_coordinate (<i>self</i> , <i>index</i>) Get the page coordinate of the elements.	
Parameters index (<i>int</i>) – The index of the element in paging list.	
Returns The page number and the index of the page.	
Return type Tuple[int, int]	
extend (<i>self</i> , <i>lengths</i>) Update the offsets when extending the paging list.	
Parameters lengths (<i>Iterable[int]</i>) – The lengths of the extended pages.	
Return type None	
copy (<i>self</i>) Return a copy of the Offsets.	
Returns A copy of the Offsets.	
Parameters self (<i>_O</i>) –	
Return type <i>_O</i>	

graviti.paging.page

Page related class.

Module Contents

Classes

<i>PageBase</i>	PageBase is the base class of array wrapper and represents a page in paging list.
<i>Page</i>	Page is an array wrapper and represents a page in paging list.
<i>SlicedPage</i>	SlicedPage is an array wrapper and represents a sliced page in paging list.
<i>LazyPage</i>	LazyPage is a placeholder when the paging list page is not loaded yet.
<i>LazySlicedPage</i>	LazySlicedPage is a placeholder when the sliced paging list page is not loaded yet.
<i>MappedPageBase</i>	MappedPageBase is the base class of the page with mapper, is used for nested DataFrame.
<i>MappedPage</i>	MappedPage is an array wrapper and represents a page in paging list.
<i>MappedSlicedPage</i>	MappedSlicedPage is an array wrapper and represents a sliced page in paging list.
<i>MappedLazyPage</i>	LazyPage with a mapper for converting every item in the source array.
<i>MappedLazySlicedPage</i>	LazySlicedPage with a mapper for converting every item in the source array.

class graviti.paging.page.**PageBase**

Bases: Sequence[_T]

PageBase is the base class of array wrapper and represents a page in paging list.

get_item(self, index)

Return the item at the given index.

Parameters **index** (*int*) – Position of the mutable sequence.

Returns The item at the given index.

Return type _T

abstract **get_slice**(self, start=None, stop=None, step=None)

Return a sliced page according to the given start and stop index.

Parameters

- **start** (*Optional[int]*) – The start index.
- **stop** (*Optional[int]*) – The stop index.
- **step** (*Optional[int]*) – The slice step.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type *PageBase*[_T]

abstract `get_array(self)`

Get the array inside the page.

Raises `NotImplementedError` – The method of the base class should not be called.

Return type `Sequence[_T]`

class `graviti.paging.page.Page(array)`

Bases: `PageBase[_T]`

Page is an array wrapper and represents a page in paging list.

Parameters `array` (`Sequence[_T]`) – The internal sequence of page.

get_slice(*self*, *start=None*, *stop=None*, *step=None*)

Return a sliced page according to the given start and stop index.

Parameters

- **start** (`Optional[int]`) – The start index.
- **stop** (`Optional[int]`) – The stop index.
- **step** (`Optional[int]`) – The slice step.

Returns A sliced page according to the given start and stop index.

Return type `SlicedPage[_T]`

get_array(*self*)

Get the array inside the page.

Returns The array inside the page.

Return type `Sequence[_T]`

class `graviti.paging.page.SlicedPage(ranging, source_array)`

Bases: `PageBase[_T]`

SlicedPage is an array wrapper and represents a sliced page in paging list.

Parameters

- **ranging** (`range`) – The range instance of this page.
- **array** – The internal sequence of page.
- **source_array** (`Sequence[_T]`) –

get_slice(*self*, *start=None*, *stop=None*, *step=None*)

Return a sliced page according to the given start and stop index.

Parameters

- **start** (`Optional[int]`) – The start index.
- **stop** (`Optional[int]`) – The stop index.
- **step** (`Optional[int]`) – The slice step.

Returns A sliced page according to the given start and stop index.

Return type `SlicedPage[_T]`

get_array(*self*)

Get the array inside the page.

Returns The array inside the page.

Return type `Sequence[_T]`

class `graviti.paging.page.LazyPage(length, array_getter)`

Bases: `PageBase[_T]`

`LazyPage` is a placeholder when the paging list page is not loaded yet.

Parameters

- **length** (`int`) – The length of this page.
- **array_getter** (`Callable[[], Sequence[_T]]`) – A callable object to get the source array.

get_slice(`self, start=None, stop=None, step=None`)

Return a lazy sliced page according to the given start and stop index.

Parameters

- **start** (`Optional[int]`) – The start index.
- **stop** (`Optional[int]`) – The stop index.
- **step** (`Optional[int]`) – The slice step.

Returns A sliced page according to the given start and stop index.

Return type `LazySlicedPage[_T]`

get_array(`self`)

Get the array inside the page.

Returns The array inside the page.

Return type `Sequence[_T]`

class `graviti.paging.page.LazySlicedPage(ranging, array_getter)`

Bases: `PageBase[_T]`

`LazySlicedPage` is a placeholder when the sliced paging list page is not loaded yet.

Parameters

- **ranging** (`range`) – The range instance of this page.
- **array_getter** (`Callable[[], Sequence[_T]]`) – A callable object to get the source array.

get_slice(`self, start=None, stop=None, step=None`)

Return a lazy sliced page according to the given start and stop index.

Parameters

- **start** (`Optional[int]`) – The start index.
- **stop** (`Optional[int]`) – The stop index.
- **step** (`Optional[int]`) – The slice step.

Returns A sliced page according to the given start and stop index.

Return type `LazySlicedPage[_T]`

get_array(`self`)

Get the array inside the page.

Returns The array inside the page.

Return type `Sequence[_T]`

class graviti.paging.page.**MappedPageBase**

Bases: [PageBase](#)[_T]

MappedPageBase is the base class of the page with mapper, is used for nested DataFrame.

abstract copy(*self, copier, mapper*)

Return a copy of the mapped page.

Parameters

- **copier** (*Callable*[[[Any](#)], [Any](#)]) – A callable object to convert loaded items in the source page to the copied page.
- **mapper** (*Callable*[[[Any](#)], [Any](#)]) – The mapper of the new mapped page.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type [MappedPageBase](#)[_T]

class graviti.paging.page.**MappedPage**(*array*)

Bases: [MappedPageBase](#)[_T], [Page](#)[_T]

MappedPage is an array wrapper and represents a page in paging list.

Parameters **array** (*Sequence*[_T]) –

get_slice(*self, start=None, stop=None, step=None*)

Return a sliced page according to the given start and stop index.

Parameters

- **start** (*Optional*[int]) – The start index.
- **stop** (*Optional*[int]) – The stop index.
- **step** (*Optional*[int]) – The slice step.

Returns A sliced page according to the given start and stop index.

Return type [MappedSlicedPage](#)[_T]

copy(*self, copier, mapper*)

Return a copy of the mapped page.

Parameters

- **copier** (*Callable*[[_T], _T]) – A callable object to convert loaded items in the source page to the copied page.
- **mapper** (*Callable*[[[Any](#)], [Any](#)]) – The mapper of the new mapped page.

Returns A copy of the mapped page.

Return type [MappedPage](#)[_T]

class graviti.paging.page.**MappedSlicedPage**(*ranging, source_array*)

Bases: [MappedPageBase](#)[_T], [SlicedPage](#)[_T]

MappedSlicedPage is an array wrapper and represents a sliced page in paging list.

Parameters

- **ranging** (*range*) –
- **source_array** (*Sequence*[_T]) –

get_slice(*self, start=None, stop=None, step=None*)

Return a sliced page according to the given start and stop index.

Parameters

- **start** (*Optional[int]*) – The start index.
- **stop** (*Optional[int]*) – The stop index.
- **step** (*Optional[int]*) – The slice step.

Returns A sliced page according to the given start and stop index.

Return type *MappedSlicedPage*[_T]

copy(*self, copier, mapper*)

Return a copy of the mapped page.

Parameters

- **copier** (*Callable[[Any], Any]*) – A callable object to convert loaded items in the source page to the copied page.
- **mapper** (*Callable[[Any], Any]*) – The mapper of the new mapped page.

Returns A copy of the mapped page.

Return type *MappedPage*[_T]

class graviti.paging.page.**MappedLazyPage**(*length, array_getter, mapper*)

Bases: *MappedPageBase*[_T]

LazyPage with a mapper for converting every item in the source array.

Parameters

- **length** (*int*) – The length of this page.
- **array_getter** (*Callable[[], Sequence[_T]]*) – A callable object to get the source array.
- **mapper** (*Callable[[Any], Any]*) – A callable object to convert every item in the source array.

get_slice(*self, start=None, stop=None, step=None*)

Return a lazy sliced page according to the given start and stop index.

Parameters

- **start** (*Optional[int]*) – The start index.
- **stop** (*Optional[int]*) – The stop index.
- **step** (*Optional[int]*) – The slice step.

Returns A sliced page according to the given start and stop index.

Return type Union[*MappedLazySlicedPage*[_T], *MappedSlicedPage*[_T]]

get_array(*self*)

Get the array inside the page.

Returns The array inside the page.

Return type *Sequence*[_T]

copy(*self, copier, mapper*)

Return a copy of the mapped page.

Parameters

- **copier** (*Callable*[[*Any*], *Any*]) – A callable object to convert loaded items in the source page to the copied page.
- **mapper** (*Callable*[[*Any*], *Any*]) – The mapper of the new mapped page.

Returns A copy of the mapped page.

Return type Union[*MappedPage*[_T], *MappedLazyPage*[_T]]

class graviti.paging.page.**MappedLazySlicedPage**(*ranging*, *array_getter*, *mapper*)

Bases: *MappedPageBase*[_T]

LazySlicedPage with a mapper for converting every item in the source array.

Parameters

- **ranging** (*range*) – The range instance of this page.
- **array_getter** (*Callable*[[], *Sequence*[_T]]) – A callable object to get the source array.
- **mapper** (*Callable*[[*Any*], *Any*]) – A callable object to convert every item in the source array.

get_slice(*self*, *start=None*, *stop=None*, *step=None*)

Return a lazy sliced page according to the given start and stop index.

Parameters

- **start** (*Optional*[*int*]) – The start index.
- **stop** (*Optional*[*int*]) – The stop index.
- **step** (*Optional*[*int*]) – The slice step.

Returns A sliced page according to the given start and stop index.

Return type Union[*MappedLazySlicedPage*[_T], *MappedSlicedPage*[_T]]

get_array(*self*)

Get the array inside the page.

Returns The array inside the page.

Return type *Sequence*[_T]

copy(*self*, *copier*, *mapper*)

Return a copy of the mapped page.

Parameters

- **copier** (*Callable*[[*Any*], *Any*]) – A callable object to convert loaded items in the source page to the copied page.
- **mapper** (*Callable*[[*Any*], *Any*]) – The mapper of the new mapped page.

Returns A copy of the mapped page.

Return type Union[*MappedPage*[_T], *MappedLazySlicedPage*[_T]]

graviti.paging.wrapper

PyArrow array wrapper related class.

Module Contents

Classes

<i>WrapperRegister</i>	The class decorator to connect pyarrow type and the pyarrow array wrapper.
<i>ScalarWrapper</i>	The wrapper of pyarrow scalar.
<i>ArrayWrapper</i>	The wrapper of pyarrow array.
<i>StructScalarWrapper</i>	The wrapper of pyarrow StructScalar to make it case insensitive.
<i>StructArrayWrapper</i>	The wrapper of pyarrow StructArray to make it case insensitive.
<i>ListScalarWrapper</i>	The wrapper of pyarrow ListScalar to make it case insensitive.
<i>ListArrayWrapper</i>	The wrapper of pyarrow ListArray to make it case insensitive.

class graviti.paging.wrapper.**WrapperRegister**(*pyarrow_type_id*)
The class decorator to connect pyarrow type and the pyarrow array wrapper.

Parameters **pyarrow_type_id** (*int*) – The PyArrow type id.

classmethod **get**(*cls*, *pyarrow_type_id*)
Get the corresponding registered pyarrow array wrapper.

Parameters **pyarrow_type_id** (*int*) – The PyArrow type id.

Returns The corresponding registered pyarrow array wrapper.

Return type Type[*ArrayWrapper*]

class graviti.paging.wrapper.**ScalarWrapper**(*scalar*)
The wrapper of pyarrow scalar.

Parameters **scalar** (*pyarrow.scalar*) – The PyArrow scalar needs to be wrapped.

property **is_valid**(*self*)
The wrapper of pyarrow Scalar.is_valid method.

Returns Bool value indicating whether this scalar is None.

Return type bool

as_py(*self*)
The wrapper of pyarrow Scalar.as_py method.

Returns Return this value as a Python builtin object.

Return type *Any*

class graviti.paging.wrapper.**ArrayWrapper**(*array*)
The wrapper of pyarrow array.

Parameters **array** (*pyarrow.Array*) – The PyArrow array needs to be wrapped.

class graviti.paging.wrapper.**StructScalarWrapper**(*scalar*)

Bases: [ScalarWrapper](#)

The wrapper of pyarrow StructScalar to make it case insensitive.

Parameters **scalar** (*pyarrow.StructScalar*) – The PyArrow StructScalar needs to be wrapped.

classmethod **from_wrapper**(*cls, scalar, wrappers*)

Create StructScalarWrapper instance by inputing scalar and wrappers.

Parameters

- **scalar** (*pyarrow.ListScalar*) – The PyArrow StructScalar needs to be wrapped.
- **wrappers** (*Dict[str, Type[ArrayWrapper]]*) – The wrappers of the input scalar.
- **cls** (*Type[_S]*) –

Returns The StructScalarWrapper instance created by the input scalar and wrapper.

Return type *_S*

class graviti.paging.wrapper.**StructArrayWrapper**(*array*)

Bases: [ArrayWrapper](#)

The wrapper of pyarrow StructArray to make it case insensitive.

Parameters **array** (*pyarrow.StringArray*) – The PyArrow StructArray instance needs to be wrapped.

field(*self, key*)

The wrapper of pyarrow StructArray.field method.

Parameters **key** (*str*) – The name of the field.

Returns The child array belonging to the field.

Return type *pyarrow.Array*

class graviti.paging.wrapper.**ListScalarWrapper**(*scalar*)

Bases: [ScalarWrapper](#)

The wrapper of pyarrow ListScalar to make it case insensitive.

Parameters **scalar** (*pyarrow.ListScalar*) – The PyArrow ListScalar instance needs to be wrapped.

classmethod **from_wrapper**(*cls, scalar, wrapper*)

Create ListScalarWrapper instance by inputing scalar and wrapper.

Parameters

- **scalar** (*pyarrow.ListScalar*) – The PyArrow ListScalar instance needs to be wrapped.
- **wrapper** (*Type[ArrayWrapper]*) – The wrapper of the input scalar.
- **cls** (*Type[_LS]*) –

Returns The ListScalarWrapper instance created by the input scalar and wrapper.

Return type *_LS*

property **values**(*self*)

The wrapper of pyarrow ListScalar.values attr.

Returns The internal values of the pyarrow scalar.

Return type *ArrayWrapper*

class graviti.paging.wrapper.ListArrayWrapper(array)

Bases: *ArrayWrapper*

The wrapper of pyarrow ListArray to make it case insensitive.

Parameters *array* (pyarrow.ListArray) – The PyArrow ListScalar instance needs to be wrapped.

classmethod from_wrapper(cls, array, wrapper)

Create ListScalarWrapper instance by inputting scalar and wrapper.

Parameters

- **array** (pyarrow.ListArray) – The PyArrow ListArray instance needs to be wrapped.
- **wrapper** (Type[*ArrayWrapper*]) – The wrapper of the input array.
- **cls** (Type[_LA]) –

Returns The ListScalarWrapper instance created by the input scalar and wrapper.

Return type _LA

graviti.portex

Schema module.

Submodules

graviti.portex.avro

Code converting PyArrow schema to Avro Schema.

Module Contents

Classes

AvroSchema

AvroField

AvroPrimitiveSchema

AvroRecord

AvroArray

PortexEnum

PortexDate

continues on next page

Table 1.66 – continued from previous page

*PortexTime**PortexTimestamp**PortexTimedelta***Functions***convert_portex_schema_to_avro*(portex_type)**class** graviti.portex.avro.**AvroSchema**(name, namespace, portex_type)**Parameters**

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** (*graviti.portex.base.PortexType*) –

abstract *to_json*(*self*)**Return type** Dict[*str*, *Any*]**class** graviti.portex.avro.**AvroField**(type_, name, *, optional=True, has_default=False, default=None)**Parameters**

- **type_** (*AvroSchema*) –
- **name** (*str*) –
- **optional** (*bool*) –
- **has_default** (*bool*) –
- **default** (*Any*) –

to_json(*self*)**Return type** Dict[*str*, *Any*]**class** graviti.portex.avro.**AvroPrimitiveSchema**(name, namespace, portex_type)Bases: *AvroSchema***Parameters**

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** (*graviti.portex.base.PortexType*) –

to_json(*self*)

Return type str

class graviti.portex.avro.**AvroRecord**(*name, namespace, portex_type*)

Bases: [AvroSchema](#)

Parameters

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** ([graviti.portex.builtin.record](#)) –

to_json(*self*)

Return type Dict[str, *Any*]

class graviti.portex.avro.**AvroArray**(*name, namespace, portex_type*)

Bases: [AvroSchema](#)

Parameters

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** ([graviti.portex.builtin.array](#)) –

to_json(*self*)

Return type Dict[str, *Any*]

class graviti.portex.avro.**PortexEnum**(*name, namespace, portex_type*)

Bases: [AvroSchema](#)

Parameters

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** ([graviti.portex.builtin.enum](#)) –

to_json(*self*)

Return type Dict[str, *Any*]

class graviti.portex.avro.**PortexDate**(*name, namespace, portex_type*)

Bases: [AvroSchema](#)

Parameters

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** ([graviti.portex.base.PortexType](#)) –

to_json(*self*)

Return type Dict[str, *Any*]

class graviti.portex.avro.**PortexTime**(*name, namespace, portex_type*)

Bases: [AvroSchema](#)

Parameters

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** (`graviti.portex.builtin.time`) –

to_json(*self*)

Return type Dict[*str*, *Any*]

class `graviti.portex.avro.PortexTimestamp`(*name*, *namespace*, *portex_type*)

Bases: `AvroSchema`

Parameters

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** (`graviti.portex.builtin.timestamp`) –

to_json(*self*)

Return type Dict[*str*, *Any*]

class `graviti.portex.avro.PortexTimedelta`(*name*, *namespace*, *portex_type*)

Bases: `AvroSchema`

Parameters

- **name** (*str*) –
- **namespace** (*str*) –
- **portex_type** (`graviti.portex.builtin.timedelta`) –

to_json(*self*)

Return type Dict[*str*, *Any*]

`graviti.portex.avro.convert_portex_schema_to_avro`(*portex_type*)

Parameters **portex_type** (`graviti.portex.builtin.record`) –

Return type Dict[*str*, *Any*]

graviti.portex.base

The base elements of Portex type.

Module Contents

Classes

<i>PortexType</i>	The base class of portex type.
<i>PortexRecordBase</i>	The base class of record like Portex types.

Functions

<i>read_yaml</i> (path)	Read a yaml file into Portex type.
<i>read_json</i> (path)	Read a json file into Portex type.

Attributes

<i>PYARROW_TYPE_ID_TO_PORTEX_TYPE</i>

graviti.portex.base.PYARROW_TYPE_ID_TO_PORTEX_TYPE

class graviti.portex.base.**PortexType**

The base class of portex type.

property **imports**(*self*)

Get the PortexType imports.

Returns The Imports instance of this PortexType.

Return type *graviti.portex.package.Imports*

classmethod **from_pyobj**(*cls, content, _imports=None*)

Create Portex type instance from python dict.

Parameters

- **content** (*Dict[str, Any]*) – A python dict representing a Portex type.
- **cls** (*Type[_T]*) –
- **_imports** (*Optional[graviti.portex.package.Imports]*) –

Returns A Portex type instance created from the input python dict.

Return type *_T*

classmethod **from_pyarrow**(*cls, paarray*)

Create Portex type instance from PyArrow type.

Parameters

- **paarray** (*pyarrow.Array*) – The PyArrow array.
- **cls** (*Type[_T]*) –

Raises **TypeError** – When the PyArrow type is not supported.

Returns The created Portex type instance.

Return type `_T`

classmethod `from_json(cls, content)`

Create Portex type instance from JSON string.

Parameters

- **content** (*str*) – A JSON string representing a Portex type.
- **cls** (*Type[_T]*) –

Returns A Portex type instance created from the input JSON string.

Return type `_T`

classmethod `from_yaml(cls, content)`

Create Portex type instance from YAML string.

Parameters

- **content** (*str*) – A YAML string representing a Portex type.
- **cls** (*Type[_T]*) –

Returns A Portex type instance created from the input YAML string.

Return type `_T`

to_pyobj(*self*, *_with_imports=True*)

Dump the instance to a python dict.

Returns A python dict representation of the Portex type.

Parameters *_with_imports* (*bool*) –

Return type `Dict[str, Any]`

to_json(*self*)

Dump the instance to a JSON string.

Returns A JSON representation of the Portex type.

Return type `str`

to_yaml(*self*)

Dump the instance to a YAML string.

Returns A YAML representation of the Portex type.

Return type `str`

abstract **to_pyarrow**(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Raises **NotImplementedError** – The method of the base class should not be called.

Returns The corresponding builtin PyArrow DataType.

Parameters *_to_backend* (*bool*) –

Return type `pyarrow.DataType`

abstract **to_builtin**(*self*)

Expand the top level type to Portex builtin type.

Raises **NotImplementedError** – The method of the base class should not be called.

Return type `graviti.portex.builtin.PortexBuiltinType`

copy(*self*)

Get a copy of the portex type.

Returns A copy of the portex type.**Parameters** *self* (*_T*) –**Return type** *_T***class** graviti.portex.base.**PortexRecordBase**Bases: *PortexType*, graviti.utility.UserMutableMapping[str, *PortexType*]

The base class of record like Portex types.

insert(*self*, *index*, *name*, *portex_type*)

Insert the name and portex_type at the index.

Parameters

- **index** (*int*) – The index to insert the field.
- **name** (*str*) – The name of the field to be inserted.
- **portex_type** (*PortexType*) – The portex_type of the field to be inserted.

Return type None**astype**(*self*, *name*, *portex_type*)

Convert the type of the field with the given name to the new PortexType.

Parameters

- **name** (*str*) – The name of the field to convert.
- **portex_type** (*PortexType*) – The new PortexType of the field to convert to.

Return type None**rename**(*self*, *old_name*, *new_name*)

Rename the name of a field.

Parameters

- **old_name** (*str*) – The current name of the field to be renamed.
- **new_name** (*str*) – The new name of the field to assign.

Return type None**to_pyarrow**(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow StructType.

Returns The corresponding builtin PyArrow StructType.**Parameters** *_to_backend* (*bool*) –**Return type** pyarrow.StructTypegraviti.portex.base.**read_yaml**(*path*)

Read a yaml file into Portex type.

Parameters *path* (*graviti.utility.PathLike*) – The path of the yaml file.**Returns** A Portex type instance created from the input yaml file.**Return type** *PortexType*graviti.portex.base.**read_json**(*path*)

Read a json file into Portex type.

Parameters `path` (*graviti.utility.PathLike*) – The path of the json file.

Returns A Portex type instance created from the input json file.

Return type *PortexType*

graviti.portex.builder

Portex type builder related classes.

Module Contents

Classes

<i>PackageRepo</i>	The local git repo of the external Portex package.
<i>PackageBuilder</i>	The builder of the external Portex package.
<i>TypeBuilder</i>	The builder of the external Portex template type.
<i>BuilderImports</i>	The imports of the Portex template type.

Functions

<i>build_package</i> (url, revision)	Build an external package.
--------------------------------------	----------------------------

Attributes

<i>EXTERNAL_TYPE_TO_CONTAINER</i>

graviti.portex.builder.**EXTERNAL_TYPE_TO_CONTAINER**

class graviti.portex.builder.**PackageRepo**(url, revision)

The local git repo of the external Portex package.

Parameters

- **url** (*str*) – The git repo url of the external package.
- **revision** (*str*) – The git repo revision (tag/commit) of the external package.

get_root(*self*)

Get the root directory path of the package repo.

Returns The root directory path of the package repo.

Raises **TypeError** – when the “ROOT.yaml” not found or more than one “ROOT.yaml” found.

Return type `pathlib.Path`

class graviti.portex.builder.**PackageBuilder**(url, revision)

The builder of the external Portex package.

Parameters

- **url** (*str*) – The git repo url of the external package.
- **revision** (*str*) – The git repo revision (tag/commit) of the external package.

build(*self*)

Build the Portex external package.

Returns The builded Portex external package.

Return type *graviti.portex.package.ExternalPackage*

class *graviti.portex.builder.TypeBuilder*(*name*, *path*, *builder*)

The builder of the external Portex template type.

Parameters

- **name** (*str*) – The name of the Portex template type.
- **path** (*pathlib.Path*) – The source file path of the Portex template type.
- **package** – The package the Portex template type belongs to.
- **builder** (*PackageBuilder*) –

build(*self*)

Build the Portex external type.

Returns The builded Portex external type.

Raises **TypeError** – Raise when circular reference detected.

Return type *Type[graviti.portex.external.PortexExternalType]*

class *graviti.portex.builder.BuilderImports*

Bases: *graviti.portex.package.Imports*

The imports of the Portex template type.

Parameters **package** – The package the portex belongs to.

classmethod **from_pyobj**(*cls*, *content*, *builder*)

Create Imports instance from python list.

Parameters

- **content** (*List[Dict[str, Any]]*) – A python list representing imported types.
- **builder** (*PackageBuilder*) – The package builder.
- **cls** (*Type[_I]*) –

Returns A Imports instance created from the input python list.

Return type *_I*

graviti.portex.builder.build_package(*url*, *revision*)

Build an external package.

Parameters

- **url** (*str*) – The git repo url of the external package.
- **revision** (*str*) – The git repo revision (tag/commit) of the external package.

Returns The ExternalPackage instance.

Return type *graviti.portex.package.ExternalPackage*

graviti.portex.builtin

The Portex builtin types.

Module Contents**Classes**

<i>PortexBuiltinType</i>	The base class of Portex builtin type.
<i>string</i>	Portex primitive type <code>string</code> .
<i>binary</i>	Portex primitive type <code>binary</code> .
<i>boolean</i>	Portex primitive type <code>boolean</code> .
<i>int32</i>	Portex primitive type <code>int32</code> .
<i>int64</i>	Portex primitive type <code>int64</code> .
<i>float32</i>	Portex primitive type <code>float32</code> .
<i>float64</i>	Portex primitive type <code>float64</code> .
<i>record</i>	Portex complex type <code>record</code> .
<i>enum</i>	Portex complex type <code>enum</code> .
<i>array</i>	Portex complex type <code>array</code> .
<i>date</i>	Portex temporal type <code>date</code> .
<i>time</i>	Portex temporal type <code>time</code> .
<i>timestamp</i>	Portex temporal type <code>timestamp</code> .
<i>timedelta</i>	Portex temporal type <code>timedelta</code> .

Attributes

<i>tz_checker</i>
<i>builtins</i>

`graviti.portex.builtin.tz_checker`

`graviti.portex.builtin.builtins`

class `graviti.portex.builtin.PortexBuiltinType`(*nullable=False*)

Bases: `graviti.portex.base.PortexType`

The base class of Portex builtin type.

Parameters `nullable` (*bool*) –

to_builtin(*self*)

Expand the top level type to Portex builtin type.

Returns The expanded Portex builtin type.

Parameters `self` (*_T*) –

Return type *_T*

class `graviti.portex.builtin.string`(*nullable=False*)

Bases: `PortexBuiltinType`

Portex primitive type string.

Parameters `nullable` (*bool*) – Whether it is a nullable type.

Examples

```
>>> t = string()
>>> t
string()
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters `_to_backend` (*bool*) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.binary(nullable=False)`

Bases: [*PortexBuiltinType*](#)

Portex primitive type binary.

Parameters `nullable` (*bool*) – Whether it is a nullable type.

Examples

```
>>> t = binary()
>>> t
binary()
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters `_to_backend` (*bool*) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.boolean(nullable=False)`

Bases: [*PortexBuiltinType*](#)

Portex primitive type boolean.

Parameters `nullable` (*bool*) – Whether it is a nullable type.

Examples

```
>>> t = boolean()
>>> t
boolean()
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters `_to_backend` (*bool*) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.int32`(*nullable=False*)

Bases: `PortexBuiltinType`

Portex primitive type `int32`.

Parameters `nullable` (*bool*) – Whether it is a nullable type.

Examples

```
>>> t = int32()
>>> t
int32()
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow `DataType`.

Returns The corresponding builtin PyArrow `DataType`.

Parameters `_to_backend` (*bool*) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.int64`(*nullable=False*)

Bases: `PortexBuiltinType`

Portex primitive type `int64`.

Parameters `nullable` (*bool*) – Whether it is a nullable type.

Examples

```
>>> t = int64()
>>> t
int64()
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow `DataType`.

Returns The corresponding builtin PyArrow `DataType`.

Parameters `_to_backend` (*bool*) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.float32`(*nullable=False*)

Bases: `PortexBuiltinType`

Portex primitive type `float32`.

Parameters `nullable` (*bool*) – Whether it is a nullable type.

Examples

```
>>> t = float32()
>>> t
float32()
```

to_pyarrow(self, *, _to_backend=False)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters **_to_backend** (bool) –

Return type pyarrow.DataType

class graviti.portex.builtin.**float64**(nullable=False)

Bases: [PortexBuiltinType](#)

Portex primitive type float64.

Parameters **nullable** (bool) – Whether it is a nullable type.

Examples

```
>>> t = float64()
>>> t
float64()
```

to_pyarrow(self, *, _to_backend=False)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters **_to_backend** (bool) –

Return type pyarrow.DataType

class graviti.portex.builtin.**record**(fields, nullable=False)

Bases: [PortexBuiltinType](#), [graviti.portex.base.PortexRecordBase](#)

Portex complex type record.

Parameters

- **fields** (Union[Iterable[Tuple[str, [graviti.portex.base.PortexType](#)]], Mapping[str, [graviti.portex.base.PortexType](#)]]) – The fields of the record.
- **nullable** (bool) – Whether it is a nullable type.

Examples

Create a record by dict:

```
>>> t = record({"f0": int32(), "f1": float32()})
>>> t
record(
  fields={
    'f0': int32(),
```

(continues on next page)

(continued from previous page)

```

    'f1': float32(),
},
)

```

Create a record by tuple list:

```

>>> t = record([("f0", string()), ("f1", enum(["v0", "v1"]))])
>>> t
record(
  fields={
    'f0': string(),
    'f1': enum(
      values=['v0', 'v1'],
    ),
  },
)

```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow struct DataType.

Parameters *_to_backend* (*bool*) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.enum`(*values*, *nullable=False*)

Bases: `PortexBuiltinType`

Portex complex type enum.

Parameters

- **values** (`Iterable[_E]`) – The values of the enum members.
- **nullable** (*bool*) – Whether it is a nullable type.

Examples

```

>>> t = enum(["v0", "v1"])
>>> t
enum(
  values=['v0', 'v1'],
)

```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters *_to_backend* (*bool*) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.array`(*items*, *length=None*, *nullable=False*)

Bases: `PortexBuiltinType`

Portex complex type array.

Parameters

- **items** (`graviti.portex.base.PortexType`) – The item type of the array.
- **length** (`Optional[int]`) – The length of the array.
- **nullable** (`bool`) – Whether it is a nullable type.

Examples

```
>>> t = array(int32(0), 100)
>>> t
array(
  items=int32(
    minimum=0,
  ),
  length=100,
)
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters *_to_backend* (`bool`) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.date(nullable=False)`

Bases: `PortexBuiltinType`

Portex temporal type date.

Parameters **nullable** (`bool`) – Whether it is a nullable type.

Examples

```
>>> t = date()
>>> t
date()
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters *_to_backend* (`bool`) –

Return type `pyarrow.DataType`

class `graviti.portex.builtin.time(unit, nullable=False)`

Bases: `PortexBuiltinType`

Portex temporal type time.

Parameters

- **unit** (`str`) – The unit of the time, supports ‘s’, ‘ms’, ‘us’ and ‘ns’.
- **nullable** (`bool`) – Whether it is a nullable type.

Examples

```
>>> t = time("ms")
>>> t
times(
  unit='ms',
)
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters *_to_backend* (*bool*) –

Return type pyarrow.DataType

class graviti.portex.builtin.timestamp(*unit*, *tz=None*, *nullable=False*)

Bases: [PortexBuiltinType](#)

Portex temporal type timestamp.

Parameters

- **unit** (*str*) – The unit of the timestamp, supports 's', 'ms', 'us' and 'ns'.
- **tz** (*Optional[str]*) – The name of the timezone, *None* indicates the timestamp is naive.
- **nullable** (*bool*) – Whether it is a nullable type.

Examples

```
>>> t = timestamp("ms")
>>> t
timestamp(
  unit='ms',
)
>>>
>>> t = timestamp("us", tz="UTC")
>>> t
timestamp(
  unit='ms',
  tz='UTC',
)
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters *_to_backend* (*bool*) –

Return type pyarrow.DataType

class graviti.portex.builtin.timedelta(*unit*, *nullable=False*)

Bases: [PortexBuiltinType](#)

Portex temporal type timedelta.

Parameters

- **unit** (*str*) – The unit of the timedelta, supports ‘s’, ‘ms’, ‘us’ and ‘ns’.
- **nullable** (*bool*) – Whether it is a nullable type.

Examples

```
>>> t = timedelta("ms")
>>> t
timedelta(
    unit='ms',
)
```

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.

Parameters *_to_backend* (*bool*) –

Return type `pyarrow.DataType`

`graviti.portex.enum`

Portex enum values related classes.

Module Contents

Classes

<i>EnumValues</i>	The base class of portex enum values.
<i>EnumValueList</i>	The portex enum values in list format.
<i>EnumValueDict</i>	The portex enum values in dict format.

Functions

<i>create_enum_values</i> (values)	The factory function of EnumValues.
------------------------------------	-------------------------------------

Attributes

<i>EnumValueType</i>

`graviti.portex.enum.EnumValueType`

class `graviti.portex.enum.EnumValues`

The base class of portex enum values.

```

abstract to_pyobj(self)
    Dump the instance to a python list or dict.

    Raises NotImplementedError – The method of the base class should not be called.

    Return type Union[List[EnumValueType], Dict[int, EnumValueType]]

abstract to_pyarrow(self)
    Dump the instance to a pyarrow array.

    Raises NotImplementedError – The method of the base class should not be called.

    Return type pyarrow.Array

class graviti.portex.enum.EnumValueList(values)
    Bases: EnumValues, graviti.utility.UserSequence[EnumValueType]

    The portex enum values in list format.

    Parameters values (Iterable[EnumValueType]) – The enum values.

    to_pyobj(self)
        Dump the instance to a python list.

        Returns A python list representation of the enum values.

        Return type List[EnumValueType]

    to_pyarrow(self)
        Dump the instance to a pyarrow array.

        Returns A pyarrow array representation of the enum values.

        Return type pyarrow.Array

class graviti.portex.enum.EnumValueDict(values)
    Bases: EnumValues, graviti.utility.UserMapping[int, EnumValueType]

    The portex enum values in dict format.

    Parameters values (Mapping[int, EnumValueType]) – The enum values.

    to_pyobj(self)
        Dump the instance to a python dict.

        Returns A python dict representation of the enum values.

        Return type Dict[int, EnumValueType]

    to_pyarrow(self)
        Dump the instance to a pyarrow array.

        Raises TypeError – EnumValueDict is not supported converting to pyarrow.

        Return type pyarrow.Array

graviti.portex.enum.create_enum_values(values)
    The factory function of EnumValues.

    Parameters values (Union[Sequence[EnumValueType], Mapping[int, EnumValueType]]) – The enum values.

    Returns The EnumValues instance created by the input enum values.

    Raises TypeError – When the input enum values is not in list or dict format.

    Return type EnumValues

```

`graviti.portex.external`

Portex external base class.

Module Contents

Classes

*PortexExternalType*The base class of Portex external type.

Attributes

EXTERNAL_TYPE_TO_CONTAINER

EXTERNAL_TYPE_TO_ELEMENT

`graviti.portex.external.EXTERNAL_TYPE_TO_CONTAINER``graviti.portex.external.EXTERNAL_TYPE_TO_ELEMENT`**class** `graviti.portex.external.PortexExternalType(*args, **kwargs)`Bases: *graviti.portex.base.PortexType*

The base class of Portex external type.

Parameters

- **args** (*Any*) –
- **kwargs** (*Any*) –

property `internal_type(self)`

Get the internal type of the PortexExternalType.

Returns The internal type of the PortexExternalType.**Return type** *graviti.portex.base.PortexType***to_pyarrow**(*self*, *, *_to_backend=False*)

Convert the Portex type to the corresponding builtin PyArrow DataType.

Returns The corresponding builtin PyArrow DataType.**Parameters** *_to_backend* (*bool*) –**Return type** `pyarrow.DataType`**to_builtin**(*self*)

Expand the top level of the Portex external type to Portex builtin type.

Returns The expanded Portex builtin type.**Return type** *graviti.portex.builtin.PortexBuiltinType*

graviti.portex.factory

Template factory related classes.

Module Contents**Classes**

<i>Factory</i>	The base class of the template factory.
<i>FrozenFieldsFactory</i>	The factory for FrozenFields.
<i>FrozenFieldsFactoryWrapper</i>	The factory for FrozenFields which needs kwargs transformed.
<i>ConnectedFieldsFactory</i>	The factory for ConnectedFields.
<i>TypeFactory</i>	The template factory for portex type.
<i>ConstantFactory</i>	The template factory for a constant.
<i>VariableFactory</i>	The template factory for a variable.
<i>ListFactory</i>	The template factory for a list.
<i>DictFactory</i>	The template factory for a dict.
<i>FieldFactory</i>	The template factory for a tuple of name and PortexType.
<i>FieldsFactory</i>	The template factory for a Fields.

Functions

<i>mapping_unpack_factory_creator</i> (decl, ptype)	Check the object unpack grammar and returns the corresponding factory.
<i>type_factory_creator</i> (decl, imports)	Check the input and returns the corresponding type factory.
<i>string_factory_creator</i> (decl, ptype = PTYPE.Any)	Check whether the input string is variable and returns the corresponding factory.
<i>factory_creator</i> (decl, imports, ptype = PTYPE.Any)	Check input type and returns the corresponding factory.

Attributes

<i>UnionFieldsFactory</i>

class graviti.portex.factory.Factory

The base class of the template factory.

class graviti.portex.factory.FrozenFieldsFactory(decl, imports)

Bases: *Factory*

The factory for FrozenFields.

Parameters

- **decl** (*Iterable*[*Dict*[*str*, *Any*]]) – The decalaration of frozen fields.

- **imports** (`graviti.portex.package.Imports`) – The `Imports` instance to specify the import scope of the fields.

class `graviti.portex.factory.FrozenFieldsFactoryWrapper`(*factory, kwargs_transformer*)

Bases: `Factory`

The factory for `FrozenFields` which needs `kwargs` transformed.

Parameters

- **factory** (`Union[FrozenFieldsFactory, FrozenFieldsFactoryWrapper]`) – The factory of frozen fields.
- **kwargs_transformer** (`Callable[Ellipsis, Dict[str, Any]]`) – The method to transform the `kwargs` to the `kwargs` of base type.

`graviti.portex.factory.UnionFieldsFactory`

class `graviti.portex.factory.ConnectedFieldsFactory`(*decl, class_, imports, kwargs_transformer*)

The factory for `ConnectedFields`.

Parameters

- **decl** (`Dict[str, Any]`) – A dict which indicates a portex type.
- **class** – The base type.
- **imports** (`graviti.portex.package.Imports`) – The `Imports` instance to specify the import scope of the template.
- **kwargs_transformer** (`Callable[Ellipsis, Dict[str, Any]]`) – The method to transform the `kwargs` to the `kwargs` of base type.
- **class_** (`Type[graviti.portex.base.PortexRecordBase]`) –

classmethod `from_parameter_name`(*cls, name*)

Create `ConnectedFieldsFactory` for `Fields` with the given parameter name.

Parameters

- **name** (`str`) – The parameter name of the input fields.
- **cls** (`Type[_CFF]`) –

Returns The created `ConnectedFieldsFactory`.

Return type `_CFF`

class `graviti.portex.factory.TypeFactory`(*decl, imports*)

Bases: `Factory`

The template factory for portex type.

Parameters

- **decl** (`Dict[str, Any]`) – A dict which indicates a portex type.
- **imports** (`graviti.portex.package.Imports`) –

transform_kwargs(*self, kwargs*)

Transform the keyword arguments to what the base type needs.

Parameters **kwargs** (`Dict[str, Any]`) – The input arguments.

Returns The transformed keyword arguments.

Return type `Dict[str, Any]`

class graviti.portex.factory.**ConstantFactory**(decl)

Bases: [Factory](#), Generic[_C]

The template factory for a constant.

Parameters decl (_C) – The constant to be created by the factory.

class graviti.portex.factory.**VariableFactory**(decl, ptype=PTYPE.Any, is_unpack=False)

Bases: [Factory](#)

The template factory for a variable.

Parameters

- **decl** (str) – The parameter name of the variable.
- **ptype** (graviti.portex.ptype.PType) – The parameter type.
- **is_unpack** (bool) –

class graviti.portex.factory.**ListFactory**(decl, ptype=PTYPE.Any)

Bases: [Factory](#)

The template factory for a list.

Parameters

- **decl** (List[[Any](#)]) – A list template.
- **ptype** (graviti.portex.ptype.PType) – The parameter type of the list.

class graviti.portex.factory.**DictFactory**(decl, ptype=PTYPE.Any)

Bases: [Factory](#)

The template factory for a dict.

Parameters

- **decl** (Dict[str, [Any](#)]) – A dict template.
- **ptype** (graviti.portex.ptype.PType) – The parameter type of the dict.

class graviti.portex.factory.**FieldFactory**(decl, imports)

Bases: [Factory](#)

The template factory for a tuple of name and PortexType.

Parameters

- **decl** (Dict[str, [Any](#)]) – A dict which indicates a tuple of name and PortexType.
- **imports** (graviti.portex.package.Imports) –

class graviti.portex.factory.**FieldsFactory**(decl, imports)

Bases: [Factory](#)

The template factory for a Fields.

Parameters

- **decl** (List[Union[Dict[str, [Any](#)], str]]) – A list which indicates a Fields.
- **imports** (graviti.portex.package.Imports) –

graviti.portex.factory.**mapping_unpack_factory_creator**(decl, ptype)

Check the object unpack grammar and returns the corresponding factory.

Parameters

- **decl** (*str*) – The parameter decalaration.
- **ptype** (*graviti.portex.ptype.PType*) – The parameter type of the input.

Raises **ValueError** – When the object unpack grammar is incorrect.

Returns A **VariableFactory** instance according to the input.

Return type *VariableFactory*

`graviti.portex.factory.type_factory_creator(decl, imports)`

Check the input and returns the corresponding type factory.

Parameters

- **decl** (*Dict[str, Any]*) – A dict which indicates a portex type or has object unpack grammar.
- **imports** (*graviti.portex.package.Imports*) – The **Imports** instance to specify the import scope of the template.

Raises **ValueError** – When setting the type name as a parameter.

Returns A **TypeFactory** or a **VariableFactory** instance.

Return type Union[*TypeFactory*, *VariableFactory*]

`graviti.portex.factory.string_factory_creator(decl, ptype=PTYPE.Any)`

Check whether the input string is variable and returns the corresponding factory.

Parameters

- **decl** (*str*) – A string which indicates a constant or a variable.
- **ptype** (*graviti.portex.ptype.PType*) – The parameter type of the string.

Returns A **VariableFactory** or a **ConstantFactory** instance according to the input.

Return type Union[*VariableFactory*, *ConstantFactory*[str]]

`graviti.portex.factory.factory_creator(decl, imports, ptype=PTYPE.Any)`

Check input type and returns the corresponding factory.

Parameters

- **decl** (*Any*) – A template which indicates any Portex object.
- **imports** (*Optional[graviti.portex.package.Imports]*) – The **Imports** instance to specify the import scope of the template.
- **ptype** (*graviti.portex.ptype.PType*) – The parameter type of the input.

Returns A **Factory** instance according the input.

Return type *Factory*

graviti.portex.field

Portex record field related classes.

Module Contents

Classes

<i>FrozenFields</i>	Represents a frozen fields dict.
<i>Fields</i>	Represents a Portex record fields dict.
<i>ConnectedFields</i>	Fields composed of FrozenFields and Fields.

Attributes

<i>UnionFields</i>

class graviti.portex.field.**FrozenFields**(items=None)

Bases: graviti.utility.FrozenNameOrderedDict[*graviti.portex.base.PortexType*]

Represents a frozen fields dict.

Parameters **items** (Union[Iterable[Tuple[str, _V]], Mapping[str, _V], None]) –

insert(self, index, name, portex_type)

Insert the name and portex_type at the index.

Parameters

- **index** (int) – The index to insert the field.
- **name** (str) – The name of the field to be inserted.
- **portex_type** (*graviti.portex.base.PortexType*) – The portex_type of the field to be inserted.

Raises **TypeError** – When calling this method of FrozenFields.

Return type None

astype(self, name, portex_type)

Convert the type of the field with the given name to the new PortexType.

Parameters

- **name** (str) – The name of the field to convert.
- **portex_type** (*graviti.portex.base.PortexType*) – The new PortexType of the field to convert to.

Raises **TypeError** – When calling this method of FrozenFields.

Return type None

rename(self, old_name, new_name)

Rename the name of a field.

Parameters

- **old_name** (*str*) – The current name of the field to be renamed.
- **new_name** (*str*) – The new name of the field to assign.

Raises **TypeError** – When calling this method of FrozenFields.

Return type `None`

class `graviti.portex.field.Fields`(*fields=None*)

Bases: `graviti.utility.NameOrderedDict[graviti.portex.base.PortexType, FrozenFields]`

Represents a Portex record fields dict.

Parameters **fields** (`Union[Iterable[Tuple[str, graviti.portex.base.PortexType]]`, `Mapping[str, graviti.portex.base.PortexType]`, `None`])

–

property `imports`(*self*)

Get the Fields imports.

Returns The Imports instance of this Fields.

Return type `graviti.portex.package.Imports`

insert(*self*, *index*, *name*, *portex_type*)

Insert the name and portex_type at the index.

Parameters

- **index** (*int*) – The index to insert the field.
- **name** (*str*) – The name of the field to be inserted.
- **portex_type** (`graviti.portex.base.PortexType`) – The portex_type of the field to be inserted.

Raises **KeyError** – When the name already exists in the Fields.

Return type `None`

astype(*self*, *name*, *portex_type*)

Convert the type of the field with the given name to the new PortexType.

Parameters

- **name** (*str*) – The name of the field to convert.
- **portex_type** (`graviti.portex.base.PortexType`) – The new PortexType of the field to convert to.

Raises **KeyError** – When the name does not exist in the Fields.

Return type `None`

rename(*self*, *old_name*, *new_name*)

Rename the name of a field.

Parameters

- **old_name** (*str*) – The current name of the field to be renamed.
- **new_name** (*str*) – The new name of the field to assign.

Return type `None`

classmethod `from_pyobj`(*cls*, *content*, *imports=None*)

Create Portex fields dict instance from python list.

Parameters

- **content** (*List[Dict[str, Any]]*) – A python list representing a Portex fields dict.
- **imports** (*Optional[graviti.portex.package.Imports]*) – The imports of the Portex fields dict.

Returns A Portex fields dict instance created from the input python list.

Return type *Fields*

to_pyobj(*self*)

Dump the instance to a python list.

Returns A Python List representation of the fields dict.

Return type *List[Dict[str, Any]]*

to_pyarrow(*self*, *, *_to_backend=False*)

Convert the fields to a list of PyArrow Field.

Returns A list of PyArrow Field representing the fields of Portex record.

Parameters *_to_backend* (*bool*) –

Return type *List[pyarrow.Field]*

copy(*self*)

Get a copy of the fields.

Returns A copy of the fields.

Parameters *self* (*_T*) –

Return type *_T*

`graviti.portex.field.UnionFields`

class `graviti.portex.field.ConnectedFields`(*multi_fields*)

Bases: `MutableMapping[str, graviti.portex.base.PortexType]`

Fields composed of FrozenFields and Fields.

Raises **ValueError** – When there as repeated field names.

Parameters *multi_fields* (*Iterable[UnionFields]*) – The FrozenFields and Fields.

insert(*self*, *index*, *name*, *portex_type*)

Insert the name and portex_type at the index.

Parameters

- **index** (*int*) – The index to insert the field.
- **name** (*str*) – The name of the field to be inserted.
- **portex_type** (`graviti.portex.base.PortexType`) – The portex_type of the field to be inserted.

Raises

- **ValueError** – When the name already exists in the fields.
- **TypeError** – When trying to insert a field into FrozenFields.

Return type *None*

astype(*self*, *name*, *portex_type*)

Convert the type of the field with the given name to the new PortexType.

Parameters

- **name** (*str*) – The name of the field to convert.
- **portex_type** ([graviti.portex.base.PortexType](#)) – The new PortexType of the field to convert to.

Return type None**rename**(*self, old_name, new_name*)

Rename the name of a field.

Parameters

- **old_name** (*str*) – The current name of the field to be renamed.
- **new_name** (*str*) – The new name of the field to assign.

Return type None**graviti.portex.package**

Package related class.

Module Contents**Classes**

Package	The base class of Portex package.
BuiltinPackage	The builtin Portex package used to manage builtin types.
LocalPackage	The local Portex package used to manage local types.
ExternalPackage	The external Portex package used to manage external types.
Subpackage	The subset of Portex package, used in Imports .
Packages	The package manager to manage different Portex packages.
Imports	The imports of the Portex template type.

Attributes

packages

class `graviti.portex.package.Package`Bases: `graviti.utility.AttrDict[_T]`

The base class of Portex package.

class `graviti.portex.package.BuiltinPackage`Bases: `Package[Type[graviti.portex.builtin.PortexBuiltinType]]`

The builtin Portex package used to manage builtin types.

class `graviti.portex.package.LocalPackage`

Bases: [Package](#)[[Type](#)[[graviti.portex.base.PortexType](#)]]

The local Portex package used to manage local types.

class [graviti.portex.package.ExternalPackage](#)(*url, revision*)

Bases: [Package](#)[[Type](#)[[graviti.portex.external.PortexExternalType](#)]]

The external Portex package used to manage external types.

Parameters

- **url** (*str*) – The git repo url of the external package.
- **revision** (*str*) – The git repo revision (tag/commit) of the external package.

property [repo](#)(*self*)

The repo string of the package.

Returns The “<url>@<rev>” format repo string.

Return type *str*

class [graviti.portex.package.Subpackage](#)(*package*)

Bases: [graviti.utility.UserMapping](#)[*str*, [Type](#)[[graviti.portex.external.PortexExternalType](#)]]

The subset of Portex package, used in [Imports](#).

Parameters **package** ([ExternalPackage](#)) – The source package of this subpackage.

classmethod [from_pyobj](#)(*cls, content*)

Create [Subpackage](#) instance from python dict.

Parameters **content** ([Dict](#)[*str*, *Any*]) – A python dict representing a subpackage.

Returns A [Subpackage](#) instance created from the input python dict.

Return type [Subpackage](#)

to_pyobj(*self*)

Dump the instance to a python dict.

Returns A python dict representation of the [Subpackage](#) instance.

Return type [Dict](#)[*str*, *Any*]

class [graviti.portex.package.Packages](#)

The package manager to manage different Portex packages.

[graviti.portex.package.packages](#)

class [graviti.portex.package.Imports](#)

Bases: [Mapping](#)[*str*, [Type](#)[[graviti.portex.base.PortexType](#)]], [graviti.utility.ReprMixin](#)

The imports of the Portex template type.

Parameters **package** – The package the portex belongs to.

update(*self, other*)

Update the imports with another imports.

Parameters **other** ([Imports](#)) – An [Imports](#) instance whose types need to be updated to this imports.

Return type *None*

classmethod [from_pyobj](#)(*cls, content*)

Create [Imports](#) instance from python list.

Parameters

- **content** (*List[Dict[str, Any]]*) – A python list representing imported types.
- **cls** (*Type[_I]*) –

Returns A *Imports* instance created from the input python list.

Return type *_I*

to_pyobj(*self*)

Dump the instance to a python list.

Returns A python list representation of the Portex imported types.

Return type *List[Dict[str, Any]]*

add_subpackage(*self, subpackage*)

Add subpackage to this *Imports* instance.

Parameters **subpackage** (*Subpackage*) – The subpackage which needs to be added.

Raises **KeyError** – When there are duplicate names in the *imports* instance.

Return type *None*

`graviti.portex.param`

Parameter related classes.

Module Contents

Classes

<i>Param</i>	Represents a parameter of a portex type.
<i>Params</i>	Represents all parameters of a portex type.

Functions

<i>param</i> (default = Parameter.empty, options = None, ptype = PTYPES.Any)	The factory function of Param.
--	--------------------------------

`graviti.portex.param.param`(default=Parameter.empty, options=None, ptype=PTYPES.Any)
The factory function of Param.

Parameters

- **default** (*Any*) – The default value of the parameter.
- **options** (*Optional[Iterable[Any]]*) – All possible values of the parameter.
- **ptype** (*graviti.portex.ptype.PType*) – The parameter type.

Returns A tuple which contains “default”, “options” and “ptype”.

Return type *Any*

class graviti.portex.param.**Param**(name, default=_empty, options=None, ptype=PTYPE.Any)

Bases: inspect.Parameter

Represents a parameter of a portex type.

Parameters

- **name** (*str*) – The name of the parameter.
- **default** (*Any*) – The default value of the parameter.
- **options** (*Optional[Iterable[Any]]*) – All possible values of the parameter.
- **ptype** (*graviti.portex.ptype.PType*) – The parameter type.

classmethod **from_pyobj**(cls, pyobj, ptype=PTYPE.Any)

Create Param instance from python dict.

Parameters

- **pyobj** (*Dict[str, Any]*) – A python dict representing a parameter.
- **ptype** (*graviti.portex.ptype.PType*) – The parameter type.

Returns A Param instance created from the input python dict.

Return type *Param*

property **required**(self)

Whether this parameter is a required parameter.

Returns True for required and False for non-required parameter.

Return type bool

to_pyobj(self)

Dump the instance to a python dict.

Returns A python dict representation of the Param.

Return type Dict[str, *Any*]

check(self, arg)

Check the validity of the parameter.

Parameters **arg** (*Any*) – The argument which needs to be checked.

Returns The argument after checking.

Raises **ValueError** – Raise when the argument is not in options.

Return type *Any*

load(self, content, imports)

Create an instance of the parameter type from the python content.

Parameters

- **content** (*Any*) – A python presentation of the parameter type.
- **imports** (*graviti.portex.package.Imports*) – The imports of the parameter type.

Returns An instance of the parameter type.

Return type *Any*

dump(self, arg)

Dump the parameter type instance into the python presentation.

Parameters `arg` (*Any*) – The parameter type instance.

Returns The python presentation of the input instance.

Return type *Any*

```
class graviti.portex.param.Params(values=None)
    Bases: graviti.utility.UserMapping[str, Param]
```

Represents all parameters of a portex type.

Parameters `values` (*Optional* [*Mapping* [*str*, *Param*]]) – The parameters mapping.

```
classmethod from_pyobj(cls, pyobj, keys)
    Create Params instance from python list.
```

Parameters

- **pyobj** (*List* [*Dict* [*str*, *Any*]]) – A python dict representing parameters.
- **keys** (*Dict* [*str*, *Any*]) – A python dict containing parameter types.

Returns A Params instance created from the input python list.

Return type *Params*

```
to_pyobj(self)
    Dump the instance to a python list.
```

Returns A python list representation of the Params.

Return type *List* [*Dict* [*str*, *Any*]]

```
add(self, value)
    Add a parameter.
```

Parameters `value` (*Param*) – The parameter which needs to be added to this instance.

Raises **KeyError** – When the parameter name is duplicated.

Return type *None*

```
update(self, values)
    Update the parameters.
```

Parameters `values` (*Mapping* [*str*, *Param*]) – The parameters which need to be updated to this instance.

Return type *None*

```
get_signature(self)
    Get the python inspect Signature from parameters.
```

Returns The Signature instance created by all parameters in this instance.

Return type *inspect.Signature*

graviti.portex.ptype

Parameter type related classes.

Module Contents

Classes

<i>ParameterType</i>	The base class of parameter type.
<i>Any</i>	Unconstrained parameter type.
<i>Boolean</i>	Parameter type for JSON Boolean.
<i>Array</i>	Parameter type for JSON Array.
<i>Mapping</i>	Parameter type for JSON object.
<i>Number</i>	Parameter type for JSON number.
<i>Integer</i>	Parameter type for JSON integer.
<i>String</i>	Parameter type for JSON string.
<i>Enum</i>	Parameter type for Portex enum values.
<i>Fields</i>	Parameter type for Portex record fields.
<i>PortexType</i>	Parameter type for Portex type.

Attributes

<i>PType</i>

class graviti.portex.ptype.ParameterType

The base class of parameter type.

static check(*arg*)

Check the parameter type.

Parameters *arg* (*Any*) – The argument which needs to be checked.

Returns The input argument unchanged.

Return type *Any*

static load(*content*, *_*=None)

Create an instance of the parameter type from the python content.

Parameters

- **content** (*Any*) – A python presentation of the parameter type.
- **_** (*Optional*[*graviti.portex.package.Imports*]) – The imports of the parameter type.

Returns An instance of the parameter type.

Return type *Any*

static dump(*arg*)

Dump the parameter type instance into the python presentation.

Parameters *arg* (*Any*) – The parameter type instance.

Returns The python presentation of the input instance.

Return type *Any*

`graviti.portex.ptype.PType`

class `graviti.portex.ptype.Any`

Bases: *ParameterType*

Unconstrained parameter type.

class `graviti.portex.ptype.Boolean`

Bases: `_JsonType`

Parameter type for JSON Boolean.

class `graviti.portex.ptype.Array`

Bases: `_JsonType`

Parameter type for JSON Array.

class `graviti.portex.ptype.Mapping`

Bases: `_JsonType`

Parameter type for JSON object.

class `graviti.portex.ptype.Number`

Bases: `_JsonType`

Parameter type for JSON number.

class `graviti.portex.ptype.Integer`

Bases: `_JsonType`

Parameter type for JSON integer.

class `graviti.portex.ptype.String`

Bases: `_JsonType`

Parameter type for JSON string.

class `graviti.portex.ptype.Enum`

Bases: *ParameterType*

Parameter type for Portex enum values.

static `check(arg)`

Check and transfer the parameter type.

Parameters `arg` (*Any*) – The argument which needs to be checked.

Returns A list of enum values created by the input argument.

Return type *graviti.portex.enum.EnumValues*

static `load(content, _=None)`

Create Portex EnumValues instance from python object.

Parameters

- **content** (*Union[Dict[int, graviti.portex.enum.EnumValueType], List[graviti.portex.enum.EnumValueType], None]*) – A python list or dict representing a EnumValues.
- **_** (*Optional[graviti.portex.package.Imports]*) – The imports of the Portex field.

Returns A Portex EnumValues instance created from the input python list or dict.

Raises **TypeError** – When the input enum values is not in list or dict format.

Return type Optional[*graviti.portex.enum.EnumValues*]

static dump(*arg*)

Dump the input Portex EnumValues instance to a python list or dict.

Parameters **arg** (*graviti.portex.enum.EnumValues*) – A Portex EnumValues instance.

Returns A Python list or dict representation of the Portex enum values.

Return type Union[Dict[int, *graviti.portex.enum.EnumValueType*],
List[*graviti.portex.enum.EnumValueType*]]

class *graviti.portex.ptype.Fields*

Bases: *ParameterType*

Parameter type for Portex record fields.

static check(*arg*)

Check and transfer the parameter type.

Parameters **arg** (*Any*) – The argument which needs to be checked.

Returns A *Fields* instance created by the input argument.

Return type *graviti.portex.field.Fields*

static load(*content*, *imports=None*)

Create Portex field list instance from python list.

Parameters

- **content** (*Optional[List[Any]]*) – A python list representing a Portex field list.
- **imports** (*Optional[graviti.portex.package.Imports]*) – The imports of the Portex field.

Returns A Portex field list instance created from the input python list.

Return type *graviti.portex.field.Fields*

static dump(*arg*)

Dump the input Portex field list instance to a python list.

Parameters **arg** (*graviti.portex.field.Fields*) – A Portex field list instance.

Returns A Python list representation of the Portex field list.

Return type List[*Any*]

class *graviti.portex.ptype.PortexType*

Bases: *ParameterType*

Parameter type for Portex type.

static check(*arg*)

Check the parameter type.

Parameters **arg** (*Any*) – The argument which needs to be checked.

Returns The input argument unchanged.

Raises **TypeError** – When the input argument is not a Portex type.

Return type *graviti.portex.base.PortexType*

static `load(content, imports=None)`

Create Portex type instance from python dict.

Parameters

- **content** (*Optional*[*Dict*[*str*, *Any*]]) – A python dict representing a Portex type.
- **imports** (*Optional*[*graviti.portex.package.Imports*]) – The imports of the Portex type.

Returns A Portex type instance created from the input python dict.

Return type *Optional*[*graviti.portex.base.PortexType*]

static `dump(arg)`

Dump the instance to a python dict.

Parameters **arg** (*graviti.portex.base.PortexType*) – A Portex type instance.

Returns A python dict representation of the Portex type.

Return type *Dict*[*str*, *Any*]

`graviti.portex.register`

The portex type register related classes.

Module Contents

Classes

<i>ContainerRegister</i>	The class decorator to connect portex type and the data container.
<i>ExternalContainerRegister</i>	The class decorator to connect portex external type and the data container.
<i>ExternalElementResgister</i>	The class decorator to connect portex external type and the element class.
<i>PyArrowConversionRegister</i>	Register the Portex type to set the conversion from PyArrow to Portex.

Attributes

<i>STANDARD_URL</i>

`graviti.portex.register.STANDARD_URL =`

`https://github.com/Project-OpenBytes/portex-standard`

class `graviti.portex.register.ContainerRegister(*portex_types)`

The class decorator to connect portex type and the data container.

Parameters **portex_types** (*Type*[*graviti.portex.base.PortexType*]) – The portex types needs to be connected.

class graviti.portex.register.**ExternalContainerRegister**(url, revision, *names)

The class decorator to connect portex external type and the data container.

Parameters

- **url** (str) – The git repo url of the external package.
- **revision** (str) – The git repo revision (tag/commit) of the external package.
- **name** – The portex external type name.
- **names** (str) –

class graviti.portex.register.**ExternalElementResgister**(url, revision, *names)

The class decorator to connect portex external type and the element class.

Parameters

- **url** (str) – The git repo url of the external package.
- **revision** (str) – The git repo revision (tag/commit) of the external package.
- **name** – The portex external type name.
- **names** (str) –

class graviti.portex.register.**PyArrowConversionRegister**(*pyarrow_type_ids)

Register the Portex type to set the conversion from PyArrow to Portex.

Parameters **pyarrow_type_ids** (int) – The id of the corresponding PyArrow types.

graviti.utility

Utility module.

Submodules

graviti.utility.attr

Attr related class.

Module Contents

Classes

AttrDict

A dict which allows for attr-style access of values.

class graviti.utility.attr.**AttrDict**

Bases: `_AttrDict[_T]`, `Mapping[str, _T]`

A dict which allows for attr-style access of values.

get(self, key: str) → Optional[_T]

get(self, key: str, default: _D = ...) → Union[_D, _T]

Return the value for the key if it is in the dict, else default.

Parameters

- **key** – The key for dict, which can be any immutable type.
- **default** – The value to be returned if key is not in the dict.

Returns The value for the key if it is in the dict, else default.

graviti.utility.collections

Basic concepts of user-defined objects.

Module Contents

Classes

<i>UserSequence</i>	UserSequence is a user-defined wrapper around sequence objects.
<i>UserMutableSequence</i>	UserMutableSequence is a user-defined wrapper around mutable sequence objects.
<i>UserMapping</i>	UserMapping is a user-defined wrapper around mapping objects.
<i>UserMutableMapping</i>	UserMutableMapping is a user-defined wrapper around mutable mapping objects.
<i>FrozenNameOrderedDict</i>	This class is an immutable dict of ordered elements, supports searching the element by index.
<i>NameOrderedDict</i>	This class is a dict of ordered elements, supports searching the element by its index.

class graviti.utility.collections.UserSequence

Bases: Sequence[_T], [graviti.utility.repr.ReprMixin](#)

UserSequence is a user-defined wrapper around sequence objects.

index(self, value, start=0, stop=maxsize)

Return the first index of the value.

Parameters

- **value** (_T) – The value to be found.
- **start** (int) – The start index of the subsequence.
- **stop** (int) – The end index of the subsequence.

Returns The First index of value.

Return type int

count(self, value)

Return the number of occurrences of value.

Parameters **value** (_T) – The value to be counted the number of occurrences.

Returns The number of occurrences of value.

Return type int

class graviti.utility.collections.UserMutableSequence

Bases: MutableSequence[_T], [UserSequence](#)[_T]

UserMutableSequence is a user-defined wrapper around mutable sequence objects.

insert(*self*, *index*, *value*)

Insert object before index.

Parameters

- **index** (*int*) – Position of the mutable sequence.
- **value** (*_T*) – Element to be inserted into the mutable sequence.

Return type None

append(*self*, *value*)

Append object to the end of the mutable sequence.

Parameters **value** (*_T*) – Element to be appended to the mutable sequence.

Return type None

clear(*self*)

Remove all items from the mutable sequence.

Return type None

extend(*self*, *values*)

Extend mutable sequence by appending elements from the iterable.

Parameters **values** (*Iterable[_T]*) – Elements to be Extended into the mutable sequence.

Return type None

reverse(*self*)

Reverse the items of the mutable sequence in place.

Return type None

pop(*self*, *index=-1*)

Return the item at index (default last) and remove it from the mutable sequence.

Parameters **index** (*int*) – Position of the mutable sequence.

Returns Element to be removed from the mutable sequence.

Return type *_T*

remove(*self*, *value*)

Remove the first occurrence of value.

Parameters **value** (*_T*) – Element to be removed from the mutable sequence.

Return type None

class graviti.utility.collections.UserMapping

Bases: Mapping[*_K*, *_V*], [graviti.utility.repr.ReprMixin](#)

UserMapping is a user-defined wrapper around mapping objects.

get(*self*, *key*: *_K*) → Optional[*_V*]

get(*self*, *key*: *_K*, *default*: Union[*_V*, *_T*] = ...) → Union[*_V*, *_T*]

Return the value for the key if it is in the dict, else default.

Parameters

- **key** – The key for dict, which can be any immutable type.
- **default** – The value to be returned if key is not in the dict.

Returns The value for the key if it is in the dict, else default.

items(*self*)

Return a new view of the (key, value) pairs in dict.

Returns The (key, value) pairs in dict.

Return type ItemsView[_K, _V]

keys(*self*)

Return a new view of the keys in dict.

Returns The keys in dict.

Return type KeysView[_K]

values(*self*)

Return a new view of the values in dict.

Returns The values in dict.

Return type ValuesView[_V]

class graviti.utility.collections.**UserMutableMapping**

Bases: MutableMapping[_K, _V], [UserMapping](#)[_K, _V]

UserMutableMapping is a user-defined wrapper around mutable mapping objects.

clear(*self*)

Remove all items from the mutable mapping object.

Return type None

pop(*self*, key: _K) → _V

pop(*self*, key: _K, default: Union[_V, _T] = ...) → Union[_V, _T]

Remove specified item and return the corresponding value.

Parameters

- **key** – The key for dict, which can be any immutable type.
- **default** – The value to be returned if the key is not in the dict and it is given.

Returns Value to be removed from the mutable mapping object.

popitem(*self*)

Remove and return a (key, value) pair as a tuple.

Pairs are returned in LIFO (last-in, first-out) order.

Returns A (key, value) pair as a tuple.

Return type Tuple[_K, _V]

setdefault(*self*, key, default=None)

Set the value of the item with the specified key.

If the key is in the dict, return the corresponding value. If not, insert the key with a value of default and return default.

Parameters

- **key** (_K) – The key for dict, which can be any immutable type.
- **default** (_V) – The value to be set if the key is not in the dict.

Returns The value for key if it is in the dict, else default.

Return type `_V`

update(*self*, *__m*: `_SupportsKeysAndGetItem[_K, _V]`, ***kwargs*: `_V`) → None

update(*self*, *__m*: `Iterable[Tuple[_K, _V]]`, ***kwargs*: `_V`) → None

update(*self*, ***kwargs*: `_V`) → None

Update the dict.

Parameters

- **__m** – A dict object, a generator object yielding a (key, value) pair or other object which has a `.keys()` method.
- ****kwargs** – The value to be added to the mutable mapping.

class `graviti.utility.collections.FrozenNameOrderedDict`(*items=None*)

Bases: `Mapping[str, _V]`, `graviti.utility.repr.ReprMixin`

This class is an immutable dict of ordered elements, supports searching the element by index.

Parameters **items** (`Union[Iterable[Tuple[str, _V]], Mapping[str, _V], None]`) – The items need to be stored into the `FrozenNameOrderedDict`.

class `graviti.utility.collections.NameOrderedDict`(*items=None*)

Bases: `MutableMapping[str, _V]`, `FrozenNameOrderedDict[_V]`

This class is a dict of ordered elements, supports searching the element by its index.

Parameters **items** (`Union[Iterable[Tuple[str, _V]], Mapping[str, _V], None]`) – The items need to be stored into the `NameOrderedDict`.

popitem(*self*)

Remove and return a (key, value) pair as a tuple.

Pairs are returned in LIFO (last-in, first-out) order.

Raises **KeyError** – When the dict is empty.

Returns A (key, value) pair as a tuple.

Return type `Tuple[str, _V]`

graviti.utility.common

Common tools.

Module Contents**Classes**

<code>LazyAttr</code>	The descriptor for the lazy loaded attr.
<code>CachedProperty</code>	The descriptor for the cached property.
<code>ModuleMocker</code>	A fake module to raise <code>ModuleNotFoundError</code> lazily.

Functions

<code>urlnorm(url)</code>	Normalized the input url by removing the trailing slash.
<code>locked(func)</code>	The decorator to add threading lock for methods.
<code>shorten(origin)</code>	Return the first 7 characters of the original string.
<code>convert_iso_to_datetime(date_string)</code>	Convert iso 8601 format string to datetime format time with local timezone.
<code>convert_datetime_to_gmt(utctime)</code>	Convert datetime to gmt format string.

Attributes

<code>locks</code>

`graviti.utility.common.locks :DefaultDict[int, threading.Lock]`

`graviti.utility.common.urlnorm(url)`

Normalized the input url by removing the trailing slash.

Parameters `url (str)` – the url needs to be normalized.

Returns The normalized url.

Return type `str`

`graviti.utility.common.locked(func)`

The decorator to add threading lock for methods.

Parameters `func (_CallableWithoutReturnValue)` – The method needs to add threading lock.

Returns The method with theading locked.

Return type `_CallableWithoutReturnValue`

`graviti.utility.common.shorten(origin)`

Return the first 7 characters of the original string.

Parameters `origin (str)` – The string needed to be shortened.

Returns A string of length 7.

Return type `str`

`graviti.utility.common.convert_iso_to_datetime(date_string)`

Convert iso 8601 format string to datetime format time with local timezone.

Parameters `date_string (str)` – The iso 8601 format string.

Returns The datetime format time with local timezone.

Return type `datetime.datetime`

`graviti.utility.common.convert_datetime_to_gmt(utctime)`

Convert datetime to gmt format string.

Parameters `utctime (datetime.datetime)` – The datetime with utc timezone.

Returns The gmt format string.

Return type `str`

```
class graviti.utility.common.LazyAttr
```

```
Bases: Generic[_T]
```

```
The descriptor for the lazy loaded attr.
```

```
class graviti.utility.common.CachedProperty(func)
```

```
Bases: Generic[_S, _T]
```

```
The descriptor for the cached property.
```

```
Parameters func (Callable[[_S], _T]) – the property function needs to be cached.
```

```
class graviti.utility.common.ModuleMocker(message)
```

```
A fake module to raise ModuleNotFoundError lazily.
```

```
Parameters message (str) – The error message for the raised ModuleNotFoundError.
```

graviti.utility.engine

Engine control related classes.

Module Contents

Classes

<i>Mode</i>	This class defines the engine mode and includes 'LOCAL' and 'ONLINE'.
<i>Online</i>	An engine controller used to start and stop the online mode.
<i>Engine</i>	This is a base class defining the Engine mode.

Attributes

<i>engine</i>

```
class graviti.utility.engine.Mode
```

```
Bases: enum.Enum
```

```
This class defines the engine mode and includes 'LOCAL' and 'ONLINE'.
```

```
class graviti.utility.engine.Online(_engine)
```

```
An engine controller used to start and stop the online mode.
```

```
Parameters _engine (Engine) –
```

```
class graviti.utility.engine.Engine
```

```
This is a base class defining the Engine mode.
```

```
online(self)
```

```
Init a Online instance.
```

```
Returns the Online instance.
```

```
Return type Online
```

`graviti.utility.engine.engine`

`graviti.utility.itertools`

The implementation of iteration tools.

Module Contents

Functions

<code>chunked(iterable, n)</code>	Break an iterable instance into tuples of length n.
-----------------------------------	---

`graviti.utility.itertools.chunked(iterable, n)`
Break an iterable instance into tuples of length n.

Parameters

- **iterable** (*Iterable*[*T*]) – The input iterable instance which needs to be brokened into tuples of length n.
- **n** (*int*) – The length of each yielded tuples.

Yields The tuples of length n.

Return type `Iterator[Tuple[_T, Ellipsis]]`

Examples

```
>>> list(chunked(range(9), 3))
[(0, 1, 2), (3, 4, 5), (6, 7, 8)]
```

The last yielded tuple may have fewer than n items if the length of the input iterable instance is not divisible by n:

```
>>> list(chunked(range(10), 3))
[(0, 1, 2), (3, 4, 5), (6, 7, 8), (9,)]
```

`graviti.utility.log`

The implementation of logging utilities.

Module Contents

Classes

<i>RequestLogging</i>	This class used to lazy load request to logging.
<i>ResponseLogging</i>	This class used to lazy load response to logging.

Functions

<i>dump_request_and_response(response)</i>	Dumps http request and response.
--	----------------------------------

Attributes

<i>REQUEST_TEMPLATE</i>
<i>RESPONSE_TEMPLATE</i>

`graviti.utility.log.REQUEST_TEMPLATE = Multiline-String`

```

1  =====
2  ##### HTTP Request #####
3  "url": {}
4  "method": {}
5  "headers": {}
6  "body": {}

```

`graviti.utility.log.RESPONSE_TEMPLATE = Multiline-String`

```

1  ##### HTTP Response #####
2  "url": {}
3  "status_code": {}
4  "reason": {}
5  "headers": {}
6  "content": {}
7  "cost_time": {}s
8  =====

```

class `graviti.utility.log.RequestLogging(request)`

This class used to lazy load request to logging.

Parameters `request` (`requests.models.PreparedRequest`) – The request of the request.

class `graviti.utility.log.ResponseLogging(response)`

This class used to lazy load response to logging.

Parameters `response` (`requests.models.Response`) – The response of the request.

`graviti.utility.log.dump_request_and_response(response)`

Dumps http request and response.

Parameters **response** (*requests.models.Response*) – Http response and response.

Returns

Http request and response for logging, sample:

```
##### HTTP Request #####
"url": https://gas.graviti.cn/gatewayv2/content-store/putObject
"method": POST
"headers": {
  "User-Agent": "python-requests/2.23.0",
  "Accept-Encoding": "gzip, deflate",
  "Accept": "*/*",
  "Connection": "keep-alive",
  "X-Token": "c3b1808b21024eb38f066809431e5bb9",
  "Content-Type": "multipart/form-data;
  boundary=5adff1fc0524465593d6a9ad68aad7f9",
  "Content-Length": "330001"
}
"body":
--5adff1fc0524465593d6a9ad68aad7f9
b'Content-Disposition: form-data; name="contentSetId"\r\n\r\n'
b'e6110ff1-9e7c-4c98-aaf9-5e35522969b9'

--5adff1fc0524465593d6a9ad68aad7f9
b'Content-Disposition: form-data; name="filePath"\r\n\r\n'
b'4.jpg'

--5adff1fc0524465593d6a9ad68aad7f9
b'Content-Disposition: form-data; name="fileData"; filename="4.jpg"\r\n\r\n'
[329633 bytes of object data]

--5adff1fc0524465593d6a9ad68aad7f9--

##### HTTP Response #####
"url": https://gas.graviti.cn/gatewayv2/content-stor
"status_code": 200
"reason": OK
"headers": {
  "Date": "Sat, 23 May 2020 13:05:09 GMT",
  "Content-Type": "application/json;charset=utf-8",
  "Content-Length": "69",
  "Connection": "keep-alive",
  "Access-Control-Allow-Origin": "*",
  "X-Kong-Upstream-Latency": "180",
  "X-Kong-Proxy-Latency": "112",
  "Via": "kong/2.0.4"
}
"content": {
  "success": true,
  "code": "DATACENTER-0",
  "message": "success",
```

(continues on next page)

(continued from previous page)

```
"data": {}
}
"cost_time": 0.0813691616058
=====
```

Return type `str`

`graviti.utility.repr`

Repr related methods.

Module Contents

Classes

<code>ReprType</code>	ReprType is an enumeration type.
<code>ReprMixin</code>	ReprMixin provides customized repr config and method.

Attributes

<code>MAX_REPR_ROWS</code>
<code>INDENT</code>
<code>repr_config</code>

`graviti.utility.repr.MAX_REPR_ROWS = 10`

`graviti.utility.repr.INDENT`

class `graviti.utility.repr.ReprType`
Bases: `enum.Enum`

ReprType is an enumeration type.

It defines the repr strategy type and includes 'INSTANCE', 'SEQUENCE' and 'MAPPING'.

class `graviti.utility.repr.ReprMixin`
ReprMixin provides customized repr config and method.

`graviti.utility.repr.repr_config`

graviti.utility.requests

The implementation of request related tools.

Module Contents

Classes

<i>Config</i>	This is a base class defining the concept of Request Config.
<i>TimeoutHTTPAdapter</i>	This class defines the http adapter for setting the timeout value.
<i>UserSession</i>	This class defines UserSession.
<i>UserResponse</i>	This class used to read data from Response with stream method.

Functions

<i>get_session()</i>	Create and return a session per PID so each sub-processes will use their own session.
<i>submit_multithread_tasks</i> (function, arguments, *, jobs)	Multi-thread framework.

Attributes

<i>logger</i>
<i>config</i>
<i>SESSIONS</i>

graviti.utility.requests.logger

class graviti.utility.requests.Config

This is a base class defining the concept of Request Config.

max_retries

Maximum retry times of the request.

allowed_retry_methods

The allowed methods for retrying request.

allowed_retry_status

The allowed status for retrying request. If both methods and status are fitted, the retrying strategy will work.

timeout

Timeout value of the request in seconds.

is_internal

Whether the request is from internal.

graviti.utility.requests.config

class graviti.utility.requests.TimeoutHTTPAdapter(*args, timeout=None, **kwargs)

Bases: requests.adapters.HTTPAdapter

This class defines the http adapter for setting the timeout value.

Parameters

- ***args** – Extra arguments to initialize TimeoutHTTPAdapter.
- **timeout** (*Optional[int]*) – Timeout value of the post request in seconds.
- ****kwargs** – Extra keyword arguments to initialize TimeoutHTTPAdapter.
- **args** (*Any*) –
- **kwargs** (*Any*) –

send(self, request, stream=False, timeout=None, verify=True, cert=None, proxies=None)

Send the request.

Parameters

- **request** (*requests.models.PreparedRequest*) – The PreparedRequest being sent.
- **stream** (*Any*) – Whether to stream the request content.
- **timeout** (*Any*) – Timeout value of the post request in seconds.
- **verify** (*Any*) – A path string to a CA bundle to use or a boolean which controls whether to verify the server's TLS certificate.
- **cert** (*Any*) – User-provided SSL certificate.
- **proxies** (*Any*) – Proxies dict applying to the request.

Returns Response object.

Return type *Any*

class graviti.utility.requests.UserSession

Bases: requests.Session

This class defines UserSession.

request(self, method, url, *args, **kwargs)

Make the request.

Parameters

- **method** (*str*) – Method for the request.
- **url** (*str*) – URL for the request.
- ***args** – Extra arguments to make the request.
- ****kwargs** – Extra keyword arguments to make the request.
- **args** (*Any*) –
- **kwargs** (*Any*) –

Returns Response of the request.

Raises *ResponseError* – If post response error.

Return type *requests.models.Response*

`graviti.utility.requests.SESSIONS :DefaultDict[int, UserSession]`

`graviti.utility.requests.get_session()`

Create and return a session per PID so each sub-processes will use their own session.

Returns The session corresponding to the process.

Return type *UserSession*

class `graviti.utility.requests.UserResponse(response)`

This class used to read data from Response with stream method.

Parameters *response* (*requests.models.Response*) – Response of the Session.request().

close(*self*)

Close the response.

Return type *None*

read(*self*, *amt=None*)

Read data from response.

Parameters *amt* (*Optional[int]*) – The needed read amount.

Returns Response of the request.

Return type *bytes*

`graviti.utility.requests.submit_multithread_tasks(function, arguments, *, jobs)`

Multi-thread framework.

Parameters

- **function** (*Callable[[_T], Any]*) – The function to call.
- **arguments** (*Iterable[_T]*) – The arguments of the function.
- **jobs** (*int*) – The number of the max workers in multi-thread call procession.

Return type *None*

graviti.utility.typing

Graviti customized types.

Module Contents

Classes

NestedDict

Typehint for nested dict.

Functions

<code>check_type(name, value, expected_type)</code>	Check the type of the argument.
---	---------------------------------

Attributes

PathLike

SortParam

`graviti.utility.typing.PathLike`

`graviti.utility.typing.SortParam`

class `graviti.utility.typing.NestedDict`

Bases: `typing_extensions.Protocol[_K, _V]`

Typehint for nested dict.

items(*self*)

Return (key, value) pairs of the dict.

Return type `AbstractSet[Tuple[_K, Union[NestedDict[_K, _V], _V]]]`

setdefault(*self, key, default*)

Get the value of the key if exists, else set the value as default and return.

Parameters

- **key** (*_K*) – The key.
- **default** (*Union[*NestedDict*[_K, _V], _V]*) – The default value to set if the key does not exist.

Return type `Union[NestedDict[_K, _V], _V]`

`graviti.utility.typing.check_type(name, value, expected_type)`

Check the type of the argument.

Parameters

- **name** (*str*) – The name of the argument.
- **value** (*Any*) – The value of the argument.
- **expected_type** (*Type[*Any*]*) – The type of the argument.

Raises **TypeError** – When the value is not of the type.

Return type `None`

1.11.2 Submodules

graviti.exception

Basic concepts of Graviti custom exceptions.

Module Contents

Classes

<i>ResponseErrorRegister</i>	A class decorator to register the ResponseError into the distributor.
------------------------------	---

exception graviti.exception.GravitiException(*message=None*)

Bases: Exception

This is the base class for Graviti custom exceptions.

Parameters *message* (*Optional[str]*) – The error message.

exception graviti.exception.UtilityError(*message=None*)

Bases: *GravitiException*

This is the base class for custom exceptions in Graviti utility module.

Parameters *message* (*Optional[str]*) –

exception graviti.exception.ImageDecodeError(*message=None*)

Bases: *UtilityError*

This class defines the exception for the image decode errors.

Parameters *message* (*Optional[str]*) –

exception graviti.exception.PortexError(*message=None*)

Bases: *GravitiException*

This is the base class for custom exceptions in Graviti portex module.

Parameters *message* (*Optional[str]*) –

exception graviti.exception.FieldNameConflictError(*message=None*)

Bases: *PortexError*

This class defines the exception for the portex field name error.

Parameters *message* (*Optional[str]*) –

exception graviti.exception.GitNotFoundError(*message=_MESSAGE*)

Bases: *PortexError*

This class defines the exception for the git command not found error.

Parameters *message* (*str*) – The error message.

exception graviti.exception.GitCommandError(*message, called_process_error*)

Bases: *PortexError*

This class defines the exception for the git command related error.

Parameters

- **message** (*str*) – The error message.
- **called_process_error** (*subprocess.CalledProcessError*) – The `CalledProcessError` raised from the `subprocess.run()`.

exception `graviti.exception.OperationError`(*message=None*)

Bases: [`GravitiException`](#)

This is the base class for custom exceptions in Graviti operation module.

Parameters **message** (*Optional[str]*) –

exception `graviti.exception.ObjectCopyError`(*message=None*)

Bases: [`OperationError`](#)

This class defines the exception for object copy error.

Parameters **message** (*Optional[str]*) –

exception `graviti.exception.ManagerError`(*message=None*)

Bases: [`GravitiException`](#)

This is the base class for custom exceptions in Graviti manager module.

Parameters **message** (*Optional[str]*) –

exception `graviti.exception.CriteriaError`(*message=None*)

Bases: [`ManagerError`](#)

This class defines the exception for invalid search criteria.

Parameters **message** (*Optional[str]*) –

exception `graviti.exception.StatusError`(*message=None*)

Bases: [`ManagerError`](#)

This class defines the exception for illegal status.

Parameters **message** (*Optional[str]*) –

exception `graviti.exception.NoCommitsError`(*message=None*)

Bases: [`StatusError`](#)

This class defines the exception for illegal operations on dataset with no commit history.

Parameters **message** (*Optional[str]*) –

exception `graviti.exception.ResourceNameError`(*resource, name*)

Bases: [`ManagerError`](#)

This class defines the exception for invalid resource names.

Parameters

- **resource** (*str*) –
- **name** (*str*) –

exception `graviti.exception.ResponseError`(*message=None, *, response=None*)

Bases: [`ManagerError`](#)

This class defines the exception for post response error.

Parameters

- **response** (*Optional[requests.models.Response]*) – The response of the request.
- **message** (*Optional[str]*) –

response

The response of the request.

class graviti.exception.**ResponseErrorRegister**(*status_code*, *error_code=None*)

A class decorator to register the ResponseError into the distributor.

Parameters

- **status_code** (*int*) – The http status code of the specific ResponseError.
- **error_code** (*Optional[str]*) – The response error code of the specific ResponseError.

exception graviti.exception.**AccessDeniedError**(*message=None*, *, *response=None*)

Bases: [ResponseError](#)

This class defines the exception for access denied response error.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception graviti.exception.**ForbiddenError**(*message=None*, *, *response=None*)

Bases: [ResponseError](#)

This class defines the exception for illegal operations Graviti forbids.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception graviti.exception.**InvalidParamsError**(*message=None*, *, *response=None*)

Bases: [ResponseError](#)

This class defines the exception for invalid parameters response error.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception graviti.exception.**NameConflictError**(*message=None*, *, *response=None*)

Bases: [ResponseError](#)

This class defines the exception for name conflict response error.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception graviti.exception.**RequestParamsMissingError**(*message=None*, *, *response=None*)

Bases: [ResponseError](#)

This class defines the exception for request parameters missing response error.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception `graviti.exception.NotFoundError(message=None, *, response=None)`

Bases: [`ResponseError`](#)

This class defines the exception for 404 not found response error without error code.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception `graviti.exception.ResourceNotExistError(message=None, *, response=None)`

Bases: [`NotFoundError`](#)

This class defines the exception for resource not existing response error.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception `graviti.exception.InternalServerError(message=None, *, response=None)`

Bases: [`ResponseError`](#)

This class defines the exception for internal server error.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception `graviti.exception.UnauthorizedError(message=None, *, response=None)`

Bases: [`ResponseError`](#)

This class defines the exception for unauthorized response error.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

exception `graviti.exception.ServiceUnavailableError(message=None, *, response=None)`

Bases: [`ResponseError`](#)

This class defines the exception for 503 service unavailable error without error code.

Parameters

- **message** (*Optional[str]*) –
- **response** (*Optional[requests.models.Response]*) –

PYTHON MODULE INDEX

g

- graviti, 49
- graviti.dataframe, 49
 - graviti.dataframe.column, 49
 - graviti.dataframe.column.indexing, 49
 - graviti.dataframe.column.series, 50
 - graviti.dataframe.container, 66
 - graviti.dataframe.frame, 67
 - graviti.dataframe.indexing, 74
 - graviti.dataframe.row, 54
 - graviti.dataframe.row.indexing, 54
 - graviti.dataframe.row.series, 54
 - graviti.dataframe.sql, 56
 - graviti.dataframe.sql.array, 56
 - graviti.dataframe.sql.container, 61
 - graviti.dataframe.sql.operator, 62
 - graviti.dataframe.sql.scalar, 63
- graviti.exception, 240
- graviti.file, 75
 - graviti.file.audio, 75
 - graviti.file.base, 75
 - graviti.file.image, 77
 - graviti.file.image_size, 79
 - graviti.file.point_cloud, 81
- graviti.manager, 81
 - graviti.manager.action, 81
 - graviti.manager.branch, 86
 - graviti.manager.commit, 87
 - graviti.manager.common, 89
 - graviti.manager.dataset, 90
 - graviti.manager.draft, 94
 - graviti.manager.lazy, 97
 - graviti.manager.permission, 101
 - graviti.manager.search, 104
 - graviti.manager.sheets, 106
 - graviti.manager.storage_config, 106
 - graviti.manager.tag, 108
 - graviti.manager.workspace, 109
- graviti.openapi, 110
 - graviti.openapi.action, 110
 - graviti.openapi.branch, 114
 - graviti.openapi.commit, 117
 - graviti.openapi.data, 120
 - graviti.openapi.dataset, 127
 - graviti.openapi.draft, 131
 - graviti.openapi.object, 136
 - graviti.openapi.record, 140
 - graviti.openapi.requests, 146
 - graviti.openapi.schema, 147
 - graviti.openapi.search, 148
 - graviti.openapi.sheet, 154
 - graviti.openapi.storage_config, 159
 - graviti.openapi.tag, 162
 - graviti.openapi.user, 165
 - graviti.openapi.workspace, 166
- graviti.operation, 167
 - graviti.operation.common, 167
 - graviti.operation.frame, 168
 - graviti.operation.sheet, 171
- graviti.paging, 172
 - graviti.paging.factory, 172
 - graviti.paging.lists, 176
 - graviti.paging.offset, 181
 - graviti.paging.page, 182
 - graviti.paging.wrapper, 188
- graviti.portex, 190
 - graviti.portex.avro, 190
 - graviti.portex.base, 193
 - graviti.portex.builder, 197
 - graviti.portex.builtin, 199
 - graviti.portex.enum, 206
 - graviti.portex.external, 208
 - graviti.portex.factory, 209
 - graviti.portex.field, 213
 - graviti.portex.package, 216
 - graviti.portex.param, 218
 - graviti.portex.ptype, 221
 - graviti.portex.register, 224
- graviti.utility, 225
 - graviti.utility.attr, 225
 - graviti.utility.collections, 226
 - graviti.utility.common, 229
 - graviti.utility.engine, 231
 - graviti.utility.itertools, 232

`graviti.utility.log`, [232](#)
`graviti.utility.repr`, [235](#)
`graviti.utility.requests`, [236](#)
`graviti.utility.typing`, [238](#)

A

AccessDeniedError, 242
 Action (class in graviti.manager.action), 82
 ActionManager (class in graviti.manager.action), 82
 actions() (graviti.manager.dataset.Dataset property), 92
 add() (graviti.portex.param.Params method), 220
 add_data() (in module graviti.openapi.data), 125
 add_records() (in module graviti.openapi.record), 144
 add_subpackage() (graviti.portex.package.Imports method), 218
 AddData (class in graviti.operation.frame), 169
 alias (graviti.manager.dataset.Dataset attribute), 91
 all() (graviti.dataframe.sql.array.Array method), 58
 ALL_BRANCHES (in module graviti.manager.common), 90
 allowed_retry_methods (graviti.utility.requests.Config attribute), 236
 allowed_retry_status (graviti.utility.requests.Config attribute), 236
 Any (class in graviti.portex.ptype), 222
 any() (graviti.dataframe.sql.array.Array method), 58
 append() (graviti.manager.lazy.LazyPagingList method), 100
 append() (graviti.utility.collections.UserMutableSequence method), 227
 apply() (graviti.dataframe.frame.DataFrame method), 74
 APPLY_KEY (in module graviti.dataframe.frame), 67
 arguments (graviti.manager.action.Run attribute), 84
 ArithmeticOperatorsMixin (class in graviti.dataframe.sql.array), 57
 ArithmeticOperatorsMixin (class in graviti.dataframe.sql.scalar), 64
 Array (class in graviti.dataframe.sql.array), 57
 array (class in graviti.portex.builtin), 203
 Array (class in graviti.portex.ptype), 222
 ArrayContainer (class in graviti.dataframe.sql.container), 61
 ArrayDistributor (class in graviti.dataframe.sql.array), 60
 ArraySeries (class in graviti.dataframe.column.series), 52

ArraySeries (class in graviti.dataframe.sql.array), 61
 ArrayWrapper (class in graviti.paging.wrapper), 188
 as_py() (graviti.paging.wrapper.ScalarWrapper method), 188
 astype() (graviti.portex.base.PortexRecordBase method), 196
 astype() (graviti.portex.field.ConnectedFields method), 215
 astype() (graviti.portex.field.Fields method), 214
 astype() (graviti.portex.field.FrozenFields method), 213
 AttrDict (class in graviti.utility.attr), 225
 Audio (class in graviti.file.audio), 75
 AvroArray (class in graviti.portex.avro), 192
 AvroField (class in graviti.portex.avro), 191
 AvroPrimitiveSchema (class in graviti.portex.avro), 191
 AvroRecord (class in graviti.portex.avro), 192
 AvroSchema (class in graviti.portex.avro), 191
 AZUREObjectPermissionManager (class in graviti.manager.permission), 102

B

 backend_type (graviti.manager.storage_config.StorageConfig attribute), 107
 binary (class in graviti.portex.builtin), 200
 BinarySeries (class in graviti.dataframe.column.series), 52
 BMP (class in graviti.file.image_size), 80
 boolean (class in graviti.portex.builtin), 200
 Boolean (class in graviti.portex.ptype), 222
 BooleanArray (class in graviti.dataframe.sql.array), 58
 BooleanScalar (class in graviti.dataframe.sql.scalar), 65
 Branch (class in graviti.manager.branch), 86
 branch (graviti.manager.draft.Draft attribute), 95
 branches() (graviti.manager.dataset.Dataset property), 92
 BranchManager (class in graviti.manager.branch), 86
 build() (graviti.portex.builder.PackageBuilder method), 198
 build() (graviti.portex.builder.TypeBuilder method), 198

`build_package()` (in module `graviti.portex.builder`), 198
`BuilderImports` (class in `graviti.portex.builder`), 198
`BuiltinPackage` (class in `graviti.portex.package`), 216
`builtins` (in module `graviti.portex.builtin`), 199

C

`CachedProperty` (class in `graviti.utility.common`), 231
`cancel()` (`graviti.manager.action.Run` method), 84
`cancel_action_run()` (in module `graviti.openapi.action`), 113
`check()` (`graviti.file.image_size.ImageFormatBase` class method), 79
`check()` (`graviti.portex.param.Param` method), 219
`check()` (`graviti.portex.ptype.Enum` static method), 222
`check()` (`graviti.portex.ptype.Fields` static method), 223
`check()` (`graviti.portex.ptype.ParameterType` static method), 221
`check()` (`graviti.portex.ptype.PortexType` static method), 223
`check_head_status()` (in module `graviti.manager.common`), 90
`check_type()` (in module `graviti.utility.typing`), 239
`checkout()` (`graviti.manager.dataset.Dataset` method), 93
`children` (`graviti.manager.action.Node` attribute), 85
`chunked()` (in module `graviti.utility.itertools`), 232
`clear()` (`graviti.utility.collections.UserMutableMapping` method), 228
`clear()` (`graviti.utility.collections.UserMutableSequence` method), 227
`close()` (`graviti.manager.draft.Draft` method), 95
`close()` (`graviti.utility.requests.UserResponse` method), 238
`ColumnSeriesILocIndexer` (class in `graviti.dataframe.column.indexing`), 49
`ColumnSeriesLocIndexer` (class in `graviti.dataframe.column.indexing`), 49
`Commit` (class in `graviti.manager.commit`), 87
`commit` (`graviti.manager.search.SearchHistory` attribute), 104
`commit()` (`graviti.manager.dataset.Dataset` method), 93
`commit()` (`graviti.manager.draft.Draft` method), 95
`commit_draft()` (in module `graviti.openapi.commit`), 117
`commit_id` (`graviti.manager.commit.Commit` attribute), 87
`commit_id` (`graviti.manager.dataset.Dataset` attribute), 92
`CommitManager` (class in `graviti.manager.commit`), 88
`commits()` (`graviti.manager.dataset.Dataset` property), 92
`committed_at` (`graviti.manager.commit.Commit` attribute), 87

`committer` (`graviti.manager.commit.Commit` attribute), 87
`ComparisonOperatorsMixin` (class in `graviti.dataframe.sql.array`), 57
`ComparisonOperatorsMixin` (class in `graviti.dataframe.sql.scalar`), 64
`Config` (class in `graviti.utility.requests`), 236
`config` (in module `graviti.utility.requests`), 237
`config_type` (`graviti.manager.storage_config.StorageConfig` attribute), 107
`ConnectedFields` (class in `graviti.portex.field`), 215
`ConnectedFieldsFactory` (class in `graviti.portex.factory`), 210
`ConstantFactory` (class in `graviti.portex.factory`), 210
`Container` (class in `graviti.dataframe.container`), 66
`ContainerRegister` (class in `graviti.portex.register`), 224
`convert_datetime_to_gmt()` (in module `graviti.utility.common`), 230
`convert_iso_to_datetime()` (in module `graviti.utility.common`), 230
`convert_portex_schema_to_avro()` (in module `graviti.portex.avro`), 193
`copy()` (`graviti.dataframe.container.Container` method), 67
`copy()` (`graviti.paging.lists.MappedPagingList` method), 179
`copy()` (`graviti.paging.lists.PagingListBase` method), 178
`copy()` (`graviti.paging.lists.PyArrowPagingList` method), 180
`copy()` (`graviti.paging.offset.Offsets` method), 181
`copy()` (`graviti.paging.page.MappedLazyPage` method), 186
`copy()` (`graviti.paging.page.MappedLazySlicedPage` method), 187
`copy()` (`graviti.paging.page.MappedPage` method), 185
`copy()` (`graviti.paging.page.MappedPageBase` method), 185
`copy()` (`graviti.paging.page.MappedSlicedPage` method), 186
`copy()` (`graviti.portex.base.PortexType` method), 195
`copy()` (`graviti.portex.field.Fields` method), 215
`copy_objects()` (in module `graviti.openapi.object`), 139
`count()` (`graviti.manager.lazy.LazyPagingList` method), 101
`count()` (`graviti.utility.collections.UserSequence` method), 226
`create()` (`graviti.manager.action.ActionManager` method), 83
`create()` (`graviti.manager.action.RunManager` method), 84
`create()` (`graviti.manager.branch.BranchManager`

- method), 86
- `create()` (graviti.manager.dataset.DatasetManager method), 93
- `create()` (graviti.manager.draft.DraftManager method), 97
- `create()` (graviti.manager.tag.TagManager method), 108
- `create_action()` (in module graviti.openapi.action), 110
- `create_action_run()` (in module graviti.openapi.action), 112
- `create_branch()` (in module graviti.openapi.branch), 114
- `create_dataset()` (in module graviti.openapi.dataset), 127
- `create_draft()` (in module graviti.openapi.draft), 132
- `create_enum_values()` (in module graviti.portex.enum), 207
- `create_list()` (graviti.paging.factory.LazyFactory method), 174
- `create_list()` (graviti.paging.factory.LazyFactoryBase method), 172
- `create_list()` (graviti.paging.factory.LazySubFactory method), 175
- `create_mapped_list()` (graviti.paging.factory.LazyFactory method), 174
- `create_mapped_list()` (graviti.paging.factory.LazyFactoryBase method), 172
- `create_mapped_list()` (graviti.paging.factory.LazySubFactory method), 175
- `create_pyarrow_list()` (graviti.paging.factory.LazyFactory method), 174
- `create_pyarrow_list()` (graviti.paging.factory.LazyFactoryBase method), 172
- `create_pyarrow_list()` (graviti.paging.factory.LazySubFactory method), 175
- `create_search_history()` (in module graviti.openapi.search), 149
- `create_sheet()` (in module graviti.openapi.sheet), 154
- `create_tag()` (in module graviti.openapi.tag), 162
- `created_at` (graviti.manager.dataset.Dataset attribute), 92
- `created_at` (graviti.manager.draft.Draft attribute), 95
- `created_at` (graviti.manager.search.SearchHistory attribute), 104
- `CreateSheet` (class in graviti.operation.sheet), 171
- `creator` (graviti.manager.dataset.Dataset attribute), 92
- `creator` (graviti.manager.draft.Draft attribute), 95
- `creator` (graviti.manager.search.SearchHistory attribute), 104
- `criteria` (graviti.manager.search.SearchHistory attribute), 104
- `CriteriaError`, 241
- `CURRENT_BRANCH` (in module graviti.manager.common), 90
- `CURRENT_COMMIT` (in module graviti.manager.common), 90
- ## D
- `data` (graviti.manager.lazy.LazyItem attribute), 98
- `DataFrame` (class in graviti.dataframe.frame), 67
- `DataFrame` (class in graviti.dataframe.sql.array), 60
- `DataFrameIlocIndexer` (class in graviti.dataframe.indexing), 74
- `DataFrameLocIndexer` (class in graviti.dataframe.indexing), 74
- `DataFrameOperation` (class in graviti.operation.frame), 168
- `DataOperation` (class in graviti.operation.frame), 168
- `Dataset` (class in graviti.manager.dataset), 91
- `DatasetManager` (class in graviti.manager.dataset), 93
- `datasets()` (graviti.manager.workspace.Workspace property), 109
- `date` (class in graviti.portex.builtin), 204
- `DateArray` (class in graviti.dataframe.sql.array), 59
- `DateScalar` (class in graviti.dataframe.sql.scalar), 65
- `default_branch` (graviti.manager.dataset.Dataset attribute), 91
- `default_storage_config()` (graviti.manager.storage_config.StorageConfigManager property), 107
- `DefaultValue` (class in graviti.manager.common), 90
- `delete()` (graviti.manager.action.ActionManager method), 83
- `delete()` (graviti.manager.branch.BranchManager method), 86
- `delete()` (graviti.manager.dataset.DatasetManager method), 94
- `delete()` (graviti.manager.search.SearchManager method), 105
- `delete()` (graviti.manager.tag.TagManager method), 109
- `delete_action()` (in module graviti.openapi.action), 112
- `delete_branch()` (in module graviti.openapi.branch), 116
- `delete_data()` (in module graviti.openapi.data), 126
- `delete_dataset()` (in module graviti.openapi.dataset), 131
- `delete_records()` (in module graviti.openapi.record), 145

- `delete_search_history()` (in module `graviti.openapi.search`), 152
`delete_sheet()` (in module `graviti.openapi.sheet`), 159
`delete_tag()` (in module `graviti.openapi.tag`), 164
`DeleteData` (class in `graviti.operation.frame`), 170
`DeleteSheet` (class in `graviti.operation.sheet`), 171
`description` (`graviti.manager.commit.Commit` attribute), 87
`description` (`graviti.manager.draft.Draft` attribute), 95
`DictFactory` (class in `graviti.portex.factory`), 211
`disable()` (`graviti.manager.action.Action` method), 82
`display_name` (`graviti.manager.action.Node` attribute), 85
`do()` (in module `graviti.openapi.requests`), 146
`Draft` (class in `graviti.manager.draft`), 94
`draft_number` (`graviti.manager.search.SearchHistory` attribute), 104
`DraftManager` (class in `graviti.manager.draft`), 96
`drafts()` (`graviti.manager.dataset.Dataset` property), 92
`dump()` (`graviti.portex.param.Param` method), 219
`dump()` (`graviti.portex.ptype.Enum` static method), 223
`dump()` (`graviti.portex.ptype.Fields` static method), 223
`dump()` (`graviti.portex.ptype.ParameterType` static method), 221
`dump()` (`graviti.portex.ptype.PortexType` static method), 224
`dump_request_and_response()` (in module `graviti.utility.log`), 233
`duration` (`graviti.manager.action.Node` attribute), 85
`duration` (`graviti.manager.action.Run` attribute), 84
- ## E
- `edit()` (`graviti.manager.action.Action` method), 82
`edit()` (`graviti.manager.dataset.Dataset` method), 93
`edit()` (`graviti.manager.draft.Draft` method), 95
`edit()` (`graviti.manager.storage_config.StorageConfigManager` method), 108
`edition` (`graviti.manager.action.Action` attribute), 82
`enable()` (`graviti.manager.action.Action` method), 82
`ended_at` (`graviti.manager.action.Node` attribute), 85
`ended_at` (`graviti.manager.action.Run` attribute), 84
`Engine` (class in `graviti.utility.engine`), 231
`engine` (in module `graviti.utility.engine`), 231
`enum` (class in `graviti.portex.builtin`), 203
`Enum` (class in `graviti.portex.ptype`), 222
`EnumArray` (class in `graviti.dataframe.sql.array`), 58
`EnumScalar` (class in `graviti.dataframe.sql.scalar`), 65
`EnumSeries` (class in `graviti.dataframe.column.series`), 53
`EnumValueDict` (class in `graviti.portex.enum`), 207
`EnumValueList` (class in `graviti.portex.enum`), 207
`EnumValues` (class in `graviti.portex.enum`), 206
`EnumValueType` (in module `graviti.portex.enum`), 206
`EqualOperatorsMixin` (class in `graviti.dataframe.sql.array`), 57
`EqualOperatorsMixin` (class in `graviti.dataframe.sql.scalar`), 64
`execute()` (`graviti.operation.frame.AddData` method), 169
`execute()` (`graviti.operation.frame.DataFrameOperation` method), 168
`execute()` (`graviti.operation.frame.DeleteData` method), 170
`execute()` (`graviti.operation.frame.UpdateData` method), 170
`execute()` (`graviti.operation.frame.UpdateSchema` method), 169
`execute()` (`graviti.operation.sheet.CreateSheet` method), 171
`execute()` (`graviti.operation.sheet.DeleteSheet` method), 171
`execute()` (`graviti.operation.sheet.SheetOperation` method), 171
`extend()` (`graviti.dataframe.frame.DataFrame` method), 72
`extend()` (`graviti.manager.lazy.LazyPagingList` method), 101
`extend()` (`graviti.paging.lists.PagingListBase` method), 177
`extend()` (`graviti.paging.lists.PyArrowPagingList` method), 180
`extend()` (`graviti.paging.offset.Offsets` method), 181
`extend()` (`graviti.utility.collections.UserMutableSequence` method), 227
`extend_iterable()` (`graviti.paging.lists.PagingListBase` method), 177
`extend_nulls()` (`graviti.paging.lists.PagingListBase` method), 178
`extend_nulls()` (`graviti.paging.lists.PyArrowPagingList` method), 180
`extension()` (`graviti.file.base.File` property), 76
`extension()` (`graviti.file.base.FileBase` property), 76
`EXTERNAL_TYPE_TO_CONTAINER` (in module `graviti.portex.builder`), 197
`EXTERNAL_TYPE_TO_CONTAINER` (in module `graviti.portex.external`), 208
`EXTERNAL_TYPE_TO_ELEMENT` (in module `graviti.portex.external`), 208
`ExternalContainerRegister` (class in `graviti.portex.register`), 224
`ExternalElementResgister` (class in `graviti.portex.register`), 225
`ExternalPackage` (class in `graviti.portex.package`), 217

F

- Factory (class in *graviti.portex.factory*), 209
- factory_creator() (in module *graviti.portex.factory*), 212
- field() (*graviti.paging.wrapper.StructArrayWrapper* class method), 189
- FieldFactory (class in *graviti.portex.factory*), 211
- FieldNameConflictError, 240
- Fields (class in *graviti.portex.field*), 214
- Fields (class in *graviti.portex.ptype*), 223
- FieldsFactory (class in *graviti.portex.factory*), 211
- File (class in *graviti.file.base*), 76
- FileBase (class in *graviti.file.base*), 76
- FileSeries (class in *graviti.dataframe.column.series*), 53
- FLIF (class in *graviti.file.image_size*), 80
- float32 (class in *graviti.portex.builtin*), 201
- float64 (class in *graviti.portex.builtin*), 202
- ForbiddenError, 242
- from_array() (*graviti.paging.lists.MappedPagingList* class method), 178
- from_data() (*graviti.manager.lazy.LazyItem* class method), 98
- from_factory() (*graviti.paging.lists.MappedPagingList* class method), 178
- from_factory() (*graviti.paging.lists.PagingList* class method), 178
- from_factory() (*graviti.paging.lists.PyArrowPagingList* class method), 179
- from_items() (*graviti.manager.lazy.LazyPage* class method), 99
- from_json() (*graviti.portex.base.PortexType* class method), 195
- from_page() (*graviti.manager.lazy.LazyItem* class method), 98
- from_pandas() (*graviti.dataframe.column.series.Series* class method), 51
- from_pandas() (*graviti.dataframe.frame.DataFrame* class method), 68
- from_parameter_name() (*graviti.portex.factory.ConnectedFieldsFactory* class method), 210
- from_pyarrow() (*graviti.dataframe.column.series.Series* class method), 50
- from_pyarrow() (*graviti.dataframe.frame.DataFrame* class method), 68
- from_pyarrow() (*graviti.paging.lists.PyArrowPagingList* class method), 179
- from_pyarrow() (*graviti.portex.base.PortexType* class method), 194
- from_pyobj() (*graviti.portex.base.PortexType* class method), 194
- from_pyobj() (*graviti.portex.builder.BuilderImports* class method), 198
- from_pyobj() (*graviti.portex.field.Fields* class method), 214
- from_pyobj() (*graviti.portex.package.Imports* class method), 217
- from_pyobj() (*graviti.portex.package.Subpackage* class method), 217
- from_pyobj() (*graviti.portex.param.Param* class method), 219
- from_pyobj() (*graviti.portex.param.Params* class method), 220
- from_response() (*graviti.manager.commit.Commit* class method), 87
- from_response() (*graviti.manager.commit.NamedCommit* class method), 88
- from_response() (*graviti.manager.storage_config.StorageConfig* class method), 107
- from_upper() (*graviti.dataframe.sql.array.ArrayDistributor* class method), 60
- from_upper() (*graviti.dataframe.sql.container.ArrayContainer* class method), 62
- from_upper() (*graviti.dataframe.sql.container.ScalarContainer* class method), 61
- from_wrapper() (*graviti.paging.wrapper.ListArrayWrapper* class method), 190
- from_wrapper() (*graviti.paging.wrapper.ListScalarWrapper* class method), 189
- from_wrapper() (*graviti.paging.wrapper.StructScalarWrapper* class method), 189
- from_yaml() (*graviti.portex.base.PortexType* class method), 195
- FrozenFields (class in *graviti.portex.field*), 213
- FrozenFieldsFactory (class in *graviti.portex.factory*), 209
- FrozenFieldsFactoryWrapper (class in *graviti.portex.factory*), 210
- FrozenNameOrderedDict (class in *graviti.utility.collections*), 229

G

- get() (*graviti.manager.action.ActionManager* method), 83
- get() (*graviti.manager.action.RunManager* method), 84
- get() (*graviti.manager.branch.BranchManager* method), 86

`get()` (*graviti.manager.commit.CommitManager method*), 88
`get()` (*graviti.manager.dataset.DatasetManager method*), 93
`get()` (*graviti.manager.draft.DraftManager method*), 97
`get()` (*graviti.manager.lazy.LazyItem method*), 98
`get()` (*graviti.manager.search.SearchManager method*), 105
`get()` (*graviti.manager.storage_config.StorageConfigManager method*), 107
`get()` (*graviti.manager.tag.TagManager method*), 109
`get()` (*graviti.paging.wrapper.WrapperRegister class method*), 188
`get()` (*graviti.utility.attr.AttrDict method*), 225
`get()` (*graviti.utility.collections.UserMapping method*), 227
`get_action()` (*in module graviti.openapi.action*), 111
`get_action_run()` (*in module graviti.openapi.action*), 113
`get_action_run_node_log()` (*in module graviti.openapi.action*), 113
`get_array()` (*graviti.paging.factory.LazyFactory method*), 174
`get_array()` (*graviti.paging.factory.LazyLowerCaseFactory method*), 175
`get_array()` (*graviti.paging.page.LazyPage method*), 184
`get_array()` (*graviti.paging.page.LazySlicedPage method*), 184
`get_array()` (*graviti.paging.page.MappedLazyPage method*), 186
`get_array()` (*graviti.paging.page.MappedLazySlicedPage method*), 187
`get_array()` (*graviti.paging.page.Page method*), 183
`get_array()` (*graviti.paging.page.PageBase method*), 182
`get_array()` (*graviti.paging.page.SlicedPage method*), 183
`get_branch()` (*in module graviti.openapi.branch*), 116
`get_checksum()` (*graviti.file.base.File method*), 77
`get_commit()` (*in module graviti.openapi.commit*), 119
`get_commit_sheet()` (*in module graviti.openapi.sheet*), 158
`get_coordinate()` (*graviti.paging.offset.Offsets method*), 181
`get_current_user()` (*in module graviti.openapi.user*), 165
`get_current_workspace()` (*in module graviti.openapi.workspace*), 166
`get_data_count()` (*graviti.operation.frame.DataFrameOperation method*), 168
`get_data_count()` (*graviti.operation.frame.DataOperation method*), 169
`get_dataset()` (*in module graviti.openapi.dataset*), 128
`get_draft()` (*in module graviti.openapi.draft*), 133
`get_draft_sheet()` (*in module graviti.openapi.sheet*), 157
`get_file_count()` (*graviti.operation.frame.DataFrameOperation method*), 168
`get_file_count()` (*graviti.operation.frame.DataOperation method*), 169
`get_image_size()` (*graviti.file.image_size.ImageFormatBase class method*), 80
`get_image_size()` (*in module graviti.file.image_size*), 79
`get_item()` (*graviti.paging.lists.PagingListBase method*), 176
`get_item()` (*graviti.paging.page.PageBase method*), 182
`get_object()` (*graviti.manager.permission.AZUREObjectPermissionManager method*), 103
`get_object()` (*graviti.manager.permission.ObjectPermissionManager method*), 101
`get_object()` (*graviti.manager.permission.OSSObjectPermissionManager method*), 102
`get_object()` (*graviti.manager.permission.S3ObjectPermissionManager method*), 103
`get_object_permission()` (*in module graviti.openapi.object*), 136
`get_offsets()` (*graviti.paging.factory.LazyFactory method*), 174
`get_page_lengths()` (*graviti.paging.factory.LazyFactory method*), 174
`get_revision()` (*in module graviti.openapi.commit*), 120
`get_root()` (*graviti.portex.builder.PackageRepo method*), 197
`get_schema()` (*in module graviti.operation.common*), 167
`get_search_history()` (*in module graviti.openapi.search*), 151
`get_search_record_count()` (*in module graviti.openapi.search*), 152
`get_session()` (*in module graviti.utility.requests*), 238
`get_signature()` (*graviti.portex.param.Params method*), 220
`get_slice()` (*graviti.paging.lists.PagingListBase method*), 176
`get_slice()` (*graviti.paging.lists.PyArrowPagingList method*), 180
`get_slice()` (*graviti.paging.page.LazyPage method*), 184

`get_slice()` (*graviti.paging.page.LazySlicedPage method*), 184
`get_slice()` (*graviti.paging.page.MappedLazyPage method*), 186
`get_slice()` (*graviti.paging.page.MappedLazySlicedPage method*), 187
`get_slice()` (*graviti.paging.page.MappedPage method*), 185
`get_slice()` (*graviti.paging.page.MappedSlicedPage method*), 185
`get_slice()` (*graviti.paging.page.Page method*), 183
`get_slice()` (*graviti.paging.page.PageBase method*), 182
`get_slice()` (*graviti.paging.page.SlicedPage method*), 183
`get_storage_config()` (*in module graviti.openapi.storage_config*), 160
`get_tag()` (*in module graviti.openapi.tag*), 163
`get_type()` (*in module graviti.dataframe.sql.operator*), 63
`get_workspace()` (*in module graviti.openapi.workspace*), 166
GIF (*class in graviti.file.image_size*), 80
GitCommandError, 240
GitNotFoundError, 240
graviti
 module, 49
graviti.dataframe
 module, 49
graviti.dataframe.column
 module, 49
graviti.dataframe.column.indexing
 module, 49
graviti.dataframe.column.series
 module, 50
graviti.dataframe.container
 module, 66
graviti.dataframe.frame
 module, 67
graviti.dataframe.indexing
 module, 74
graviti.dataframe.row
 module, 54
graviti.dataframe.row.indexing
 module, 54
graviti.dataframe.row.series
 module, 54
graviti.dataframe.sql
 module, 56
graviti.dataframe.sql.array
 module, 56
graviti.dataframe.sql.container
 module, 61
graviti.dataframe.sql.operator
 module, 62
graviti.dataframe.sql.scalar
 module, 63
graviti.exception
 module, 240
graviti.file
 module, 75
graviti.file.audio
 module, 75
graviti.file.base
 module, 75
graviti.file.image
 module, 77
graviti.file.image_size
 module, 79
graviti.file.point_cloud
 module, 81
graviti.manager
 module, 81
graviti.manager.action
 module, 81
graviti.manager.branch
 module, 86
graviti.manager.commit
 module, 87
graviti.manager.common
 module, 89
graviti.manager.dataset
 module, 90
graviti.manager.draft
 module, 94
graviti.manager.lazy
 module, 97
graviti.manager.permission
 module, 101
graviti.manager.search
 module, 104
graviti.manager.sheets
 module, 106
graviti.manager.storage_config
 module, 106
graviti.manager.tag
 module, 108
graviti.manager.workspace
 module, 109
graviti.openapi
 module, 110
graviti.openapi.action
 module, 110
graviti.openapi.branch
 module, 114
graviti.openapi.commit
 module, 117
graviti.openapi.data

- module, 120
- graviti.openapi.dataset
 - module, 127
- graviti.openapi.draft
 - module, 131
- graviti.openapi.object
 - module, 136
- graviti.openapi.record
 - module, 140
- graviti.openapi.requests
 - module, 146
- graviti.openapi.schema
 - module, 147
- graviti.openapi.search
 - module, 148
- graviti.openapi.sheet
 - module, 154
- graviti.openapi.storage_config
 - module, 159
- graviti.openapi.tag
 - module, 162
- graviti.openapi.user
 - module, 165
- graviti.openapi.workspace
 - module, 166
- graviti.operation
 - module, 167
- graviti.operation.common
 - module, 167
- graviti.operation.frame
 - module, 168
- graviti.operation.sheet
 - module, 171
- graviti.paging
 - module, 172
- graviti.paging.factory
 - module, 172
- graviti.paging.lists
 - module, 176
- graviti.paging.offset
 - module, 181
- graviti.paging.page
 - module, 182
- graviti.paging.wrapper
 - module, 188
- graviti.portex
 - module, 190
- graviti.portex.avro
 - module, 190
- graviti.portex.base
 - module, 193
- graviti.portex.builder
 - module, 197
- graviti.portex.builtin

- module, 199
- graviti.portex.enum
 - module, 206
- graviti.portex.external
 - module, 208
- graviti.portex.factory
 - module, 209
- graviti.portex.field
 - module, 213
- graviti.portex.package
 - module, 216
- graviti.portex.param
 - module, 218
- graviti.portex.ptype
 - module, 221
- graviti.portex.register
 - module, 224
- graviti.utility
 - module, 225
- graviti.utility.attr
 - module, 225
- graviti.utility.collections
 - module, 226
- graviti.utility.common
 - module, 229
- graviti.utility.engine
 - module, 231
- graviti.utility.itertools
 - module, 232
- graviti.utility.log
 - module, 232
- graviti.utility.repr
 - module, 235
- graviti.utility.requests
 - module, 236
- graviti.utility.typing
 - module, 238
- GravitiException, 240

H

- handler (*in module graviti.manager.dataset*), 91
- head() (*graviti.dataframe.frame.DataFrame method*), 70
- HEAD() (*graviti.manager.dataset.Dataset property*), 92
- height() (*graviti.file.image.Image property*), 78
- height() (*graviti.file.image.RemoteImage property*), 78

I

- ICO (*class in graviti.file.image_size*), 80
- iloc() (*graviti.dataframe.column.series.Series property*), 51
- iloc() (*graviti.dataframe.container.Container property*), 66
- iloc() (*graviti.dataframe.frame.DataFrame property*), 68

[iloc\(\)](#) (*graviti.dataframe.row.series.Series* property), 55
[Image](#) (class in *graviti.file.image*), 77
[Image](#) (in module *graviti.file.image_size*), 79
[ImageDecodeError](#), 240
[ImageFormatBase](#) (class in *graviti.file.image_size*), 79
[Imports](#) (class in *graviti.portex.package*), 217
[imports\(\)](#) (*graviti.portex.base.PortexType* property), 194
[imports\(\)](#) (*graviti.portex.field.Fields* property), 214
[INDENT](#) (in module *graviti.utility.repr*), 235
[index\(\)](#) (*graviti.manager.lazy.LazyPagingList* method), 100
[index\(\)](#) (*graviti.utility.collections.UserSequence* method), 226
[infer_type\(\)](#) (in module *graviti.dataframe.sql.operator*), 63
[InitPage](#) (class in *graviti.manager.lazy*), 99
[insert\(\)](#) (*graviti.manager.lazy.LazyPagingList* method), 100
[insert\(\)](#) (*graviti.portex.base.PortexRecordBase* method), 196
[insert\(\)](#) (*graviti.portex.field.ConnectedFields* method), 215
[insert\(\)](#) (*graviti.portex.field.Fields* method), 214
[insert\(\)](#) (*graviti.portex.field.FrozenFields* method), 213
[insert\(\)](#) (*graviti.utility.collections.UserMutableSequence* method), 227
[int32](#) (class in *graviti.portex.builtin*), 201
[int64](#) (class in *graviti.portex.builtin*), 201
[Integer](#) (class in *graviti.portex.ptype*), 222
[internal_type\(\)](#) (*graviti.portex.external.PortexExternalType* property), 208
[InternalServerError](#), 243
[InvalidParamsError](#), 242
[is_internal](#) (*graviti.utility.requests.Config* attribute), 236
[is_public](#) (*graviti.manager.dataset.Dataset* attribute), 92
[is_valid\(\)](#) (*graviti.paging.wrapper.ScalarWrapper* property), 188
[items](#) (*graviti.manager.lazy.InitPage* attribute), 100
[items](#) (*graviti.manager.lazy.LazyPage* attribute), 99
[items\(\)](#) (*graviti.dataframe.frame.DataFrame* method), 70
[items\(\)](#) (*graviti.manager.sheets.Sheets* method), 106
[items\(\)](#) (*graviti.utility.collections.UserMapping* method), 228
[items\(\)](#) (*graviti.utility.typing.NestedDict* method), 239

J

[JPEG](#) (class in *graviti.file.image_size*), 80
[JPEG2000](#) (class in *graviti.file.image_size*), 80

K

[key\(\)](#) (*graviti.file.base.File* property), 76
[key\(\)](#) (*graviti.file.base.FileBase* property), 76
[keys\(\)](#) (*graviti.dataframe.frame.DataFrame* method), 70
[keys\(\)](#) (*graviti.manager.sheets.Sheets* method), 106
[keys\(\)](#) (*graviti.utility.collections.UserMapping* method), 228

L

[LazyAttr](#) (class in *graviti.utility.common*), 230
[LazyFactory](#) (class in *graviti.paging.factory*), 173
[LazyFactoryBase](#) (class in *graviti.paging.factory*), 172
[LazyItem](#) (class in *graviti.manager.lazy*), 98
[LazyLowerCaseFactory](#) (class in *graviti.paging.factory*), 175
[LazyLowerCaseSubFactory](#) (class in *graviti.paging.factory*), 176
[LazyPage](#) (class in *graviti.manager.lazy*), 99
[LazyPage](#) (class in *graviti.paging.page*), 184
[LazyPagingList](#) (class in *graviti.manager.lazy*), 100
[LazySlicedPage](#) (class in *graviti.paging.page*), 184
[LazySubFactory](#) (class in *graviti.paging.factory*), 175
[LIMIT](#) (in module *graviti.manager.common*), 90
[list\(\)](#) (*graviti.manager.action.ActionManager* method), 83
[list\(\)](#) (*graviti.manager.action.RunManager* method), 85
[list\(\)](#) (*graviti.manager.branch.BranchManager* method), 86
[list\(\)](#) (*graviti.manager.commit.CommitManager* method), 89
[list\(\)](#) (*graviti.manager.dataset.DatasetManager* method), 94
[list\(\)](#) (*graviti.manager.draft.DraftManager* method), 97
[list\(\)](#) (*graviti.manager.search.SearchManager* method), 105
[list\(\)](#) (*graviti.manager.storage_config.StorageConfigManager* method), 108
[list\(\)](#) (*graviti.manager.tag.TagManager* method), 109
[list_action_runs\(\)](#) (in module *graviti.openapi.action*), 112
[list_actions\(\)](#) (in module *graviti.openapi.action*), 111
[list_branches\(\)](#) (in module *graviti.openapi.branch*), 115
[list_commit_data\(\)](#) (in module *graviti.openapi.data*), 123
[list_commit_records\(\)](#) (in module *graviti.openapi.record*), 142
[list_commit_sheets\(\)](#) (in module *graviti.openapi.sheet*), 156
[list_commits\(\)](#) (in module *graviti.openapi.commit*), 118

- `list_datasets()` (in module `graviti.openapi.dataset`), 129
- `list_draft_data()` (in module `graviti.openapi.data`), 121
- `list_draft_records()` (in module `graviti.openapi.record`), 140
- `list_draft_sheets()` (in module `graviti.openapi.sheet`), 155
- `list_drafts()` (in module `graviti.openapi.draft`), 132
- `list_search_histories()` (in module `graviti.openapi.search`), 150
- `list_search_records()` (in module `graviti.openapi.search`), 153
- `list_storage_configs()` (in module `graviti.openapi.storage_config`), 160
- `list_tags()` (in module `graviti.openapi.tag`), 163
- `ListArrayWrapper` (class in `graviti.paging.wrapper`), 190
- `ListFactory` (class in `graviti.portex.factory`), 211
- `ListScalarWrapper` (class in `graviti.paging.wrapper`), 189
- `load()` (`graviti.portex.param.Param` method), 219
- `load()` (`graviti.portex.ptype.Enum` static method), 222
- `load()` (`graviti.portex.ptype.Fields` static method), 223
- `load()` (`graviti.portex.ptype.ParameterType` static method), 221
- `load()` (`graviti.portex.ptype.PortexType` static method), 223
- `loc()` (`graviti.dataframe.column.series.Series` property), 51
- `loc()` (`graviti.dataframe.container.Container` property), 66
- `loc()` (`graviti.dataframe.frame.DataFrame` property), 69
- `loc()` (`graviti.dataframe.row.series.Series` property), 55
- `LocalPackage` (class in `graviti.portex.package`), 216
- `locked()` (in module `graviti.utility.common`), 230
- `locks` (in module `graviti.utility.common`), 230
- `logger` (in module `graviti.manager.dataset`), 91
- `logger` (in module `graviti.utility.requests`), 236
- `LogicalOperatorsMixin` (class in `graviti.dataframe.sql.array`), 57
- `LogicalOperatorsMixin` (class in `graviti.dataframe.sql.scalar`), 64
- `mapping_unpack_factory_creator()` (in module `graviti.portex.factory`), 211
- `max()` (`graviti.dataframe.sql.array.NumberArray` method), 60
- `MAX_REPR_ROWS` (in module `graviti.utility.repr`), 235
- `max_retries` (`graviti.utility.requests.Config` attribute), 236
- `min()` (`graviti.dataframe.sql.array.NumberArray` method), 60
- `Mode` (class in `graviti.utility.engine`), 231
- module
 - `graviti`, 49
 - `graviti.dataframe`, 49
 - `graviti.dataframe.column`, 49
 - `graviti.dataframe.column.indexing`, 49
 - `graviti.dataframe.column.series`, 50
 - `graviti.dataframe.container`, 66
 - `graviti.dataframe.frame`, 67
 - `graviti.dataframe.indexing`, 74
 - `graviti.dataframe.row`, 54
 - `graviti.dataframe.row.indexing`, 54
 - `graviti.dataframe.row.series`, 54
 - `graviti.dataframe.sql`, 56
 - `graviti.dataframe.sql.array`, 56
 - `graviti.dataframe.sql.container`, 61
 - `graviti.dataframe.sql.operator`, 62
 - `graviti.dataframe.sql.scalar`, 63
 - `graviti.exception`, 240
 - `graviti.file`, 75
 - `graviti.file.audio`, 75
 - `graviti.file.base`, 75
 - `graviti.file.image`, 77
 - `graviti.file.image_size`, 79
 - `graviti.file.point_cloud`, 81
 - `graviti.manager`, 81
 - `graviti.manager.action`, 81
 - `graviti.manager.branch`, 86
 - `graviti.manager.commit`, 87
 - `graviti.manager.common`, 89
 - `graviti.manager.dataset`, 90
 - `graviti.manager.draft`, 94
 - `graviti.manager.lazy`, 97
 - `graviti.manager.permission`, 101
 - `graviti.manager.search`, 104
 - `graviti.manager.sheets`, 106
 - `graviti.manager.storage_config`, 106
 - `graviti.manager.tag`, 108
 - `graviti.manager.workspace`, 109
 - `graviti.openapi`, 110
 - `graviti.openapi.action`, 110
 - `graviti.openapi.branch`, 114
 - `graviti.openapi.commit`, 117
 - `graviti.openapi.data`, 120
 - `graviti.openapi.dataset`, 127

M

- `ManagerError`, 241
- `MappedLazyPage` (class in `graviti.paging.page`), 186
- `MappedLazySlicedPage` (class in `graviti.paging.page`), 187
- `MappedPage` (class in `graviti.paging.page`), 185
- `MappedPageBase` (class in `graviti.paging.page`), 184
- `MappedPagingList` (class in `graviti.paging.lists`), 178
- `MappedSlicedPage` (class in `graviti.paging.page`), 185
- `Mapping` (class in `graviti.portex.ptype`), 222

- graviti.openapi.draft, 131
- graviti.openapi.object, 136
- graviti.openapi.record, 140
- graviti.openapi.requests, 146
- graviti.openapi.schema, 147
- graviti.openapi.search, 148
- graviti.openapi.sheet, 154
- graviti.openapi.storage_config, 159
- graviti.openapi.tag, 162
- graviti.openapi.user, 165
- graviti.openapi.workspace, 166
- graviti.operation, 167
- graviti.operation.common, 167
- graviti.operation.frame, 168
- graviti.operation.sheet, 171
- graviti.paging, 172
- graviti.paging.factory, 172
- graviti.paging.lists, 176
- graviti.paging.offset, 181
- graviti.paging.page, 182
- graviti.paging.wrapper, 188
- graviti.portex, 190
- graviti.portex.avro, 190
- graviti.portex.base, 193
- graviti.portex.builder, 197
- graviti.portex.builtin, 199
- graviti.portex.enum, 206
- graviti.portex.external, 208
- graviti.portex.factory, 209
- graviti.portex.field, 213
- graviti.portex.package, 216
- graviti.portex.param, 218
- graviti.portex.ptype, 221
- graviti.portex.register, 224
- graviti.utility, 225
- graviti.utility.attr, 225
- graviti.utility.collections, 226
- graviti.utility.common, 229
- graviti.utility.engine, 231
- graviti.utility.itertools, 232
- graviti.utility.log, 232
- graviti.utility.repr, 235
- graviti.utility.requests, 236
- graviti.utility.typing, 238
- ModuleMocker (class in graviti.utility.common), 231
- N**
- name (graviti.manager.action.Action attribute), 82
- name (graviti.manager.action.Node attribute), 85
- name (graviti.manager.action.Run attribute), 84
- name (graviti.manager.dataset.Dataset attribute), 91
- name (graviti.manager.storage_config.StorageConfig attribute), 107
- NameConflictError, 242
- NamedCommit (class in graviti.manager.commit), 88
- NameOrderedDict (class in graviti.utility.collections), 229
- NestedDict (class in graviti.utility.typing), 239
- NoCommitsError, 241
- Node (class in graviti.manager.action), 85
- node_id (graviti.manager.action.Node attribute), 85
- nodes() (graviti.manager.action.Run method), 84
- NotFoundError, 242
- Number (class in graviti.portex.ptype), 222
- number (graviti.manager.action.Run attribute), 84
- number (graviti.manager.draft.Draft attribute), 94
- NumberArray (class in graviti.dataframe.sql.array), 59
- NumberScalar (class in graviti.dataframe.sql.scalar), 64
- NumberSeries (class in graviti.dataframe.column.series), 52
- NUMERICAL_PRIORITIES (in module graviti.dataframe.sql.scalar), 64
- O**
- ObjectCopyError, 241
- ObjectPermissionManager (class in graviti.manager.permission), 101
- ObjectPermissionManagerType (class in graviti.manager.dataset), 91
- Offsets (class in graviti.paging.offset), 181
- OldPNG (class in graviti.file.image_size), 80
- Online (class in graviti.utility.engine), 231
- online() (graviti.utility.engine.Engine method), 231
- open() (graviti.file.base.File method), 77
- open() (graviti.file.base.FileBase method), 76
- open() (graviti.file.base.RemoteFile method), 77
- open_api_do() (in module graviti.openapi.requests), 147
- OperationError, 241
- OperatorRegister (class in graviti.dataframe.sql.operator), 63
- OPERATORS (in module graviti.dataframe.sql.operator), 62
- OSSObjectPermissionManager (class in graviti.manager.permission), 102
- P**
- Package (class in graviti.portex.package), 216
- PackageBuilder (class in graviti.portex.builder), 197
- PackageRepo (class in graviti.portex.builder), 197
- Packages (class in graviti.portex.package), 217
- packages (in module graviti.portex.package), 217
- Page (class in graviti.paging.page), 183
- page (graviti.manager.lazy.LazyItem attribute), 98
- PageBase (class in graviti.paging.page), 182
- PagingGenerator (in module graviti.manager.lazy), 98
- PagingList (class in graviti.paging.lists), 178
- PagingListBase (class in graviti.paging.lists), 176

- Param (class in *graviti.portex.param*), 218
 param() (in module *graviti.portex.param*), 218
 ParameterType (class in *graviti.portex.ptype*), 221
 Params (class in *graviti.portex.param*), 220
 parent (graviti.manager.commit.Commit attribute), 87
 parent (graviti.manager.draft.Draft attribute), 95
 path() (graviti.file.base.File property), 76
 PathLike (in module *graviti.utility.typing*), 239
 payload (graviti.manager.action.Action attribute), 82
 pd (in module *graviti.dataframe.column.series*), 50
 pd (in module *graviti.dataframe.frame*), 67
 phase (graviti.manager.action.Node attribute), 85
 PNG (class in *graviti.file.image_size*), 80
 PointCloud (class in *graviti.file.point_cloud*), 81
 pop() (graviti.manager.lazy.LazyPagingList method), 100
 pop() (graviti.utility.collections.UserMutableMapping method), 228
 pop() (graviti.utility.collections.UserMutableSequence method), 227
 popitem() (graviti.utility.collections.NameOrderedDict method), 229
 popitem() (graviti.utility.collections.UserMutableMapping method), 228
 PortexBuiltinType (class in *graviti.portex.builtin*), 199
 PortexDate (class in *graviti.portex.avro*), 192
 PortexEnum (class in *graviti.portex.avro*), 192
 PortexError, 240
 PortexExternalType (class in *graviti.portex.external*), 208
 PortexRecordBase (class in *graviti.portex.base*), 196
 PortexTime (class in *graviti.portex.avro*), 192
 PortexTimedelta (class in *graviti.portex.avro*), 193
 PortexTimestamp (class in *graviti.portex.avro*), 193
 PortexType (class in *graviti.portex.base*), 194
 PortexType (class in *graviti.portex.ptype*), 223
 prefix() (graviti.manager.permission.ObjectPermissionManager property), 101
 PType (in module *graviti.portex.ptype*), 222
 pull() (graviti.manager.lazy.LazyPage method), 99
 put_object() (graviti.manager.permission.AZUREObjectPermissionManager method), 103
 put_object() (graviti.manager.permission.ObjectPermissionManager method), 102
 put_object() (graviti.manager.permission.OSSObjectPermissionManager method), 102
 put_object() (graviti.manager.permission.S3ObjectPermissionManager method), 103
 PYARROW_TYPE_ID_TO_PORTEX_TYPE (in module *graviti.portex.base*), 194
 PyArrowConversionRegister (class in *graviti.portex.register*), 225
 PyArrowPagingList (class in *graviti.paging.lists*), 179
 PyarrowSeries (class in *graviti.dataframe.column.series*), 52
 PYTHON_TYPE_TO_PORTEX_TYPE (in module *graviti.dataframe.sql.operator*), 62
- ## Q
- query() (graviti.dataframe.frame.DataFrame method), 73
 query() (graviti.dataframe.sql.array.Array method), 58
 query() (graviti.dataframe.sql.array.DataFrame method), 60
- ## R
- read() (graviti.utility.requests.UserResponse method), 238
 read_json() (in module *graviti.portex.base*), 196
 read_yaml() (in module *graviti.portex.base*), 196
 record (class in *graviti.portex.builtin*), 202
 record_count() (graviti.manager.search.SearchHistory method), 104
 RemoteAudio (class in *graviti.file.audio*), 75
 RemoteFile (class in *graviti.file.base*), 77
 RemoteImage (class in *graviti.file.image*), 78
 RemotePointCloud (class in *graviti.file.point_cloud*), 81
 remove() (graviti.utility.collections.UserMutableSequence method), 227
 rename() (graviti.portex.base.PortexRecordBase method), 196
 rename() (graviti.portex.field.ConnectedFields method), 216
 rename() (graviti.portex.field.Fields method), 214
 rename() (graviti.portex.field.FrozenFields method), 213
 repo() (graviti.portex.package.ExternalPackage property), 217
 repr_config (in module *graviti.utility.repr*), 235
 ReprMixin (class in *graviti.utility.repr*), 235
 ReprType (class in *graviti.utility.repr*), 235
 request() (graviti.utility.requests.UserSession method), 237
 REQUEST_TEMPLATE (in module *graviti.utility.log*), 233
 RequestLogging (class in *graviti.utility.log*), 233
 RequestParamsMissingError, 242
 required() (graviti.portex.param.Param property), 219
 ResourceNameError, 241
 ResourceNotExistError, 243
 response (graviti.exception.ResponseError attribute), 241
 RESPONSE_ERROR_DISTRIBUTOR (in module *graviti.openapi.requests*), 146
 RESPONSE_TEMPLATE (in module *graviti.utility.log*), 233
 ResponseError, 241
 ResponseErrorRegister (class in *graviti.exception*), 242

- ResponseLogging (class in *graviti.utility.log*), 233
 ReturnGenerator (class in *graviti.manager.lazy*), 99
 reverse() (*graviti.manager.lazy.LazyPagingList* method), 100
 reverse() (*graviti.utility.collections.UserMutableSequence* method), 227
 RevisionType (class in *graviti.manager.dataset*), 91
 RowSeries (class in *graviti.dataframe.sql.scalar*), 66
 RowSeriesILocIndexer (class in *graviti.dataframe.row.indexing*), 54
 RowSeriesLocIndexer (class in *graviti.dataframe.row.indexing*), 54
 Run (class in *graviti.manager.action*), 83
 run() (*graviti.manager.search.SearchHistory* method), 105
 RunManager (class in *graviti.manager.action*), 84
 runs() (*graviti.manager.action.Action* property), 82
- ## S
- S3ObjectPermissionManager (class in *graviti.manager.permission*), 103
 ScalarContainer (class in *graviti.dataframe.sql.container*), 61
 ScalarWrapper (class in *graviti.paging.wrapper*), 188
 schema() (*graviti.manager.search.SearchHistory* method), 105
 search_id (*graviti.manager.search.SearchHistory* attribute), 104
 SearchContainerRegister (class in *graviti.dataframe.sql.container*), 62
 searches() (*graviti.manager.dataset.Dataset* property), 92
 SearchHistory (class in *graviti.manager.search*), 104
 SearchManager (class in *graviti.manager.search*), 105
 send() (*graviti.utility.requests.TimeoutHTTPAdapter* method), 237
 Series (class in *graviti.dataframe.column.series*), 50
 Series (class in *graviti.dataframe.row.series*), 54
 ServiceUnavailableError, 243
 SESSIONS (in module *graviti.utility.requests*), 238
 set_item() (*graviti.paging.lists.PagingListBase* method), 177
 set_slice() (*graviti.paging.lists.PagingListBase* method), 177
 set_slice() (*graviti.paging.lists.PyArrowPagingList* method), 180
 set_slice_iterable() (*graviti.paging.lists.PagingListBase* method), 177
 setdefault() (*graviti.utility.collections.UserMutableMapping* method), 228
 setdefault() (*graviti.utility.typing.NestedDict* method), 239
 shape() (*graviti.dataframe.frame.DataFrame* property), 69
 sheet (*graviti.manager.search.SearchHistory* attribute), 104
 SheetOperation (class in *graviti.operation.sheet*), 171
 Sheets (class in *graviti.manager.sheets*), 106
 shorten() (in module *graviti.utility.common*), 230
 size() (*graviti.dataframe.frame.DataFrame* property), 70
 size() (*graviti.dataframe.sql.array.NumberArray* method), 60
 size() (*graviti.file.base.File* property), 77
 size() (*graviti.file.base.FileBase* property), 76
 SlicedPage (class in *graviti.paging.page*), 183
 SortParam (in module *graviti.utility.typing*), 239
 STANDARD_URL (in module *graviti.portex.register*), 224
 started_at (*graviti.manager.action.Node* attribute), 85
 started_at (*graviti.manager.action.Run* attribute), 84
 state (*graviti.manager.action.Action* attribute), 82
 state (*graviti.manager.draft.Draft* attribute), 94
 status (*graviti.manager.action.Run* attribute), 84
 StatusError, 241
 StatusWarning, 90
 storage_config (*graviti.manager.dataset.Dataset* attribute), 92
 storage_configs() (*graviti.manager.workspace.Workspace* property), 109
 StorageConfig (class in *graviti.manager.storage_config*), 106
 StorageConfigManager (class in *graviti.manager.storage_config*), 107
 string (class in *graviti.portex.builtin*), 199
 String (class in *graviti.portex.ptype*), 222
 string_factory_creator() (in module *graviti.portex.factory*), 212
 StringArray (class in *graviti.dataframe.sql.array*), 58
 StringScalar (class in *graviti.dataframe.sql.scalar*), 65
 StringSeries (class in *graviti.dataframe.column.series*), 52
 StructArrayWrapper (class in *graviti.paging.wrapper*), 189
 StructScalarWrapper (class in *graviti.paging.wrapper*), 188
 submit_multithread_tasks() (in module *graviti.utility.requests*), 238
 Subpackage (class in *graviti.portex.package*), 217
 sum() (*graviti.dataframe.sql.array.NumberArray* method), 60
 Tag (class in *graviti.manager.tag*), 108
 TagManager (class in *graviti.manager.tag*), 108
 tags() (*graviti.manager.dataset.Dataset* property), 92

- `tail()` (*graviti.dataframe.frame.DataFrame* method), 71
- `TemporalArrayBase` (class in *graviti.dataframe.sql.array*), 58
- `TemporalScalarBase` (class in *graviti.dataframe.sql.scalar*), 65
- `TIFF` (class in *graviti.file.image_size*), 80
- `time` (class in *graviti.portex.builtin*), 204
- `TimeArray` (class in *graviti.dataframe.sql.array*), 59
- `timedelta` (class in *graviti.portex.builtin*), 205
- `TimedeltaArray` (class in *graviti.dataframe.sql.array*), 59
- `TimedeltaScalar` (class in *graviti.dataframe.sql.scalar*), 66
- `timeout` (*graviti.utility.requests.Config* attribute), 236
- `TimeoutHTTPAdapter` (class in *graviti.utility.requests*), 237
- `TimeScalar` (class in *graviti.dataframe.sql.scalar*), 65
- `TimeSeries` (class in *graviti.dataframe.column.series*), 53
- `timestamp` (class in *graviti.portex.builtin*), 205
- `TimestampArray` (class in *graviti.dataframe.sql.array*), 59
- `TimestampScalar` (class in *graviti.dataframe.sql.scalar*), 66
- `title` (*graviti.manager.commit.Commit* attribute), 87
- `title` (*graviti.manager.draft.Draft* attribute), 95
- `to_builtin()` (*graviti.portex.base.PortexType* method), 195
- `to_builtin()` (*graviti.portex.builtin.PortexBuiltinType* method), 199
- `to_builtin()` (*graviti.portex.external.PortexExternalType* method), 208
- `to_json()` (*graviti.portex.avro.AvroArray* method), 192
- `to_json()` (*graviti.portex.avro.AvroField* method), 191
- `to_json()` (*graviti.portex.avro.AvroPrimitiveSchema* method), 191
- `to_json()` (*graviti.portex.avro.AvroRecord* method), 192
- `to_json()` (*graviti.portex.avro.AvroSchema* method), 191
- `to_json()` (*graviti.portex.avro.PortexDate* method), 192
- `to_json()` (*graviti.portex.avro.PortexEnum* method), 192
- `to_json()` (*graviti.portex.avro.PortexTime* method), 193
- `to_json()` (*graviti.portex.avro.PortexTimedelta* method), 193
- `to_json()` (*graviti.portex.avro.PortexTimestamp* method), 193
- `to_json()` (*graviti.portex.base.PortexType* method), 195
- `to_pandas()` (*graviti.dataframe.column.series.ArraySeries* method), 53
- `to_pandas()` (*graviti.dataframe.column.series.EnumSeries* method), 53
- `to_pandas()` (*graviti.dataframe.column.series.FileSeries* method), 53
- `to_pandas()` (*graviti.dataframe.column.series.PyarrowSeries* method), 53
- `to_pandas()` (*graviti.dataframe.column.series.PyarrowSeries* method), 52
- `to_pandas()` (*graviti.dataframe.column.series.Series* method), 52
- `to_pandas()` (*graviti.dataframe.container.Container* method), 67
- `to_pandas()` (*graviti.dataframe.frame.DataFrame* method), 73
- `to_pyarrow()` (*graviti.paging.lists.PyArrowPagingList* method), 180
- `to_pyarrow()` (*graviti.portex.base.PortexRecordBase* method), 196
- `to_pyarrow()` (*graviti.portex.base.PortexType* method), 195
- `to_pyarrow()` (*graviti.portex.builtin.array* method), 204
- `to_pyarrow()` (*graviti.portex.builtin.binary* method), 200
- `to_pyarrow()` (*graviti.portex.builtin.boolean* method), 200
- `to_pyarrow()` (*graviti.portex.builtin.date* method), 204
- `to_pyarrow()` (*graviti.portex.builtin.enum* method), 203
- `to_pyarrow()` (*graviti.portex.builtin.float32* method), 202
- `to_pyarrow()` (*graviti.portex.builtin.float64* method), 202
- `to_pyarrow()` (*graviti.portex.builtin.int32* method), 201
- `to_pyarrow()` (*graviti.portex.builtin.int64* method), 201
- `to_pyarrow()` (*graviti.portex.builtin.record* method), 203
- `to_pyarrow()` (*graviti.portex.builtin.string* method), 200
- `to_pyarrow()` (*graviti.portex.builtin.time* method), 205
- `to_pyarrow()` (*graviti.portex.builtin.timedelta* method), 206
- `to_pyarrow()` (*graviti.portex.builtin.timestamp* method), 205
- `to_pyarrow()` (*graviti.portex.enum.EnumValueDict* method), 207
- `to_pyarrow()` (*graviti.portex.enum.EnumValueList* method), 207
- `to_pyarrow()` (*graviti.portex.enum.EnumValues* method), 207
- `to_pyarrow()` (*graviti.portex.external.PortexExternalType* method), 208
- `to_pyarrow()` (*graviti.portex.field.Fields* method), 215
- `to_pylist()` (*graviti.dataframe.column.series.ArraySeries* method), 52
- `to_pylist()` (*graviti.dataframe.column.series.EnumSeries* method), 53
- `to_pylist()` (*graviti.dataframe.column.series.FileSeries* method), 53
- `to_pylist()` (*graviti.dataframe.column.series.PyarrowSeries* method), 52

[to_pylist\(\)](#) (*graviti.dataframe.column.series.Series* method), 52
[to_pylist\(\)](#) (*graviti.dataframe.column.series.TimeSeries* method), 53
[to_pylist\(\)](#) (*graviti.dataframe.container.Container* method), 67
[to_pylist\(\)](#) (*graviti.dataframe.frame.DataFrame* method), 73
[to_pyobj\(\)](#) (*graviti.portex.base.PortexType* method), 195
[to_pyobj\(\)](#) (*graviti.portex.enum.EnumValueDict* method), 207
[to_pyobj\(\)](#) (*graviti.portex.enum.EnumValueList* method), 207
[to_pyobj\(\)](#) (*graviti.portex.enum.EnumValues* method), 206
[to_pyobj\(\)](#) (*graviti.portex.field.Fields* method), 215
[to_pyobj\(\)](#) (*graviti.portex.package.Imports* method), 218
[to_pyobj\(\)](#) (*graviti.portex.package.Subpackage* method), 217
[to_pyobj\(\)](#) (*graviti.portex.param.Param* method), 219
[to_pyobj\(\)](#) (*graviti.portex.param.Params* method), 220
[to_yaml\(\)](#) (*graviti.portex.base.PortexType* method), 195
[total_count](#) (*graviti.manager.lazy.InitPage* attribute), 100
[transform_kwargs\(\)](#) (*graviti.portex.factory.TypeFactory* method), 210
[type_factory_creator\(\)](#) (in module *graviti.portex.factory*), 212
[TypeBuilder](#) (class in *graviti.portex.builder*), 198
[TypeFactory](#) (class in *graviti.portex.factory*), 210
[tz_checker](#) (in module *graviti.portex.builtin*), 199

U

[UnauthorizedError](#), 243
[UnionFields](#) (in module *graviti.portex.field*), 215
[UnionFieldsFactory](#) (in module *graviti.portex.factory*), 210
[update\(\)](#) (*graviti.paging.offset.Offsets* method), 181
[update\(\)](#) (*graviti.portex.package.Imports* method), 217
[update\(\)](#) (*graviti.portex.param.Params* method), 220
[update\(\)](#) (*graviti.utility.collections.UserMutableMapping* method), 229
[update_action\(\)](#) (in module *graviti.openapi.action*), 111
[update_data\(\)](#) (in module *graviti.openapi.data*), 124
[update_dataset\(\)](#) (in module *graviti.openapi.dataset*), 130
[update_draft\(\)](#) (in module *graviti.openapi.draft*), 134
[update_records\(\)](#) (in module *graviti.openapi.record*), 143
[update_schema\(\)](#) (in module *graviti.openapi.schema*), 147
[update_storage_configs\(\)](#) (in module *graviti.openapi.storage_config*), 161
[updated_at](#) (*graviti.manager.dataset.Dataset* attribute), 92
[updated_at](#) (*graviti.manager.draft.Draft* attribute), 95
[UpdateData](#) (class in *graviti.operation.frame*), 170
[UpdateSchema](#) (class in *graviti.operation.frame*), 169
[upload\(\)](#) (*graviti.manager.draft.Draft* method), 96
[url\(\)](#) (*graviti.manager.action.Run* property), 84
[urlnorm\(\)](#) (in module *graviti.utility.common*), 230
[UserMapping](#) (class in *graviti.utility.collections*), 227
[UserMutableMapping](#) (class in *graviti.utility.collections*), 228
[UserMutableSequence](#) (class in *graviti.utility.collections*), 226
[UserResponse](#) (class in *graviti.utility.requests*), 238
[UserSequence](#) (class in *graviti.utility.collections*), 226
[UserSession](#) (class in *graviti.utility.requests*), 237
[UtilityError](#), 240

V

[value](#) (*graviti.manager.lazy.ReturnGenerator* attribute), 99
[values\(\)](#) (*graviti.manager.sheets.Sheets* method), 106
[values\(\)](#) (*graviti.paging.wrapper.ListScalarWrapper* property), 189
[values\(\)](#) (*graviti.utility.collections.UserMapping* method), 228
[VariableFactory](#) (class in *graviti.portex.factory*), 211

W

[WebP](#) (class in *graviti.file.image_size*), 80
[width\(\)](#) (*graviti.file.image.Image* property), 78
[width\(\)](#) (*graviti.file.image.RemoteImage* property), 78
[Workspace](#) (class in *graviti.manager.workspace*), 109
[workspace](#) (*graviti.manager.dataset.Dataset* attribute), 91
[WrapperRegister](#) (class in *graviti.paging.wrapper*), 188